



Machine Introduction

Structure and Feature:

- ★ Adopt suction structure with high pressure strong fan. Air suction device with sound, the air source and electrical control are on the same operation counters, the distance from the host machine will not be less than 1.5 meters, operating side closed all the hood.
- ★ Engine base and wallboard adopt cast iron structure, the thickness of wallboard is 130 mm. independent gear box, gimble transmission.
- ★ Corrugated roller adopts 48 CrMo alloy steel, treated by tempering, laser quenching and surface polishing. Corrugated roller diameter is $\Phi 320$ mm, surface hardness is above HRC60 degrees. The bearings of the corrugated roller and pressure roller in the key part use in wafangdian high temperature resistant bearing.
- ★ Pressure roller is $\Phi 315$ mm, surface is grinded and processed by chromium; Cylinder control moving, the material is medium-carbon steel 45, quenching and tempering treatment (with buffer device).
- ★ Glue wallboard adopts slide structure, pneumatic control the glue, glue roller diameter is $\Phi 216$ mm surface is treated by polishing and hard chromium plating. The glue-scraping roller surface is polished and treated by hard chromium.
- ★ Glue part can move bodily, replace glue roller quickly and conveniently. Electric adjustment glue spread quantities.
- ★ Corrugated roller, pressure roller raw materials provided by Zhongyuan special steel, corrugated roller unilateral 0.15 mm high on, pressure roller unilateral 0.075 mm high. Add limiting device.
- ★ Pressure cylinder uses $\Phi 284$ mm cylinder.
- ★ Preheating roller adopts $\Phi 270$ mm and $\Phi 320$ mm seamless steel tube which is produced by Tianjin Iron and Steel Group Co., Ltd, all with metal hose connection.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



Technical Specifications

Model	OG-1600
Corrugated Rollers	Φ 320mm
Press Rollers	Φ 320mm
Glue Rollers	Φ 216mm
Preheater	Φ270 mm and Φ320 mm
Working width	1600mm
Operation Direction	Left or right (decided by the workshop of customer)
Machinery Speed	100m/min
Temperature	160—200°C
Air pressure	0.4—0.9Mpa
Steam Pressure	0.8—1.3Mpa
Corrugated Flute Type	UV or UVV
Draw Fan Motor	11kw Nominal voltage: 380V 50Hz Continuous (S1) working
Main Motor	11kw Nominal voltage: 380V 50Hz Continuous (S1) working

Part List

No	Part Name	Brand or Origin	Material
1	Wallboard & Foundation Plate	Xinhua	HT200
2	Drive Box	Xinhua	
3	Rotating Joint & Flexible Metallic Tube	Shandong Tengzhou Rotating Joint Factory	
4	Main Motor	Hebei hengshui	
5	Inverter	SINEE	
6	Electric	CHINT	

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657



OG-1600

Single Facer Corrugated Machine



* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

