



Machine Introduction

SWAFM-1050 automatic laminator is updated laminating machine for film and paper lamination. The machine is equipped with complete automation to paper feed, lamination, paper separation, delivery and temperature control. The electrics and pneumatics are controlled by PLC (programmable control) system, and can be operated easily in touch screen. Heating roller adopts electromagnetic heater. To meet users' different requirements, delivery section is optional for stacker. This machine centralizes the features of high automation, high precision of lamination, humanized configuration and easy operation, and is the best choice with high-cost performance for large and medium-size enterprises.

Configuration:

1. Automatic paper feeder adopts oil-free vacuum pump and pre-stacker to feed paper automatically. Paper can be added meanwhile the machine is working, which improves working efficiency
2. Man-machine interface system: color touch screen simplifies the machine operation. On the touch screen, as long as the operator inputs paper size, overlap length and working speed etc., the machine can realize completely automated operation. And on touch screen, working status of the machine can be checked at any time.
3. Automatic feeding system is equipped with no sheet protector, paper break protector and paper superposing protector, which are controlled by photoelectric and mechanical systems. When paper is miss or break, the machine stops automatically for self-protection.
4. Side lay and front lay. The Servo controller front lay and side lay mechanism guarantees precise paper alignment at all times.
5. Feeder vacuum table is furnished with air aspirator and front lay etc. to regulate paper conveying and overlap and improve lamination prevision.
6. 320mm diameter with high-precision chrome plated heating roller is equipped with electromagnetic heater, which is safe fast pre-heating energy saving and environmental protection. The laminating temperature is adjustable upon applications.
7. Hydraulic pressuring system provides automatically big and steady pressure to guarantee good laminating quality.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.





PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



8. Air shaft releases film, and perfects the precision of film release, and also makes the loading and unloading of film roll much more convenient. The combination of air expansion shaft and braking device can adjust film release tension and release speed.
9. Space between separation section and laminator section, which makes the machine maintenance easier
10. Pneumatic separation system realizes automatic paper cut as long as the operator inputs the size of workable paper on the touch screen.
11. Corrugating belt makes the paper collection more easily and regular.
12. Automatic delivery (auto stacker) is standard.

Features

Auto Feeder This machine is equipped with a paper pre-stacker, servo-controlled feeder and a photoelectric sensor to ensure that paper is continuously fed into the machine		Electromagnetic Heater Equipped with advanced electromagnetic heater. Fast pre-heating. Energy saving. Environmental protection.	
Side Lay Regulator The servo controller and side lay mechanism guarantees precise paper alignment at all times.		Human-computer interface A user-friendly interface system with a colour touch-screen simplifies the operation process. The operator can easily and automatically control paper sizes, overlapping and machine speeds.	
Anti-curvature Device The machine is equipped with an anti-curl device, which ensures that paper remains flat and smooth during the lamination process.		Separation System Pneumatic separation system to separate the paper stably and quickly.	
Corrugated Delivery A corrugated delivery system collect paper easily		Automatic Stacker Automatic stacker receive the sheets quickly in order without stop the machine as well as counter the sheets	
Film Loader Operating the film loader is easy and efficient to use.			

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



Technical Specifications

Model	SWAFM-1050
Max. paper size	1050x820mm
Min. paper size	300x300mm
Laminating speed	0-80m/min
Paper thickness	90-600gsm
Gross power	35/18kw
Overall dimensions	5200x2200x1900mm
Pre-stacker Length	1850mm
Weight	3800Kgs

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO

Jl. Terusan Bandengan Utara No.16 / B 3-4

Jakarta, 14450, Indonesia

Tel. (021) 660 2665, 661 8255.

Fax. (021) 668 5874, 660 2657

