



Machine Introduction

Features:

1. Feida automatic paper feeder can adjust the parameters according to the paper size.
2. Equipped with a high-speed offset press dedicated feida head. (Accurate and smooth paper feeding)
3. Air pump adopts no oil pump.
4. There are suction and wheel pressure under the paper feeding table.
5. Main engine wallboard cast iron structure, 6 paper inlet belts and 2 paper outlet belts with suction underneath.
6. The coating roller adopts the rolling extrusion oil and reverse oil (the latter is used when making dumb oil and tissue paper).
7. The paper feeding position is equipped with optical fiber probe for accurate memory of paper feeding.
8. The coating cots are equipped with optical fiber, in order to protect the cots, the paper will automatically stop.
9. Thin paper USES air knife to blow qigong energy, optical fiber and encoder to control solenoid valve.
10. The oven is equipped with a standard of 5 meters (customized according to customer requirements). The oven heating lid will automatically rise and fall when the machine is shut down or started up.
11. The mesh belt is high temperature resistant and automatic edge correction.
12. Part of the paper receiving machine: 6 strips of paper feeding belt (with suction) are pressed into corrugated form with the upper pressing wheel to improve the paper receiving effect, and there is qigong blowing energy below.
13. The touch screen adopts manual automatic integrated screen switching. (The device can be operated manually or automatically)
14. Automatic intelligent identification system. (When the machine runs automatically, the oven heating, fan, temperature and oil quantity can be adjusted appropriately according to the product)
15. High-precision sensor detection system. (It can accurately detect empty sheets and double sheets, standby or stop according to different situations)
16. Diversified instrument display. (Can display presets, cumulative count; Meter, linear speed, efficiency, etc.)

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



Technical Specifications

Model	CYSG-1200B
Min. paper size	310×280MM
Max. paper size	1100MM×1100MM
Dryer way	IR/UV
Speed	5-80M/min
IR Drying Tunnel	IR light 30-100°C power1.5KW/18pcs
IR Fan	8pcs
IR Power	27KW
UV Tunnel	UV power 8KW/3pcs
Total Power	48kw
Weight	5500kg
Dimension	11000*2000*1850mm

Configurations

Name	Remarks
Frequency	Taida
Paper weight	80g-600g
Feeder	Taida
Pump	Shanggang 80m ² /n
PLC	Taida
Low voltage	Schneider
Touch Screen	Taida
Solenoid valve	Yadeke
Bearing	NSK
Quartz tube	HONGDA
Blower	Chuangda
Motor	Shanggang 80m ² /n
Tunnel	5000mm × 1pcs
Glue Barrel	2pcs
Glue Pump	2pcs
Glue dish	2pcs

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

