



Machine Introduction

Features of Computer:

1. Nc model (manual operation)
2. SPC model (self-motion)
3. Position programming (operator input program)
4. Sample programming (operator can save the data according to the position of the material to be cut, which is suitable for the situation that it is difficult to obtain the accurate cutting size)
5. Cut and program in equal parts (division programming, total dimensions divided by number of shares.
6. Absolute position programming (add and subtract numbers)
7. Isometric programming (multiplication programming is used when a large number of equidistant cuts are required)
8. Modify data (reprogramming)
9. Parameter setting mode
10. Automatic cutting selection
11. Fault indication
12. Platform air cushion control of paper cutter
13. Paper choose ("0"-Yes "1"-No)
14. Unit selection (mm, cm, inch)

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

36 YEARS
SERVING
INDONESIA

Main Performance Characteristic and Configuration:

1. Symmetrical shape, nice shape, solid structure of the gantry machine frame;
2. Slot less, chrome plated, double rail countertop ensures easy and accurate cutting;
3. The display screen adopts Hitachi 7-inch color screen;
4. Computer chip uses Japan Fujitsu, frequency conversion module uses Japan Mitsubishi company;
5. Main components of low voltage electrical appliances are French Schneider;
6. Micro switch using Japan OMRON;
7. Blade changing switch using French Schneider;
8. Adopt quick oil cylinder designed by Germany, the main hydraulic components adopt Taiwan Chaotian company;
9. Convenient and reliable automatic feeding structure ensures safe feeding;
10. Work stable is equipped with air cushion device to facilitate paper pushing;
11. Adopt the high-performance electromagnetism of Hefei clutch factory of Beijing machine tool research institution, clutch is safe and reliable;
12. Main motor and hydraulic motor are independent, stable and reliable pressure.

Main Technical Specifications

Model	QZK-205
Maximum cutting width (mm/inches)	920/36"
Max. Cutting length (mm/inches)	920/36"
Max. Cutting height (mm/inches)	120/4.7"
Maximum pressure (N)	30000
Cutting speed (time/min)	40
Motor power (KW)	3
Net weight (kg)	1800
Overall dimensions (mm) (L-W-H)	3000x1340x1830

Other Parameters

Min. Cutting depth (without clamp)	2.5cm
length of work table	62cm
Height of work table	88cm
Machine width (including side table)	182cm
Worktable length	200cm
Maximum pressure	≥30000N
Back gauge motor	0.37KW
Air pump	0.75KW
Hydraulic motor	1.5KW

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

36 YEARS
SERVING
INDONESIA

Accessories and Spare Parts

No.	Name	Qty	Specification	Note
1	Blade	2	12.7*127*1520mm	One of them has been installed on the machine
2	Cylinder	1		
3	Blade handle	2		
4	Jiggle bar	1		
5	Air tap	10		
6	Blade-replacement wrench	1		Blade change
7	Bent nails	1		
8	Solid wrench	2	13-16, 30, 46mm	One for each specification
9	Allen wrench	8	2.5, 3, 4, 5, 6, 8, 10, 12mm	One for each specification
10	Adjustable spanner	2	12"	one piece
11	Screwdriver	2	cross 4"	one piece
12	Oilcan	1		
13	Hexagon bolt	9	M12X22mm	
14	Operation instruction	1		
15	Blade strip	2		One of them has been installed on the machine
16	Safety bolt	1		

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

36 YEARS
SERVING
INDONESIA