



Machine Parts



Sealing balde



Heating tunnel



Driving rollers



Touch panel



Waste plastic collection



Transporting film structure

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



Technical Specifications

Model	GPL-4535IM	GPS-4525
Machine dimension	L1740×W1265×H1310mm	L1300×W715×H1455mm
Packaging Size	1880*1370*1480mm	1450*830*1170mm
Packing size	L+H≤450/W+H≤350mm (H≤100mm)	L700×W350×H150mm
Cutter size/ tunnel size	L555×W450mm	L1000×W450×H250mm
Customer product size		
Packing speed	10~15Pcs/min	20~40Pcs/min
Power	2KW	10KW
Power supply	220V/ 50/ 60Hz, 1Phase	380V 50/ 60Hz, 3 Phase
Air pressure	5.5kg/cm ³	/
Max current	10A	30A
Material	POF	POF
Machine direction	Right to left	Right to left
Net weight	420kg	185kg
Table height	850+30mm	850+30mm

Configuration List

Item	Origin
PLC	Germany Siemens
Sensor	USA Banner
Intermediate Relay	Japan IDEC
Temperature Controller	Japan OMRON
Contactor	France SCHNEIDER
Motor	Taiwan GPG&VTV
Pneumatic Parts	Air TAC
Speed controller	Taiwan VTV
Belts	Diamond pattern

Summarize:

- Automatic L-bar sealing machine: GPL-4535I, Qty 1, Standard
- Shrink machine: GPS-4525, Qty 1, Standard
- The front powered belt: 1000*450mm, Qty 1, Optional
- The rear unpowered drum conveyor: 1000*450mm, Qty 1, Optional

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

