



Machine Introduction

Features:

1. The main motor adopts imported converter to govern in a steepless way.
2. Feeding and discharging are controlled through magnetic powder brake and clutch (Japanese Mitsubishi aut tension controller).
3. Unhindered system is controlled by auto rectify sensor.
4. Adopt ceramic mesh distributor roller, which is characterized by durability , wear resistance, and corrosion resistance, The doctors can be Used, which is more efficient for reducing the times for changing in order to increase the production efficiency.
5. The printing unit can register in 360degrees. Each printing unit can independently gear and loosen to have the units continue printing.
6. The printing units are all equipped with a group of infrared dryers respectively.
7. Each IR dryer device of printing unit can interchange of UV dryer device.
8. The roofing device is adopted with a group of infrared dryers respectively.
9. The inking roller can automatically fall off at stoppage and transfer at low speed in order to keep the ink from being dry and solid.
10. The roll feeding, printing, auto infrared drying. Laminating and rolling can be processed in one processing. Lt is characterized by wide application, non-population of printing ink and fast drying, quick printing. So it is an ideal printing machine for the commercial bill to print high Graded free adhesive trademark.
11. The scraping blade is used to improve ink filling, and at the same time it can prevent splashing ink hurting working people.
12. The camera with display can show people the image of the sticker.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

33 YEARS
SERVING
INDONESIA

Technical Specifications

Web width	330mm
Print width	320mm
Unwind Diameter max	600mm
Rewind Diameter max	600mm
Press Speed max (Production speed depending on process, job etc.)	80m/min
Gear Pitch	1/8" (3.175mm)
Flexo Print Units (IR dryer):	2
Die-Cutting Units: number	1
Min.Max repeat Print Cylinder	7" - 13.5"
Web Guiding: number	1
Turn Bar: number	1
Lamination Unit: number	1
Waste Rewinder: number	1
Automatic tension : number	2
Magnetic Powder : number	3
Roll : number	2
Voltage	3 phase 380V, 50HZ
Diameter of air shafts	76mm
Diameter of printing plate	1.7mm
Diameter of plate mounting tape	0.38mm
Simple paste version machine	One
Ceramic anilox roller	2 pcs, lines from 200-1000 choose by buyer
Printing roller	2 pieces * 3 sets =6 pcs, (buyer offers dimension)
Unwinding tension controller	ZXT-B600
Rewinding tension controller	ZXT-B600
Temperature controller	XMTG-6501
Main motor	2.2KW
Web guiding	1
Automatic tension	2
Magnetic Powder	3
Roll	2

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

33 YEARS
SERVING
INDONESIA