



Machine Introduction

Leading edge suction paper feeding system, can reduce the friction between cardboard and mesa by 60%, its characteristics protect the original strength of cardboard, avoid pressing thin, collapse, combined with air pressure type elastic paper feeding mechanism, is conducive to the smooth input of cardboard after pressing line.

Function and characteristic:

1. High pressure centrifugal fan can control the wind pressure with frequency conversion according to the degree of warping of cardboard to ensure high speed and accurate transmission of warped cardboard and thin cardboard.
2. Separate paper feeding device, according to the need to choose paper. To ensure that large scale cardboard can also be processed.
3. Install 7-inch touch screen, which can automatically display the production quantity and production speed. Can design production quantity.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657





Die Cutting Unit

Die rubber roller

1. Die rubber $\Phi 388.9\text{mm}$, centrifugal cast alloy steel pipe, grinding processing, hard chrome plating, static balance.
2. Die rubber pad selection "Germany Dipai", width 250mm, normal can be used 8 million times, mechanical left and right movement 30mm, and equipped with radial differential device, so that the rubber pad wear average distribution, greatly improve the service life of the rubber pad.
3. Die cots are equipped with built-in differential automatic compensation device, so that the rubber pad and the template roll automatically maintain the same linear speed. Make the product size of each batch consistent, thereby reducing production cost.
4. The machine is equipped with die rubber adhesive correction device, which can be used after repeated correction.6) The grooving part is equipped with interlocking control switch to realize emergency stop, urgent delivery or return to feed paper.

Template roller

1. Template roller $\Phi 360\text{mm}$, centrifugal cast alloy steel pipe, grinding, hard chrome plating, static balance.
2. The template is fixed with screw hole M10, the axial spacing is 100mm, and the radial spacing is 18 equals (the Angle between holes is 20°).
3. The thickness of the cutting die board: 16mm (three layers of cardboard) 13mm (five layers of cardboard).

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657



- The template roller is equipped with a transverse adjustment device for stretching 10mm from left to right. The PLC control mode is adopted for digital display, and the adjustment precision value is 0.1mm.
- The template roller and die rubber cots are automatically removed by cylinder eccentricity device under the condition of no die cutting, which can reduce the no-load of the machine and prolong the life of die rubber and cutter die.

Technical Specifications

Model	RDC-2512
Max. feeding size	2500x1200mm
Max. die cutting size	2400x1100mm
Min. feeding size	750x360mm
Paper feeding mode	Auto feed
Paper feeding speed	120 pages/min
Arrange mode	Manual
Main motor	11kw
Repair motor	0.75kw
Phase motor	0.37kw
Baffle motor	0.37kw
Bellows motor	7.5kw
Dimension	3.7x1.7x2 m

Part List

No	Part Name	Origin
1	Main motor	Hang Zhou Xin Li
2	Repair motor	China Xin Chao
3	Phase motor	China Xin Chao
4	Baffle motor	China Xin Chao
5	Bellows motor	China Guangming
6	Relay	China Zhengtai
7	Proximity switch	China Hugong
8	Phase meter	China Hongsheng
9	Transducer	China Yingwenteng
10	Contactor	Schneider
11	Button	Schneider

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

