

RFQ-1300A

Three Servo Motor Automatic Tension Slitting Machine



Machine Introduction

Function description

Unwinding part

1. Adopts shaftless hydraulic fixing system, easily for one person operation. Using special conic node system from 3" to 6" for durable using. The 2 sides clamping arm are controlled by the hydraulic dovetail groove linear guideway. 2pcs of hydraulic clamping oil cylinder moves to each side at the same time, easily operation.
2. With the manual adjustment system, the unloading material tightness can be controlled. The adjustable range: +/-20mm
3. Adopt thread screw to move the frame left and right by motor to make the auto error-correction.
4. Corridor type feeding materials easily for operation.
5. Magnetic powder: 20KG Brake: 1sets

Traction part

The 5.5 KW servo motor drives the mirror surface and pinch roll

Waste papers recycle device

Using motor to blow out the wastepaper. The net cage should be prepared by customer.

Rewinding part:(automatic loading and discharging, easily for operation)

1. Rewinding the cut material by upper and bottom double bearing.
2. Each rewinding shaft with 1 set of 7.5 KW servo motor to drive the air shaft. The tension decided by the roll diameter. PLC controls SMC electric automatically to make all the sheet same thickness when do the multiple slitting. Because of the press roller, all the reels end face is smooth. it has the choice of pneumatic press roller and self-weight press roller. The screw type rewinding way can control the degree of the tightness of the finished products. With the increasing of the rewinding diameter, the servo motor speed goes down to extend the life of the air shaft. The air shaft never broken except the human factor
3. It can choose the whole shaft tension without friction and the servo motor in torque control mode in PLC

Rewinding and discharging automatic up and down

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

35⁺ YEARS
SERVING
INDONESIA

Technical Specifications

Model	RFQ-1300A
Material type	PE\OPP\for large rolling materials, such as PET, BOPP, PE, paper sticker, paper, compound printing paper and so on.
Material thickness	35-600g (paper)
Max. Diameter	1600mm
Paper roll	3" or 6" for choice
Max width	1300mm
Roller width	1350mm
Slitting width	50-1300mm
Rewinding paper roll	3"
Rewinding max. Diameter	1000mm
Error-correction	150mm
Precision	+/-0.15mm
Max. Speed	350m/min
Slitting speed	50-350m/min
Power	25KW
Weight	5600KG
Dimension	Length: 3800, width 3000, height 1800mm
Slitting tolls	standard for 16 ets, according to customer's requirement
Upper cutter	Φ125*85*1.2mm, brand: shanghai
Bottom cutter	Φ100*20*16mm, brand: shanghai
Rewinding shaft	2 pcs of 3" air shaft (6" for choice)
	With the Φ90 hard aluminum oxide guide roller

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

35⁺ YEARS
SERVING
INDONESIA

Configuration List

Name	Specification	Qty	Brand name
40# steel frame	Thickness of wallboard 45mm	1set	Shanghai Baosteel
3" air adjust air shaft		2pcs	Shanghai Qingbang
Main traction roll (mirror)	φ200*1350mm	1pcs	
Rubber press roller	φ150*1350mm	1pcs	
Hardness aluminum oxide guide roller	φ90*1350mm		
Rewinding servo motor	7.5KW	2sets	zhima
Traction servo motor	5.5KW	1set	zhima
Unwinding pneumatic brake	20KG	2sets	Wenzhou
Motor for blowing the slitter edge	1.1KW	1set	Wenzhou
bearing		some	NSK、HRB
Pneumatic part		some	huanhua
Electric proportional valve		2pcs	SMC
Unwinding pneumatic brake	20KG	2sets	Wenzhou
PLC	SIMATLC S7-200SMART	1pcs	SIEMENS
10" touch screen	TPC1061Ti	1pcs	Kunlun General State
Proximity switch		1pcs	OMRON from Japan
Low-voltage apparatus		some	Schneider, zhengtai
Power supply	S100-24	1pcs	Taiwan meanwell

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

35⁺ YEARS
SERVING
INDONESIA