



JB-720 780 Full-automatic cylinder screen press



JB-1020 Full-automatic cylinder screen press

Machine Introduction

Model JB-720 780 1020 Auto cylinder screen press is a kind of automatic flat screen press with high efficiency (more than duplication printing speed over the flat one), high quality (linear touch, more suitable for spot printing), high precision (usually the precision of overprint is less than 0.10mm), it is suitable for sequence printing in bulk of high precision screen productions. It is suitable for sequence printing in bulk of high precision screen productions. It is suitable for 108~400g/m² materials, especially for paper productions (such as cigarette case, wine case, toiletry case, present case, brand, poster, other paper packing production and special fake against materials etc), flower paper, soft plastic etc.

Technical Specifications

Model	JB-720	JB-780	JB-1020
Max. paper size	720x520mm ²	780x520mm ²	1020x720mm ²
Min. paper size	350x270mm ²	350x270mm ²	560x350mm ²
Max. printing area	720x500mm ²	780x500mm ²	1020x700mm ²
Size of screen frame	880x880mm ²	940x940mm ²	1280x1140mm ²
Paper weight	108~400g/m ²	108~400g/m ²	120~400g/m ²
Paper margin	≤15mm	≤15mm	≤13mm
Precision of overprint	≤0.10mm	≤0.10mm	≤0.10mm
Pile height	700mm	700mm	700mm
Printing speed	1000-3600 pcs/h	1000-3600 pcs/h	1000-3000 pcs/h
Power	3P 380V 10.25KW	3P 380V 10.25KW	3P 380V 11.09KW
Total weight	3500kg	3800kg	4900kg
Overall size	4100x1960x1270mm ³	4200x1870x1480mm ³	4600x2310x1520mm ³

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

36 YEARS
SERVING
INDONESIA

Features:

1. Classical swing cylinder structure with stable and accurate performance. Meanwhile, the photocell is configured on both side layers to detect the orientation status of printing matter to reduce printing waster efficiently.
2. High compatibility with the printing matter of different thickness to ensure well running at high speed. Front single sheet feeder or stream feeder adjustable. Double paper pile can be applied to raise efficiency.
3. Together with paper pushing and pressing structure, feeding table has smooth transportation of all kinds of material.
4. Mechanical double sheet and empty sheet detector on the in-feeding section.
5. Pneumatic screen and master frame locking
6. Net frame is running along the imported linear guide rail and ball bearing to reduce the noise and vibration at high speed to ensure printing stability.
7. Puller/pusher side layer on the left and right and infinitely adjustable from outside.
8. Outfeeding table move up and down by pneumatic cylinder.
9. The whole machine applies auto-lubrication system to make machine life longer.
10. Imported inverter, PLC and other famous brand electrical components, the whole machine design conforms to CE standard.
11. Main parts of machine are built by CNC production equipment to ensure running accuracy.

Configuration List

	Name	Qty	Brand	Remark
1	MOTOR	1	HAIGUANG	Main motor (Brake motor)
2	MOTOR	1	TAIWAN TECO	Ink-flood (Brake motor)
3	MOTOR	1	TAIWAN TECO	Feeder (Brake motor)
4	Vortical pump (Fan)	1	HENGLI	Delivery board
5	Vacuum pump	1	GERMAN BECKER	
6	Univertor	1	JAPAN Mitsubishi	
7	PLC module	1	JAPAN OMRON	
8	Photoelectric sensor	3	JAPAN OMRON	
9	Mini relay	2	JAPAN OMRON	
10	Motor protector	4	GERMAN EATON MULLER	
11	AC contactor	8	GERMAN EATON MULLER	
12	Button switch	20	GERMAN EATON MULLER	
13	Breaker	3	GERMAN EATON MULLER	
14	Induction/jiggle switch	9	TAIWAN TEND/FOTEK	
15	Power switch	1	TAYEE	
16	Reducer	1	TAIWAN KOKI	Ink-flood
17	Reducer	1	TAIWAN KOKI	Feeding board
18	Printing rail	2	JAPAN THK	

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO

Jl. Terusan Bandengan Utara No.16 / B 3-4

Jakarta, 14450, Indonesia

Tel. (021) 660 2665, 661 8255.

Fax. (021) 668 5874, 660 2657

36 YEARS
SERVING
INDONESIA