

YSK-530

Complete Set Of 3 Color Flexo Printing Machine



* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

35⁺ YEARS
SERVING
INDONESIA



Machine Introduction

Main function: The machine uses modular chain feeder, hand feeding single paperboard, easy to operate, with high efficiency, energy, security, and other features.

1. The machine uses 360-degree planetary electric phase adjustment (microcomputer digital phase meter) can directly enter numbers, adjust faster and more accurate.
2. Each unit used electric to separate and combine, pneumatic locking and pneumatic brake, easy to operate.
3. Distribution ink system, inking roller with automatic idling features that make the machine pause ink will not dry up.
4. Transmission gear, 45# steel, helical gear after grinding and induction hardening process (precision more than six) from finishing some locations adopt keyless devices, with no gaps, higher cutting accuracy.
5. Transmission gear, 45# steel, helical gear after grinding and induction hardening process (precision more than six) from finishing some locations adopt keyless devices, with no gaps, higher cutting accuracy.
6. Lubrication system: this machine used automatic spray type lubrication, automatic spray, Uniform amount of ink, each cycle back and forth, thereby increasing the life of gear and tinted accuracy.
7. The knife uses Qingdao brand-name manufacturers, high-speed steel materials, forging grinding, induction hardening process is made. Inner tooth design (March Dental) tools sharp and durable
8. Electric: main parts imported to Schneider and domestic Chint and other well-known manufacturers, which greatly increased stability
9. The punching and the clasp hands device and the free plate quad die cutting device are optional.
10. Anilox roller mesh can option 180-250 mesh.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

35⁺ YEARS
SERVING
INDONESIA

Printing unit: (can optional 1-4 units)

1. Printing roller:
 - Outer diameter: 515.6mm, (diameter including plate: ϕ 530mm)
 - The steel tube surface grinding, hard chrome plating
 - Do balance correction, steady operation.
2. Printing press roller:
 - Outer diameter ϕ 156mm
 - The steel tube surface grinding, hard chrome plating
 - Do balance correction, steady operation
3. Feeder paper upper and lower roller:
 - upper roller, outer diameter ϕ 86mm, thick wall steel pipe, with four feeder paper roller.
 - lower roller, outer diameter ϕ 156mm, thick wall steel pipe, surface grinding, hard chromium plating.
4. Steel anilox roller: (Dalian Junfeng)
 - Outer diameter ϕ 213mm (180-250 mesh, mesh optional)
 - Steel pipe surface grinding, crushing checker, hard chromium plating.
 - Do balance correction, smooth and steady operation, lattice point is consistent, uniform inking.
 - Anilox roller wedge type overrunning clutch, distributing, wash ink is convenient swift.
5. Rubber roller:
 - Outer diameter ϕ 198mm
 - Steel pipe surface parcel wear-resisting rubber and do correction balance.
 - Rubber middle high is the special grinding, ink transfer effect is good.
 - Rubber hardness is: 60-65 degrees.
6. Phase adjustment mechanism:
 - Planetary gear structure.
 - Printing phase electric digital 360 degrees adjustment (motion and stop all can be adjusted).
 - Manually adjust the horizontal position, adjust the distance ± 10 mm.
7. Ink circulation
 - Pneumatic diaphragm pump, ink stability, convenient operation and maintenance.
 - Ink filter, filtering impurities.
8. Printing phase fixing device:
 - Cylinder type brake, printing phase fixing device.
 - When the machine separate adjustment phase, the brake institutions limit the machine running, keeping the original gear fixed point position.
9. Oil supply device
 - Mechanical oil pump (double oil pump, oil supply loop)
 - Circulation oil, gear inking amount evenly, each group of oil level balance.

Slotting unit (one unit)

1. Pressing line device
 - Shaft diameter ϕ 110, surface grinding, hard chrome plating, moving smoothly.
 - Do balance correction, smooth operation.
 - Pressing roller adopt French Martin technology, use hard pressure the soft, the press line straight and not easy seam broken line.
 - Pressing roller clearance dial manually adjust, adjustment range 0-12mm.

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657


35⁺ YEARS
SERVING
INDONESIA

2. Slotting knife holder transverse adjusting mechanism
 - Shaft diameter: $\phi 156\text{mm}$, surface grinding, hard chrome plating, moving smoothly.
 - Slotted knife width: 7mm
 - Alloy steel material after heat treatment, grinding, tooth slotting knife, hardness and toughness.
 - Alloy steel material by heat treatment grinding trimming knife, knife-edge sharp, high precision.
3. Slotting phase adjusting mechanism
 - Planetary gear mechanism
 - Slot phase adjust electric digital 360 degrees, (operation, stop can be adjusted).
4. This machine can match the punching and the clasp hands device.

Technical Specifications

Model	YSK-530
Inside wallboard width	2800 mm
Max. feeding paper size	2600x1600 mm
Max. printing size	2500x1600 mm
Min. paper size	450x600 mm
Working speed	0-60 pcs/min
Printing plate thickness	2-11 mm
Printing roller diameter	$\Phi 530$ mm (include plate)
Max. slotting depth	7x400 mm
Phase adjustment	Electric 360°
Power	9.5 kw
Tinted precision	± 0.5 mm
Slotting precision	± 1.5 mm
Weight	12655 Kgs
Outline dimensions of main printer	5600x3800x1800 mm

Main Part List


Part	Picture	Model	Brand/Place	Notes
Machine Wall		Thickness:40mm	Large processing center production	Precision cast iron
Steel Anilox Roller		Dia: 213mm	Dalian Junfeng	Thickness: 25mm, computer dynamic balancing correction

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

35⁺ YEARS
SERVING
INDONESIA

Rubber Roller		Dia: 198mm	Hebei Jizhou	Thickness: 25mm, Hardness: 60-65°
Lower printing roll		Dia: 156mm	Seamless steel	Thickness: 18mm, Balance correction, grinding processing, hard chrome plating
Roller (slotting unit)		Dia: 156mm	Seamless steel pipe	Thickness: 20mm, grinding processing, hard chrome plating
Gears		Thickness: 50mm	45#steel	Shaving processing, nitriding treatment
Bearings			Hawa Luo	
Contactora			Schneider	
Electrical elements			Schneider	
Check component			Schneider	
Main Motor		7.5 KW	Guangzhou jinlong	Speed control motor
Close and separated motor		0.37kw*1 set	Jiangsu Duote	Slotting unit

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
Jl. Terusan Bandengan Utara No.16 / B 3-4
Jakarta, 14450, Indonesia
Tel. (021) 660 2665, 661 8255.
Fax. (021) 668 5874, 660 2657

35⁺ YEARS
SERVING
INDONESIA

Phase motor		0.37kw*3set	Zhejiang	Print phase, Slot phase
Distributing motor		400w*2set	Jiangsu Duote	Printing unit
Pneumatic single-way diaphragm pumps			Wuhan jinchangjian	
Pneumatic			Delixi	
Free key connection			Xianyang	
Overrunning clutch			Xianyang	
Die cutting knife			Qingdao qifeng	

* Warna dan spesifikasi mesin bisa berubah sesuai dengan perubahan spesifikasi pabrik.



PT. EKA MAJU MESININDO
 Jl. Terusan Bandengan Utara No.16 / B 3-4
 Jakarta, 14450, Indonesia
 Tel. (021) 660 2665, 661 8255.
 Fax. (021) 668 5874, 660 2657

35⁺ YEARS
SERVING
INDONESIA