Q1) Create two tables in your SQL database: Users (user_id, username, city) and Orders (order_id, user_id, product, amount). Insert at least 3 users and 5 orders, making sure some users have no orders.

```sql
SELECT * FROM Users;

SELECT * FROM Orders;
```

Q2) Write an SQL query using INNER JOIN to list all usernames and their ordered products, showing only users who have placed at least one order.

```sql
SELECT Users.username,
Orders.product
FROM Users
INNER JOIN Orders
ON Users.user_id =
Orders.user_id;
```

Q3) Write an SQL query using LEFT JOIN to display all usernames along with their ordered products. For users who haven't placed any orders, show NULL for the product.

```sql
SELECT Users.username,
Orders.product
FROM Users
LEFT JOIN Orders
ON Users.user_id =
Orders.user_id;
```

Q4) Write an SQL query using RIGHT JOIN to show all orders and the corresponding username for each order. If an order has a user_id that doesn't exist in the Users table, display NULL for the username.

Hint: Try deleting one user and keeping their order to test this case.

```
SELECT Orders.order_id,
Orders.user_id,
Orders.product,
Orders.amount,
Users.username
FROM Users
RIGHT JOIN Orders
ON Users.user_id =
```

Q5) Suppose you want to analyze food delivery data like Zomato. Create a CustomerSegments table (segment_id, segment_name), and link it to Users with a foreign key. Write an SQL query to show each username, their segment name, and total order amount (use JOINs as needed).

```
SELECT
    U.username,
    CS.segment_name,
    COALESCE(SUM(O.amount
), 0) AS
total_order_amount
FROM Users U
LEFT JOIN
CustomerSegments CS
    ON U.segment_id =
CS.segment_id
LEFT JOIN Orders O
    ON U.user_id =
O.user_id
GROUP BY
    U.user_id,
    U.username,
    CS.segment_name;
```