Q1) Write an SQL query using the SUM() function to calculate the total amount spent by users on food orders in a table food_orders (columns: order_id, user_id, amount) — imagine it's like Zomato's order history.

```
SELECT SUM(amount) AS
total_amount
FROM food_orders;
```

Q2) Using the COUNT() function, find out how many songs a user has added to their playlist in a table spotify_playlists (columns: playlist_id, user_id, song_id).

```
SELECT user_id,
COUNT(song_id) AS
total_songs
FROM spotify_playlists
GROUP BY user_id;
```

Q3) Write an SQL query to get the average rating given to a movie in a table bookmyshow_reviews (columns: review_id, movie_id, rating), and round the result to 1 decimal place using the ROUND() function.

Hint: Use AVG() with ROUND() to format the output.

```
SELECT ROUND(AVG(rating),
1) AS average_rating
FROM bookmyshow_reviews;
```

Q4) Find the minimum and maximum transaction values for a user from a table paytm_transactions (columns: txn_id, user_id, amount) — show both the smallest and largest transaction amounts.

```
SELECT
    MIN(amount) AS
minimum_transaction,
    MAX(amount) AS
maximum_transaction
FROM paytm_transactions
WHERE user_id = 101;
```

Q5) Given a table myntra_orders (columns: order_id, user_id, total_price), write an SQL query to display the total number of orders, the average order value (rounded to 2 decimals), and the highest order value for each user_id.

Constraint: Use GROUP BY to get results per user.

```sql
SELECT
    user_id,
    COUNT(order_id) AS
total_orders,
    ROUND(AVG(total_price
), 2) AS
average_order_value,
    MAX(total_price) AS
highest_order_value
FROM myntra_orders
GROUP BY user_id;
```