Q1) Write an SQL query to find the top 5 highest-rated restaurants in Koramangala, showing their name, average rating, and number of votes.

```sql
SELECT
    name,
    rating AS
average_rating,
    votes
FROM restaurants
WHERE location =
'Koramangala'
ORDER BY rating DESC
LIMIT 5;
```

Q2) Using the Zomato Bangalore dataset, create an SQL query that lists all unique cuisines available in Indiranagar along with the count of restaurants offering each cuisine.

```sql
SELECT
    cuisine,
    COUNT(*) AS
restaurant_count
FROM restaurants
WHERE location =
'Indiranagar'
GROUP BY cuisine
ORDER BY restaurant_count
DESC;
```

Q3) Write an SQL query to calculate the average cost for two people for each restaurant type (such as 'Cafe', 'Casual Dining', etc.) and order the results from most to least expensive.

```sql
SELECT
    rest_type,
    AVG(approx_cost_for_two)
AS average_cost
FROM restaurants
GROUP BY rest_type
ORDER BY average_cost DESC;
```

Q4) Find all restaurants that have a rating below 3.0 but more than 200 votes, and suggest a possible marketing action for these based on your findings.

Hint: Think about discounts, partnerships, or events to improve ratings or attract new customers.

```
SELECT
    name,
    rate,
    votes,
    approx_cost_for_two,
    listed_in(type) AS
restaurant_type
FROM restaurants
WHERE CAST(rate AS
DECIMAL(3,1)) < 3.0
  AND votes > 200
ORDER BY votes DESC;
```

Q5) Use ChatGPT to generate an SQL query that segments restaurants into three market categories: 'Budget' (cost for two < 500), 'Mid-range' (500-1500), and 'Premium' (>1500). Test and run the query on your dataset, and paste the working query in your submission.

```
SELECT
    name,
    approx_cost_for_two,
    CASE
        WHEN
approx_cost_for_two < 500
THEN 'Budget'
        WHEN
approx_cost_for_two
BETWEEN 500 AND 1500 THEN
'Mid-range'
        WHEN
approx_cost_for_two >
1500 THEN 'Premium'
    END AS
market_category
FROM restaurants
ORDER BY
approx_cost_for_two ASC;
```