



10 m · drawing scale 1:256

# Taif / Palm House

## Design V3.1 · pentagon Z4 · north-east corner cut along the lane

15 Oct 2026 · Design V3.1 · base.typ + design_v3.typ + data/rooms_v3.csv · room studies in studies/

**V3.1** on site-test option Z4: a pentagon 13 × 23 m on wall centre lines (13.25 × 23.25 outside), 0.75 m wider than Z3 through the middle, its north-east corner cut parallel to the lane; both palms lie well beyond the south facade. The **air tower** (blue, a 4-sided polygon of about 1.65 m², ≈ 1.1 m² clear) fills the tip of the cut corner, taking no room space. **East service block** (laid out in studies/east_wing.typ): **kitchen** 4 × 6.5 m (26 m²), exactly on the courtyard lines (y 6.0–12.5), sink under the courtyard window, hob and hood on the outside east wall, fridge and tall storage beside the dining door, doors only to the dining and the laundry; **laundry** 1.5 × 3.2 m on the solid women's majlis wall, entered from the kitchen through an open entrance (no door), machines in one line, extract fan to the roof; **maid room** (≈ 6.1 m²) and **maid bath** (≈ 3.4 m², WC, basin, shower) run up to the sloped cut wall, each with a window in it; maid access only kitchen → laundry → maid room → maid bath, both maid doors at the north end so the bed takes the wide south part. **West band:** lift, stair (with a store under its landing), **utility room with the service shaft inside it** (shaft beside the west wash block), then the **west wash block** (2.75 × 12.6 m = 34.65 m², laid out in studies/guest_wing.typ), one strip of wet rooms on one drain run: coffee corner (2.75 × 2, the serving base) and family basins (2.75 × 1.5), both open to the riwaq; family WC (2.75 × 1.7); serving passage (2.75 × 1.1); then the guest side: guest WC (1.5 × 1.7) behind a short screen wall, three guest basins open to the guest passage, foyer. The **serving passage** (2.75 × 1.1, a shelf, only two doors, never open together) is the only link between family and guests: door 1 to the riwaq, lockable from the riwaq side; door 2 to the guest passage, lockable from inside the passage. An open door 2 shows only the passage and the blank family WC wall (bent entry). The living-room west wall opposite door 1 (x = 4.25, y ≈ 15.7–16.6) has no window or opening. **Family lobby + riwaq** runs as one straight strip from the front door to the men's majlis; the guest side has no door onto it. **Women's majlis** 4.75 × 6 m · **courtyard** 4.75 × 6.5 m · **living** one open room 8.75 × 5.75 m: double-height part (4.75 × 5.75) on the courtyard, normal-height half (4 × 5.75) for dining beside the kitchen door; no upper floor over the double-height half or the courtyard · **men's majlis** 10.25 × 4.75 m, its west wall on the same line as the west band wall (x = 2.75), so the wash block is a straight 2.75 m strip. Blue outlines inside rooms are the shaft and the under-stair store (not extra area); blue lines mark the ceiling-height change in the living room and the doors, openings and screen wall of the west wash block.

✓ **All checks passed**

## Areas

| | |
|---|---|
| Envelope | **667.87 m²** |
| Building limit (envelope unless set) | **291 m²** |
| Other open voids | **0 m²** |
| Courtyard (open to sky) | **30.87 m²** |
| Rooms placed (20) | **258.47 m²** |
| Limit minus courtyard and voids | **260.12 m²** |
| Air channel + duct | **1.65 m²** |
| Not yet assigned | **1.65 m²** |

## Orientation

| | |
|---|---|
| True compass vs the M line | **21.4°** |
| NW wind vs the M line | **23.6°** |

Concept only. Wind: Global Wind Atlas (area data, 10 m), NW ≈ 15–20 %, SE ≈ 7–8 %. Confirm on site with a ribbon test.

# Schedules

All coordinates in metres from M1: x east (square to the M line), y along the M line southwards.

**Envelope corners**

| Corner | x | y |
|---|---|---|
| V1 | 0 | 38.86 |
| V2 | 0 | 3.05 |
| V3 | 9.18 | 1.36 |
| V4 | 9.67 | 1.22 |
| V5 | 10.48 | 1.65 |
| V6 | 13.55 | 7.3 |
| V7 | 14.06 | 8.86 |
| V8 | 15.35 | 9.4 |
| V9 | 18.4 | 14.8 |
| V10 | 21.13 | 21.04 |
| V11 | 24.77 | 34.3 |

**Rooms**

| Name | Frame | w × d (m) | Area |
|---|---|---|---|
| Women's majlis | M | 4.75 × 6 | 28.5 m² |
| Living (double height) | M | 4.75 × 5.75 | 27.31 m² |
| Men's majlis | M | 10.25 × 4.75 | 48.69 m² |
| Maid bath | M | 2.572 × 1.6 | 3.42 m² |
| Maid room | M | 2.5 × 3.2 | 6.12 m² |
| Laundry | M | 1.5 × 3.2 | 4.8 m² |
| Kitchen | M | 4 × 6.5 | 26 m² |
| Living (normal height) · dining | M | 4 × 5.75 | 23 m² |
| Lift | M | 2.75 × 2.2 | 6.05 m² |
| Family lobby + riwaq | M | 1.5 × 18.25 | 27.38 m² |
| Stair | M | 2.75 × 5.7 | 15.67 m² |
| Utility room (shaft inside) | M | 2.75 × 2.5 | 6.88 m² |
| Coffee corner (open use) | M | 2.75 × 2 | 5.5 m² |
| Family basins (2) | M | 2.75 × 1.5 | 4.13 m² |
| Family WC + basin | M | 2.75 × 1.7 | 4.68 m² |
| Serving passage (2 doors) | M | 2.75 × 1.1 | 3.03 m² |
| Guest WC | M | 1.5 × 1.7 | 2.55 m² |
| Basins (3) | M | 1.5 × 2 | 3 m² |
| Guest passage | M | 1.25 × 3.7 | 4.63 m² |
| Foyer + entry | M | 2.75 × 2.6 | 7.15 m² |

# Design idea and philosophy

Taif / Palm House · Design V3.1 · pentagon with the north-east corner cut

## A house around a cool heart

The house is organised around one idea: a small, shaded courtyard at its centre that stays cool through the day. The rooms the family uses most open onto it. The wide double-height living room, which also holds the dining, faces it from the south; the kitchen from the east; the women's majlis from the north. On the west, the riwaq runs along it with windows. The courtyard is not a leftover space between rooms; it is the room the rest of the house looks into.

## Looking in, not out

The outer walls stay quiet, with small openings, as in the traditional houses of the region. Light, air and view come from the inside. This gives privacy from the street and the lane, protects the rooms from the hot sun and dust, and lets the family live openly within their own walls.

## Air before sun

Taif's prevailing wind comes from the north-west. An air tower filling the leftover tip of the north-east cut corner, so it takes no usable room space, catches it above the roof, where it is strong and clean, and brings it down to a tunnel below the floor. The tunnel passes through the cool ground and releases the air through a low, closable opening in the courtyard wall. Warm air rises and leaves through the open sky. The narrow courtyard is enclosed on all four sides and shaded by its walls, so it receives air without receiving sun. Every opening can be closed: open at night and early morning, closed in hot afternoons, dust and cold.

## On firm ground, as far north as possible

The house sits on the firm, higher ground in the north of the plot, square to the M line so every wall can be set out from the site pegs, and pushed as far north as the setbacks allow. The narrow courtyard keeps the house narrow, and the north-east corner is cut parallel to the lane, so the whole house reaches further north and both palms stay well clear behind it.

## One living room, two heights

The living room is one open space with two ceiling heights. The half next to the courtyard is double height: it continues the courtyard's vertical space, gives the best view into it, and works as a chimney, with high operable windows that let warm air rise and leave while cool air is drawn in from the courtyard; its 4.75 m width is a simple roof span. The east half is normal height: a warmer, lower place for dining beside the kitchen door, easier to air-condition and light, with ducts hidden in its ceiling, and the first floor continues above it. No upper floor is built over the double-height half or the courtyard.

## One band that serves the house

Everything that serves the house sits in one band on the west: the family entrance, the lift, the stair, the utility room with the service shaft and the west wash block, one strip of wet rooms on one drain run (coffee corner, family basins, family WC, guest WC, guest basins). Pipes, cables and air rise in one place, the structure gains one stiff core, and every service can be reached for maintenance without breaking a wall. The family lobby and riwaq run along this band as one straight strip on the courtyard side, the family's covered route from the front door to the living room.

## Family, guests and service, each in their place

The family enters through the lobby; women guests use the same door to reach the women's majlis. The men's majlis has its own entrance, foyer, three basins open to the guest passage and a WC whose door hides behind a short screen wall, all in the south of the west wash block; the guest side has no door onto the riwaq. Its only link to the house is a short serving passage with a shelf and only two doors that are never open together: the family opens door 1 from the riwaq, puts coffee, trays or food on the shelf, closes it and calls the host; the host opens door 2 from the guest passage and collects. Door 1 locks from the riwaq side and door 2 from inside the passage, so the family controls both. An open door 2 shows only the passage and a blank wall, a bent entry (majaz), and the coffee corner just north of it is the serving base. The kitchen stays isolated beside the courtyard, a clean 4 × 6.5 m room on the same lines as the courtyard, with its only door to the dining and an open entrance to the laundry. The laundry runs north along the solid wall of the women's majlis to the maid room and maid bath, which use the sloped corner to the full; the maid bath, laundry and kitchen sink share one drain line down the west side of the block, and the maid wing is reached only through the kitchen.

## Services built for life

The service shaft sits inside a utility room, so every service is in one place behind one door: the shaft, the main electrical panel, the water manifold with its isolation valves and the water heater. The shaft is a closed box of about 1.0 × 1.2 m clear with sealed walls and one full-height maintenance door, and the 0.9 m in front of that door is always kept clear. It stands directly beside the west wash block, so drainage runs stay short; first-floor bathrooms should stack over the north part of the block, near the shaft. The block's drain crosses under the serving passage floor, with a cleanout access point there. The space under the stair's landing becomes a store instead of dead space. The Saudi Building Code sets no fixed size for a closed pipe shaft; the sizes here follow general professional guidance and must be confirmed with the code, the municipality and the plumbing engineer.

Concept for discussion. Airflow, tunnel depth, waterproofing, drainage, structure and services need the engineers' review; wind direction to be confirmed on site.