

Section 1: File and Directory Management

1. Display the current working directory.

```
File Actions Edit View Help
(kali@kali)-[~/Desktop]
$ pwd
/home/kali/Desktop
```

2. List all the contents of your current directory, including hidden files.

```
(kali@kali)-[~]
$ ls -a
. .bash_logout .cache directory .face file2 .gnupg .mozilla 'New Folder' .pki Templates .xsession-errors
. .bashrc child .dmrc .face.icon filename .ICEauthority Music p .profile .xsession-errors.old
.. .bashrc.original .config Documents file folder .java name parent Public .viminfo .zsh_history
. .BurpSuite Desktop Downloads file1 folder1 .local new Pictures .sudo_as_admin_successful .Xauthority .zshrc

(kali@kali)-[~]
$
```

3. Change your directory to the `Desktop`.

```
(kali@kali)-[~]
$ cd Desktop

(kali@kali)-[~/Desktop]
$
```

4. Create two directories named `dir1` and `dir2` on the Desktop.

```
(kali@kali)-[~/Desktop]
$ mkdir ahmed1
mkdir: cannot create directory 'ahmed1': File exists

(kali@kali)-[~/Desktop]
$ mkdir ahmed
mkdir: cannot create directory 'ahmed': File exists

(kali@kali)-[~/Desktop]
$
```

5. Inside `dir1`, create a file named `file1.txt`.

```
(kali@kali)-[~/Desktop]
$ cd ahmed

(kali@kali)-[~/Desktop/ahmed]
$ touch ahmed2.txt
```

6. Inside `dir2`, create a file named `file2.txt`.

```
(kali@kali)-[~/Desktop]
$ cd ahmed

(kali@kali)-[~/Desktop/ahmed]
$ touch ahmed2.txt
```

7. Using nano or vim Write the numbers 1 to 9 into `file1.txt`.

```
(kali㉿kali)-[~/Desktop/ahmed]  
$ nano ahmed1.txt
```

8. From the home directory Copy the contents of `file1.txt` into `file2.txt`.

```
(kali㉿kali)-[~/Desktop]  
$ cp ahmed1/ahmed2.txt ahmed/ahmed1.txt
```

9. From the home directory, delete `file1.txt` inside `dir1`.

```
(kali㉿kali)-[~/Desktop]  
$ rm ahmed/ahmed1.txt  
  
(kali㉿kali)-[~/Desktop]  
$
```

10. Remove the directory `dir1` from the Desktop.

```
(kali㉿kali)-[~/Desktop]  
$ rmdir ahmed
```

11. Redirect the output of the network configuration command to a file named `network_info.txt` on the Desktop.

```
(kali㉿kali)-[~/Desktop]  
$ ifconfig >ahmed2.txt
```

12. Open the Desktop folder and show all files with detailed information.

```
(kali㉿kali)-[~/Desktop]  
$ ls -all  
total 20  
drwxr-xr-x  3 kali kali 4096 Aug 31 13:19 .  
drwx----- 26 kali kali 4096 Aug 31 12:46 ..  
drwxr-xr-x  2 kali kali 4096 Aug 31 11:59 ahmed1  
-rw-r--r--  1 kali kali  874 Aug 31 13:24 ahmed2.txt  
-rw-r--r--  1 kali kali    0 Aug 21 11:14 folder.folder  
-rw-----  1 kali kali 3643 Aug 24 19:13 quiz02.sh
```

Section 2: Users and Groups Management

13. Create a new user with your name.

```
(kali㉿kali)-[~/Desktop]
$ sudo adduser ahmed
info: Adding user `ahmed' ...
info: Selecting UID/GID from range 1000 to 59999 ...
info: Adding new group `ahmed' (1001) ...
info: Adding new user `ahmed' (1001) with group `ahmed (1001)' ...
info: Creating home directory `/home/ahmed' ...
info: Copying files from `/etc/skel' ...
New password:
Retype new password:
passwd: password updated successfully
Changing the user information for ahmed
Enter the new value, or press ENTER for the default
  Full Name []: ahmed abotalip
  Room Number []:
  Work Phone []:
  Home Phone []:
  Other []:
Is the information correct? [Y/n] y
info: Adding new user `ahmed' to supplemental / extra groups `users' ...
info: Adding user `ahmed' to group `users' ...
```

14. Set a password for your user.

```
(kali㉿kali)-[~]
$ sudo passwd ahmed
New password:
Retype new password:
passwd: password updated successfully
```

15. Open the file that contains user information and verify that your user has been added.

```
(kali㉿kali)-[~]
$ /home
```

```
(kali㉿kali)-[/home]
$ net ahmed
Invalid command: net ahmed
Usage:
net rpc          Run functions using RPC transport
net rap          Run functions using RAP transport
net ads          Run functions using ADS transport
net file         Functions on remote opened files
net share        Functions on shares
net session      Manage sessions
net server       List servers in workgroup
net domain       List domains/workgroups on network
net printq       Modify printer queue
```

16. Add your user to the file that gives administrative privileges.

```
(kali㉿kali)-[/home]
$ sudo usermod -ag sudo ahmed
usermod: -a flag is only allowed with the -G flag
Usage: usermod [options] LOGIN

Options:
  -a, --append                append the user to the supplementa
  l GROUPS                    mentioned by the -G option without
  removing                    the user from other groups
  -b, --badname               allow bad names
  -c, --comment COMMENT      new value of the GECOS field
```

```
(kali㉿kali)-[/home]
$ groups ahmed
ahmed : ahmed sudo users
```

17. Switch to your user and confirm the user identity.

```
(kali㉿kali)-[~]  
$ su cyber  
Password: █
```

18. Create a new group named `testgroup`.

```
(kali㉿kali)-[~]  
$ sudo addgroup testgroup  
[sudo] password for kali:  
info: Selecting GID from range 1000 to 59999 ...  
info: Adding group `testgroup' (GID 1002) ...
```

19. Add your user to `testgroup`.

```
(kali㉿kali)-[~]  
$ usermod -ag testgroup cyber  
usermod: -a flag is only allowed with the -G flag  
Usage: usermod [options] LOGIN  
  
Options:  
-a, --append                append the user to the supplemental GROUPS  
                             mentioned by the -G option without removing  
                             the user from other groups  
-b, --badname                allow bad names  
-c, --comment COMMENT       new value of the GECOS field  
-d, --home HOME_DIR         new home directory for the user account  
-e, --expiredate EXPIRE_DATE set account expiration date to EXPIRE_DATE  
-f, --inactive INACTIVE     set password inactive after expiration  
                             to INACTIVE  
-g, --gid GROUP              force use GROUP as new primary group  
-G, --groups GROUPS         new list of supplementary GROUPS  
-h, --help                  display this help message and exit  
-l, --login NEW_LOGIN       new value of the login name  
-L, --lock                  lock the user account  
-m, --move-home             move contents of the home directory to the  
                             new location (use only with -d)  
-o, --non-unique             allow using duplicate (non-unique) UID  
-p, --password PASSWORD     use encrypted password for the new password  
-P, --prefix PREFIX_DIR     prefix directory where are located the /etc/* files  
-r, --remove                remove the user from only the supplemental GROUPS  
                             mentioned by the -G option without removing  
                             the user from other groups  
-R, --root CHROOT_DIR       directory to chroot into  
-s, --shell SHELL           new login shell for the user account  
-u, --uid UID               new UID for the user account  
-U, --unlock                unlock the user account  
-v, --add-subuids FIRST-LAST add range of subordinate uids  
-V, --del-subuids FIRST-LAST remove range of subordinate uids  
-w, --add-subgids FIRST-LAST add range of subordinate gids  
-W, --del-subgids FIRST-LAST remove range of subordinate gids  
-Z, --selinux-user SEUSER   new SELinux user mapping for the user account
```

20. Add the group `testgroup` to the file that gives administrative privileges.

```
(kali㉿kali)-[~/Desktop]  
$ sudo visudo
```

21. Remove your user from the file that gives administrative privileges.

```
(kali㉿kali)-[~/Desktop]  
$ sudo visudo
```

22. Check if your user still have administrative privileges.

```
(kali㉿kali)-[~/Desktop]  
$ sudo visudo
```

23. Check which groups your user belongs to.

```
(kali㉿kali)-[~/Desktop]  
$ testgroup cyber  
testgroup: command not found  
  
(kali㉿kali)-[~/Desktop]  
$ sudo testgroup cyber  
sudo: testgroup: command not found
```

Section 3: Permissions and Ownership

24. Set the permissions of `file2.txt` on the Desktop to allow the owner to read, write, and execute; the group to read and execute; and others to read .

```
(kali㉿kali)-[~/Desktop]
$ chmod u+rwX,g+rw,o+r folder.folder
```

25. Check the permissions of `file2.txt` to verify the change.

```
(kali㉿kali)-[~/Desktop]
$ ls -l folder.folder
-rwxrw-r-- 1 kali kali 0 Aug 21 11:14 folder.folder
```

26. Change the ownership of `file2.txt` to your user.

```
(kali㉿kali)-[~/Desktop]
$ sudo chown cyber:cyber folder.folder
```

27. verify the ownership of `file2.txt`.

```
(kali㉿kali)-[~/Desktop]
$ ls -l folder.folder
-rwxrw-r-- 1 cyber cyber 0 Aug 21 11:14 folder.folder
```

28. Change back the ownership of a file `file2.txt` .

```
(kali㉿kali)-[~/Desktop]
$ sudo chown kali:kali folder.folder
```

29. Grant write permission to everyone for `file2.txt`.

```
(kali㉿kali)-[~/Desktop]
$ chmod u+w,g+w,o+w folder.folder
```

30. Remove the write permission for the group and others for `file2.txt`.

```
(kali㉿kali)-[~/Desktop]
$ chmod u+~w-,g+~,o+~ folder.folder
```

31. Delete `file2.txt` after making the necessary ownership and permission changes.

```
(kali㉿kali)-[~/Desktop]
$ rm folder.folder
rm: remove write-protected regular empty file 'folder.folder'? y
```


37. Kill a process with a specific PID.

```
(kali㉿kali)-[~]
$ kill [4529]
kill: illegal pid: [4529]

(kali㉿kali)-[~]
$
```

38. Start an application and stop it using a command that kills processes by name(exeyes).

```
(kali㉿kali)-[~]
$ exeyes &
[1] 123896

(kali㉿kali)-[~]
$ Command 'exeyes' not found, did you mean:
  command 'expeyes' from deb expeyes
  command 'xeyes' from deb x11-apps
Try: sudo apt install <deb name>

[1] + exit 127  exeyes
(kali㉿kali)-[~]
$ pkill exeyes

(kali㉿kali)-[~]
$
```

39. Restart the application, then stop it using the interactive process viewer.

```
(kali㉿kali)-[~]
$ exeyes &
[1] 124891

(kali㉿kali)-[~]
$ Command 'exeyes' not found, did you mean:
  command 'xeyes' from deb x11-apps
  command 'expeyes' from deb expeyes
Try: sudo apt install <deb name>

[1] + exit 127  exeyes
(kali㉿kali)-[~]
$ htop
Command 'htop' not found, but can be installed with:
sudo apt install htop
Do you want to install it? (N/y)y
sudo apt install htop
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
E: Unable to locate package htop
```

40. Run a command in the background, then bring it to the foreground(exeyes).

```
(kali㉿kali)-[~]
$ sudo exeyes &
[1] 127334

sudo: exeyes: command not found
[1] + exit 1      sudo exeyes
(kali㉿kali)-[~]
$ fg
fg: no current job
```

41. Check how long the system has been running.

```
(kali㉿kali)-[~]  
$ uptime  
21:03:42 up 4:34, 1 user, load average: 0.09, 0.13, 0.12
```

42. List all jobs running in the background.

```
(kali㉿kali)-[~]  
$ sleep 100 &  
[1] 130678  
  
(kali㉿kali)-[~]  
$ jobs  
[1] + running sleep 100
```

Section 5: Networking Commands

43. Display the network configuration

```
(kali㉿kali)-[~]  
$ ifconfig  
eth0: flags=4163<UP,BROADCAST,RUNNING,MULTICAST> mtu 1500  
    inet 192.168.38.129 netmask 255.255.255.0 broadcast 192.168.38.255  
    inet6 fe80::45f6:5a1f:1b84:e30f prefixlen 64 scopeid 0x20<link>  
    ether 00:0c:29:6d:ec:77 txqueuelen 1000 (Ethernet)  
    RX packets 408 bytes 41928 (40.9 KiB)  
    RX errors 0 dropped 0 overruns 0 frame 0  
    TX packets 69 bytes 10888 (10.6 KiB)  
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0  
  
lo: flags=73<UP,LOOPBACK,RUNNING> mtu 65536  
    inet 127.0.0.1 netmask 255.0.0.0  
    inet6 ::1 prefixlen 128 scopeid 0x10<host>  
    loop txqueuelen 1000 (Local Loopback)  
    RX packets 4 bytes 240 (240.0 B)  
    RX errors 0 dropped 0 overruns 0 frame 0  
    TX packets 4 bytes 240 (240.0 B)  
    TX errors 0 dropped 0 overruns 0 carrier 0 collisions 0
```

44. Check the IP address of your machine.

```
(kali㉿kali)-[~]  
$ hostname -i  
127.0.1.1
```

45. Test connectivity to an external server.


```
(kali@kali)-[~]
$ ping 192.168.1.10
PING 192.168.1.10 (192.168.1.10) 56(84) bytes of data:
From 192.168.1.3 icmp_seq=3 Destination Host Unreachable
From 192.168.1.3 icmp_seq=6 Destination Host Unreachable
From 192.168.1.3 icmp_seq=9 Destination Host Unreachable
From 192.168.1.3 icmp_seq=12 Destination Host Unreachable
From 192.168.1.3 icmp_seq=15 Destination Host Unreachable
From 192.168.1.3 icmp_seq=18 Destination Host Unreachable
From 192.168.1.3 icmp_seq=21 Destination Host Unreachable
From 192.168.1.3 icmp_seq=24 Destination Host Unreachable
From 192.168.1.3 icmp_seq=27 Destination Host Unreachable
From 192.168.1.3 icmp_seq=30 Destination Host Unreachable
From 192.168.1.3 icmp_seq=33 Destination Host Unreachable
From 192.168.1.3 icmp_seq=36 Destination Host Unreachable
From 192.168.1.3 icmp_seq=39 Destination Host Unreachable
From 192.168.1.3 icmp_seq=42 Destination Host Unreachable
From 192.168.1.3 icmp_seq=45 Destination Host Unreachable
From 192.168.1.3 icmp_seq=48 Destination Host Unreachable
From 192.168.1.3 icmp_seq=51 Destination Host Unreachable
From 192.168.1.3 icmp_seq=54 Destination Host Unreachable
From 192.168.1.3 icmp_seq=57 Destination Host Unreachable
From 192.168.1.3 icmp_seq=60 Destination Host Unreachable
From 192.168.1.3 icmp_seq=63 Destination Host Unreachable
From 192.168.1.3 icmp_seq=66 Destination Host Unreachable
From 192.168.1.3 icmp_seq=69 Destination Host Unreachable
From 192.168.1.3 icmp_seq=72 Destination Host Unreachable
From 192.168.1.3 icmp_seq=75 Destination Host Unreachable
From 192.168.1.3 icmp_seq=78 Destination Host Unreachable
```

46. Display the routing table.

```
(kali@kali)-[~]
$ route -n
Kernel IP routing table
Destination Gateway Genmask Flags Metric Ref Use Iface
0.0.0.0 192.168.38.2 0.0.0.0 UG 100 0 0 eth0
192.168.38.0 0.0.0.0 255.255.255.0 U 100 0 0 eth0
```

47. Check the open ports and connections.

active

```
(kali@kali)-[~]
$ netstat -tuln
Active Internet connections (only servers)
Proto Recv-Q Send-Q Local Address Foreign Address State
(kali@kali)-[~]
$
```

48. Show the IP address of the host machine and the VM, and verify if they are on the same network.

```
(kali@kali)-[~]
$ hostname -i
127.0.1.1
```

49. Trace the route to an external server.

```
(kali@kali)-[~]
$ traceroute 192.168.1.10
traceroute to 192.168.1.10 (192.168.1.10), 30 hops max, 60 byte packets
 1 192.168.38.2 (192.168.38.2) 0.570 ms 0.676 ms 0.862 ms
 2 * * *
 3 * * *
 4 * * *
 5 * * *
 6 *
 *
 7 * * *
 8 * * *
 9 * * *
10 * * *
11 * * *
12 * * *
13 * * *
14 * * *
15 * * *
16 * * *
17 * * *
18 * * *
19 * * *
20 * * *
21 * * *
22 * * *
23 * * *
24 * * *
25 * * * "the quieter you become, the more you are able to hear"
26 * * *
27 * * *
28 * * *
29 * * *
30 * * *
```

50. Find out the default gateway.

```
(kali@kali)-[~]
$ arp -a
? (192.168.38.254) at 00:50:56:eb:e3:ab [ether] on eth0
? (192.168.38.2) at 00:50:56:f8:13:20 [ether] on eth0
```

51. Check the MAC address of your network interface.

```
(kali@kali)-[~]
$ ip link show
1: lo: <LOOPBACK,UP,LOWER_UP> mtu 65536 qdisc noqueue state UNKNOWN mode DEFAULT group default qlen 1000
   link/loopback 00:00:00:00:00:00 brd 00:00:00:00:00:00
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc fq_codel state UP mode DEFAULT group default qlen 1000
   link/ether 00:0c:29:6d:ec:77 brd ff:ff:ff:ff:ff:ff
```

52. Ensure that the VM can access external networks.

```
(kali@kali)-[~]
$ ping 192.168.1.10
PING 192.168.1.10 (192.168.1.10) 56(84) bytes of data:
From 192.168.1.3 icmp_seq=3 Destination Host Unreachable
From 192.168.1.3 icmp_seq=6 Destination Host Unreachable
```

Section 6: UFW Firewall

53. Enable the firewall.

```
File Actions Edit View Help
(kali@kali)-[~]
$ sudo ufw enable
[sudo] password for kali:
sudo: ufw: command not found
```

54. Allow SSH connections through the firewall.

```
(kali@kali)-[~]
$ sudo ufw deny ssh
sudo: ufw: command not found
```

55. Deny all incoming traffic by default.

```
(kali@kali)-[~]
$ sudo ufw default deny incoming
sudo: ufw: command not found
```

56. Allow HTTP and HTTPS traffic.

```
(kali@kali)-[~]
$ sudo ufw allow http
sudo: ufw: command not found
```

57. Allow port 20

```
(kali@kali)-[~]
$ sudo ufw allow 20
sudo: ufw: command not found
```

58. Reset the firewall settings.

```
(kali㉿kali)-[~]  
$ sudo ufw disable  
sudo: ufw: command not found  
  
(kali㉿kali)-[~]  
$ sudo ufw reset  
sudo: ufw: command not found
```

59. Delete a rule from the firewall.

```
(kali㉿kali)-[~]  
$ sudo ufw status numbered  
sudo: ufw: command not found  
  
(kali㉿kali)-[~]  
$ sudo ufw delete 1
```

60. Disable the firewall.

```
(kali㉿kali)-[~]  
$ sudo ufw disable  
sudo: ufw: command not found
```

61. View the status of the firewall.

```
(kali㉿kali)-[~]  
$ sudo ufw status  
sudo: ufw: command not found
```

62. Log firewall activity and view it.

```
(kali㉿kali)-[~]  
$ sudo cat /var/log/ufw.log  
cat: /var/log/ufw.log: No such file or directory
```

Section 7: Searching and System Information

63. Delete the command history.

```
(kali㉿kali)-[~]  
$ bash history -c
```

64. Search for a kali in the `/etc/passwd` file.

```
(kali㉿kali)-[~]  
$ bash grep kali /etc/passwd  
/usr/bin/grep: /usr/bin/grep: cannot execute binary file
```

65. Search for a kali in the `/etc/group` file.

```
(kali㉿kali)-[~]  
$ bash grep kali /etc/group  
/usr/bin/grep: /usr/bin/grep: cannot execute binary file
```

66. Locate the `passwd` file.

```
(kali@kali)-[~]
$ locate passwd
/etc/passwd
/etc/passwd-
/etc/alternatives/vncpasswd
/etc/alternatives/vncpasswd.1.gz
/etc/pam.d/chpasswd
/etc/pam.d/passwd
/etc/security/opasswd
/usr/bin/autopasswd
/usr/bin/expect_autompasswd
/usr/bin/expect_mkpasswd
/usr/bin/expect_tkpasswd
/usr/bin/gpasswd
/usr/bin/grub-mkpasswd-pbkdf2
/usr/bin/httpasswd
/usr/bin/impacket-smbpasswd
/usr/bin/ldappasswd
/usr/bin/mkpasswd
/usr/bin/mosquitto_passwd
/usr/bin/passwd
/usr/bin/smbpasswd
/usr/bin/tightvncpasswd
/usr/bin/tkpasswd
/usr/bin/vncpasswd
/usr/include/rpcsvc/yppasswd.h
/usr/include/rpcsvc/yppasswd.x
/usr/lib/python3/dist-packages/future/backports/test/keycert.passwd.pem
/usr/lib/python3/dist-packages/future/backports/test/ssl_key.passwd.pem
/usr/lib/python3/dist-packages/impacket/krb5/kpasswd.py
/usr/lib/python3/dist-packages/impacket/krb5/_pycache_/kpasswd.cpython-311.pyc
/usr/lib/python3/dist-packages/samba/tests/krb5/kpasswd_tests.py
/usr/lib/python3/dist-packages/samba/tests/krb5/_pycache_/kpasswd_tests.cpython-311.pyc
/usr/lib/tmpfiles.d/passwd.conf
/usr/lib/x86_64-linux-gnu/samba/libmbpasswdparser-samba4.so.0
/usr/sbin/chpasswd
/usr/sbin/chpasswd
```

67. Locate the shadow file and open it.

```
(kali@kali)-[~]
$ sudo cat /etc/shadow
root:*:19590:0:99999:7:::
daemon:*:19590:0:99999:7:::
bin:*:19590:0:99999:7:::
sys:*:19590:0:99999:7:::
sync:*:19590:0:99999:7:::
games:*:19590:0:99999:7:::
man:*:19590:0:99999:7:::
lp:*:19590:0:99999:7:::
mail:*:19590:0:99999:7:::
news:*:19590:0:99999:7:::
uucp:*:19590:0:99999:7:::
proxy:*:19590:0:99999:7:::
www-data:*:19590:0:99999:7:::
backup:*:19590:0:99999:7:::
list:*:19590:0:99999:7:::
irc:*:19590:0:99999:7:::
_apt:*:19590:0:99999:7:::
nobody:*:19590:0:99999:7:::
systemd-networkd:*:19590:0:99999:7:::
systemd-timesyncd:*:19590:0:99999:7:::
messagebus:*:19590:0:99999:7:::
tss:*:19590:0:99999:7:::
strongswan:*:19590:0:99999:7:::
tcpdump:*:19590:0:99999:7:::
usbmuxd:*:19590:0:99999:7:::
sshd:*:19590:0:99999:7:::
dnsmasq:*:19590:0:99999:7:::
avahi:*:19590:0:99999:7:::
speech-dispatcher:*:19590:0:99999:7:::
pulse:*:19590:0:99999:7:::
lightdm:*:19590:0:99999:7:::
saned:*:19590:0:99999:7:::
polkitd:*:19590:0:99999:7:::
rtkit:*:19590:0:99999:7:::
colord:*:19590:0:99999:7:::
nm-openvpn:*:19590:0:99999:7:::
nm-openconnect:*:19590:0:99999:7:::
mysql:*:19590:0:99999:7:::
```

68. Search for all configuration files in the `/etc` directory.

```
(kali㉿kali)-[~]
$ find /etc -type f
/etc/python2.7/sitecustomize.py
/etc/macchanger/ifupeown.sh
/etc/alternatives/README
/etc/stunnel/README
/etc/mysql/my.cnf.fallback
/etc/mysql/conf.d/mysql.cnf
/etc/mysql/conf.d/mysqldump.cnf
/etc/mysql/debian.cnf
/etc/mysql/mariadb.cnf
/etc/mysql/mariadb.conf.d/50-mysql-clients.cnf
/etc/mysql/mariadb.conf.d/50-mysqld_safe.cnf
/etc/mysql/mariadb.conf.d/provider_lzo.cnf
/etc/mysql/mariadb.conf.d/provider_lz4.cnf
/etc/mysql/mariadb.conf.d/provider_lzma.cnf
/etc/mysql/mariadb.conf.d/provider_bzip2.cnf
/etc/mysql/mariadb.conf.d/50-client.cnf
/etc/mysql/mariadb.conf.d/provider_snappy.cnf
/etc/mysql/mariadb.conf.d/50-server.cnf
/etc/mysql/mariadb.conf.d/60-galera.cnf
/etc/mysql/debian-start
/etc/reader.conf.d/libccidtwi
/etc/ts.conf
/etc/smartd.conf
/etc/init.d/plymouth
/etc/init.d/udev
/etc/init.d/samba-ad-dc
/etc/init.d/nginx
/etc/init.d/pcscd
/etc/init.d/nfs-common
/etc/init.d/ntpsec
/etc/init.d/saned
/etc/init.d/procps
/etc/init.d/apache2
/etc/init.d/haveged
/etc/init.d/rsync
```

69. Search recursively for a specific word in

the `/var/log` directory.

```
(kali㉿kali)-[~]
$ grep -r "ah" /var/log
grep: /var/log/vmware-vmtoolsd-root.1.log: Permission denied
grep: /var/log/apt/term.log.1.gz: binary file matches
grep: /var/log/apt/eipp.log.xz: binary file matches
grep: /var/log/boot.log: Permission denied
grep: /var/log/private: Permission denied
grep: /var/log/vmware-vmtoolsd-root.3.log: Permission denied
grep: /var/log/boot.log.2: Permission denied
grep: /var/log/btmp: Permission denied
grep: /var/log/boot.log.1: Permission denied
grep: /var/log/speech-dispatcher: Permission denied
grep: /var/log/vmware-vmtoolsd-root.2.log: Permission denied
/var/log/dpkg.log.1:2023-08-21 14:52:02 install libavahi-common-data:amd64 <none> 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:02 status half-installed libavahi-common-data:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:02 status unpacked libavahi-common-data:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:02 install libavahi-common3:amd64 <none> 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:02 status half-installed libavahi-common3:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:02 status unpacked libavahi-common3:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:02 install libavahi-client3:amd64 <none> 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:02 status half-installed libavahi-client3:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:02 status unpacked libavahi-client3:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:14 install libavahi-core7:amd64 <none> 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:14 status half-installed libavahi-core7:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:14 status unpacked libavahi-core7:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:14 install avahi-daemon:amd64 <none> 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:14 status half-installed avahi-daemon:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:14 status unpacked avahi-daemon:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:42 install libavahi-glib1:amd64 <none> 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:42 status half-installed libavahi-glib1:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:52:42 status unpacked libavahi-glib1:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:53:11 configure libavahi-common-data:amd64 0.8-10 <none>
/var/log/dpkg.log.1:2023-08-21 14:53:11 status unpacked libavahi-common-data:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:53:11 status half-configured libavahi-common-data:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:53:11 status installed libavahi-common-data:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:53:15 configure libavahi-common3:amd64 0.8-10 <none>
/var/log/dpkg.log.1:2023-08-21 14:53:15 status unpacked libavahi-common3:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:53:15 status half-configured libavahi-common3:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:53:15 status installed libavahi-common3:amd64 0.8-10
/var/log/dpkg.log.1:2023-08-21 14:53:16 configure libavahi-glib1:amd64 0.8-10 <none>
/var/log/dpkg.log.1:2023-08-21 14:53:16 status unpacked libavahi-glib1:amd64 0.8-10
```


70. View the system's kernel version.

```
(kali㉿kali)-[~]  
$ uname -r  
6.3.0-kali1-amd64
```

71. Display the system's memory usage.

```
(kali㉿kali)-[~]  
$ free -h
```

	total	used	free	shared	buff/cache	available
Mem:	1.9Gi	760Mi	665Mi	6.6Mi	685Mi	1.2Gi
Swap:	1.0Gi	0B	1.0Gi			

72. Show the system's disk usage.

```
(kali㉿kali)-[~]  
$ df -f  
df: invalid option -- 'f'  
Try 'df --help' for more information.
```

73. Check the system's uptime and load average.

```
(kali㉿kali)-[~]  
$ uptime  
16:19:26 up 1:05, 1 user, load average: 0.16, 0.11, 0.05
```

74. Display the current logged-in users.

```
(kali㉿kali)-[~]  
$ who  
kali      tty7      2024-09-08 15:15 (:0)
```

75. Check the identity of the current user.

```
(kali㉿kali)-[~]  
$ whoami  
kali
```

76. View the `/var/log/auth.log` file.

```
(kali㉿kali)-[~]  
$ sudo cat /var/log/auth.log  
cat: /var/log/auth.log: No such file or directory
```

77. Shred the `auth.log` file securely.

```
(kali㉿kali)-[~]  
$ sudo shred -u /var/log/auth.log  
shred: /var/log/auth.log: failed to open for writing: No such file or directory
```

78. How do you lock a user account to prevent them from logging in.

```
(kali㉿kali)-[~]
$ sudo usermod -l cyber
Usage: usermod [options] LOGIN

Options:
  -a, --append                append the user to the supplemental GROUPS
                              mentioned by the -G option without removing
                              the user from other groups
  -b, --badname               allow bad names
  -c, --comment COMMENT      new value of the GECOS field
  -d, --home HOME_DIR        new home directory for the user account
  -e, --expiredate EXPIRE_DATE set account expiration date to EXPIRE_DATE
  -f, --inactive INACTIVE    set password inactive after expiration
                              to INACTIVE
  -g, --gid GROUP            force use GROUP as new primary group
  -G, --groups GROUPS        new list of supplementary GROUPS
  -h, --help                 display this help message and exit
  -l, --login NEW_LOGIN      new value of the login name
  -L, --lock                 lock the user account
  -m, --move-home            move contents of the home directory to the
                              new location (use only with -d)
  -o, --non-unique           allow using duplicate (non-unique) UID
  -p, --password PASSWORD    use encrypted password for the new password
  -P, --prefix PREFIX_DIR    prefix directory where are located the /etc/* files
  -r, --remove               remove the user from only the supplemental GROUPS
                              mentioned by the -G option without removing
                              the user from other groups
  -R, --root CHROOT_DIR      directory to chroot into
  -s, --shell SHELL          new login shell for the user account
  -u, --uid UID              new UID for the user account
  -U, --unlock               unlock the user account
  -v, --add-subuids FIRST-LAST add range of subordinate uids
  -V, --del-subuids FIRST-LAST remove range of subordinate uids
  -w, --add-subgids FIRST-LAST add range of subordinate gids
  -W, --del-subgids FIRST-LAST remove range of subordinate gids
  -Z, --selinux-user SEUSER  new SELinux user mapping for the user account
```

79. What command would you use to change a user's default shell.

```
(kali㉿kali)-[~]
$ sudo chsh -s /bin/bash cyber
```

80. Display the system's boot messages.

```
(kali㉿kali)-[~]
$ dmesg
[ 0.000000] Linux version 6.3.0-kali1-amd64 (devel@kali.org) (gcc-12 (Debian 12.3.0-4) 12.3.0, GNU ld (Debian 2.40-2) 2.40-2)
[ 0.000000] Command line: BOOT_IMAGE=/boot/vmlinuz-6.3.0-kali1-amd64 root=UUID=0d9f25ad-336a-4e48-bf93-7-1kali1 (2023-06-29)
[ 0.000000] Disabled fast string operations
[ 0.000000] x86/fpu: Supporting XSAVE feature 0x001: 'x87 floating point registers'
[ 0.000000] x86/fpu: Supporting XSAVE feature 0x002: 'SSE registers'
[ 0.000000] x86/fpu: Supporting XSAVE feature 0x004: 'AVX registers'
[ 0.000000] x86/fpu: xstate_offset[2]: 576, xstate_sizes[2]: 256
[ 0.000000] x86/fpu: Enabled xstate features 0x7, context size is 832 bytes, using 'standard' format.
[ 0.000000] signal: max sigframe size: 1776
[ 0.000000] BIOS-provided physical RAM map:
[ 0.000000] BIOS-e820: [mem 0x0000000000000000-0x0000000000009f3ff] usable
[ 0.000000] BIOS-e820: [mem 0x0000000000009f400-0x0000000000009ffff] reserved
[ 0.000000] BIOS-e820: [mem 0x000000000000dc000-0x000000000000ffffff] reserved
[ 0.000000] BIOS-e820: [mem 0x00000000000100000-0x0000000000007fedffff] usable
[ 0.000000] BIOS-e820: [mem 0x0000000000007fee000-0x0000000000007fefefff] ACPI data
```

