



Merchant API Integration Guide

Submitted by:

Babar Razzaq

Chief Technology Officer | PostEx. | Paid

Head of Integration Services

Contact: babar@postex.pk | 0300-0441793

Custom APIs



Table of Contents

1. Paid – A Smart Payment Solution	5
2. Ecommerce Plugin	5
3. Integration APIs.....	6
3.1 Operational Cities API.....	6
3.1.1 URL.....	6
3.1.2 Request Parameters (GET).....	6
3.1.3 Response Parameters.....	6
3.2 Pickup Address API	8
3.2.1 URL.....	8
3.2.2 Request Parameters (GET).....	8
3.2.3 Response Parameters.....	8
3.3 Create Pickup Address API.....	10
3.3.1 URL.....	10
3.3.2 Request Parameters (POST).....	10
3.3.3 Response Parameters.....	11
3.4 Order Types API	11
3.4.1 URL.....	11
3.4.2 Request Parameters (GET).....	11
3.4.3 Response Parameters.....	11
3.5 Order Creation API.....	12
3.5.1 URL.....	12
3.5.2 Request Parameters (POST).....	12
3.5.3 Response Parameters.....	13
3.6 List Un-booked Orders.....	14
3.6.1 URL.....	14
3.6.2 Request Parameters (GET).....	14
3.6.3 Response Parameters.....	14

3.7 Generate Load Sheet.....	Error! Bookmark not defined.
3.7.1 URL.....	16
3.7.2 Request Parameters (POST).....	16
3.7.3 Response Parameters.....	17
3.8 Order Tracking API.....	17
3.8.1 URL.....	17
3.8.2 Request Parameters (GET).....	17
3.8.3 Response Parameters.....	18
3.9 Bulk Order Tracking API	20
3.9.1 URL.....	20
3.9.2 Request Parameters (GET).....	20
3.9.3 Response Parameters.....	20
3.10 Airway Bill API	23
3.10.1 URL (GET).....	23
3.10.2 Response Parameters.....	23
3.10.3 Note	23
3.11 Save Shipper Advice API.....	24
3.11.1 URL.....	24
3.11.2 Request Parameters (PUT).....	24
3.11.3 Response Parameters.....	24
3.12 Get Shipper Advice API.....	25
3.12.1 URL.....	25
3.12.2 Request Parameters (GET).....	25
3.12.3 Response Parameters.....	25
3.13 Order Cancel API.....	26
3.13.1 URL.....	26
3.13.2 Request Parameters (PUT).....	26
3.13.3 Response Parameters.....	26

3.14 Payment Status API.....	26
3.14.1 URL.....	26
3.14.2 Request Parameters (GET).....	26
3.14.3 Response Parameters.....	27
3.15 Order Status API	28
3.15.1 URL.....	28
3.15.2 Request Parameters (GET).....	28
3.15.3 Response Parameters.....	28
3.16 List Orders API	29
3.16.1 URL.....	29
3.16.2 Request Parameters (GET).....	29
3.16.3 Response Parameters.....	30

1. Paid – A Smart Payment Solution

Paid makes it very quick and easy for all-sized merchants, eCommerce sites and marketplaces to accept card payments. Paid pre-built integrations link seamlessly with your checkout page to ensure a quick and secure checkout flow for your customers.

Our responsive design displays checkout page correctly on all the devices. And our secure checkout builds confidence and increases conversions saving you cost and time to accepting payments.

The most reliable and secure payment gateway tailored to support your business accept online payments from your customers with one-click integration.

Accept payments from your customers through Pakistan's most secure and reliable Payment Gateway in Pakistan with simple one-click integration.

2. Ecommerce Plugin

Considering the market requirement and the technology revolution, Paid is significantly boosting its all merchants of major platforms like Shopify, Wordpress, Magento, OpenCart, ZenCart, PrestaShop, and even for the customized websites for Debit/Credit and Account transfers.



3. Integration APIs

3.1 Operational Cities API

3.1.1 URL

<https://api.postex.pk/services/integration/api/order/v2/get-operational-city>

3.1.2 Request Parameters (GET)

Parameter	Explanation	Condition	Data Type
Header			
token	A Unique token Specific to identify the Merchant request Parameters	Mandatory	String
operationalCityType (query param)	A variable to filter Cities for pickup or Delivery operationalCityType can only have 3 values: 1. Pickup 2. Delivery 3. Null	Optional	String

3.1.3 Response Parameters

Parameter	Explanation	Condition	Data Type
Response			
Http Status	200 – Successfully Cancelled 404 – Order Not Found	Mandatory	Number
operationalCityName	City Name	Mandatory	String
countryName	Country Name	Mandatory	String
isPickupCity	Boolean variable to identify either PostEx offer pickups in this city or not	Mandatory	Boolean
isDeliveryCity	Boolean variable to identify either PostEx offer deliveries in this city or not	Mandatory	Boolean

Response Parameters (JSON Format)

```
{
  "statusCode": "200",
  "statusMessage": "SUCCESSFULLY OPERATED",
  "dist": [
    {
      "operationalCityName":
"Lahore",
      "countryName": "Pakistan"
      "isPickupCity": "true"
      "isDeliveryCity": "true"
    },
    {
      "operationalCityName":
"Islamabad",
      "countryName": "Pakistan"
      "isPickupCity": "true"
      "isDeliveryCity": "true"
    },
    {
      "operationalCityName":
"Karachi",
      "countryName": "Pakistan"
      "isPickupCity": "true"
      "isDeliveryCity": "true"
    },
    {
      "operationalCityName":
"Rawalpindi",
      "countryName": "Pakistan"
      "isPickupCity": "true"
      "isDeliveryCity": "true"
    }
  ]
}
```

3.2 Pickup Address API

3.2.1 URL

<https://api.postex.pk/services/integration/api/order/v1/get-merchant-address>

3.2.2 Request Parameters (GET)

Parameter	Explanation	Condition	Data Type
Header			
token	A Unique token Specific to identify the Merchant request Parameters	Mandatory	String
cityName	Pickup City	Optional	String

3.2.3 Response Parameters

Parameter	Explanation	Condition	Data Type
Response			
statusCode	200 /400	Mandatory	Number
Parameter			
statusMessage	Successfully Operated	Mandatory	String
phone1	Merchant's warehouse phone 1	Mandatory	String
phone2	Merchant's warehouse phone 2	Mandatory	String
contactPersonName	Merchant's warehouse contact person name	Mandatory	String
cityName	Warehouse city	Mandatory	String
address	Warehouse physical address	Mandatory	String
addressCode	Merchant's warehouse address Code	Mandatory	String

Response

Parameters

(JSON Format)

```
{
  "statusCode": "200",
  "statusMessage": "SUCCESSFULLY OPERATED",
  "dist": [
    {
      "phone1": "+923XXXXXXXXX",
      "phone2": "+923XXXXXXXXX",
      "contactPersonName": "string",

```



```
        "cityName": "String",
        "address": "string"
        "addressCode": "string"
    },
    {
        "phone1": "+923XXXXXXXXXX",
        "phone2": "+923XXXXXXXXXX",
        "contactPersonName": "string",
        "cityName": "string",
        "address": "string"
        "addressCode": "string"
    }
]
```

3.3 Create Pickup Address API

3.3.1 URL

<https://api.postex.pk/services/integration/api/order/v2/create-merchant-address>

3.3.2 Request Parameters (POST)

Parameter	Explanation	Condition	Data Type
Header			
token	A Unique token Specific to identify the Merchant request Parameters	Mandatory	String
Request			
address	Warehouse physical address	Mandatory	String
addressTypeId	Merchant Address Type 1- Return 2- Pickup	Mandatory	Number
cityName	Warehouse city	Mandatory	String
contactPersonName	Merchant's warehouse contact person name	Mandatory	String
phone1	Merchant's warehouse phone 1	Mandatory	String
phone2	Merchant's warehouse phone 2	Mandatory	String
phone3	Warehouse Manager Phone Number	Optional	String
wareHouseManagerName	Warehouse Manager Name	Optional	String

Request Parameters (JSON Format)

```
{
  "address": "string",
  "addressTypeId": 0,
  "cityName": "string",
  "contactPersonName": "string",
  "phone1": "string",
  "phone2": "string",
  "phone3": "string",
  "wareHouseManagerName": "string"
}
```

3.3.3 Response Parameters

Parameter	Explanation	Condition	Data Type
Response			
statusCode	200 /400	Mandatory	Number
statusMessage	Successfully Operated	Mandatory	String

3.4 Order Types API

3.4.1 URL

<https://api.postex.pk/services/integration/api/order/v1/get-order-types>

3.4.2 Request Parameters (GET)

Parameter	Explanation	Condition	Data Type
Header			
token	A Unique token Specific to identify the Merchant request Parameters	Mandatory	String

3.4.3 Response Parameters

Parameter	Explanation	Condition	Data Type
Response			
statusCode	200 /400	Mandatory	Number
statusMessage	Successfully Operated	Mandatory	String
dist	String of Values as below Normal Reversed Replacement	Mandatory	String

Response Parameters (JSON Format)

```
{
  "statusCode": "200",
  "statusMessage": "SUCCESSFULLY OPERATED",
  "dist": [
    "Normal",
    "Reversed",
    "Replacement"
  ]
}
```

3.5 Order Creation API

3.5.1 URL

<https://api.postex.pk/services/integration/api/order/v3/create-order>

3.5.2 Request Parameters (POST)

Parameter	Explanation	Condition	Data Type
Header			
token	A Unique token Specific to identify the Merchant request Parameters	Mandatory	String
Request			
orderRefNumber	Order Reference Number shared by the Merchant.	Mandatory	String
invoicePayment	Transaction Amount	Mandatory	String
orderDetail	Detail About Order or Product purchases, Quantity, SKU etc	Optional	String
customerName	Customer complete name	Mandatory	String
customerPhone	Format: 03xxxxxxxxx	Mandatory	String
deliveryAddress	Customer's email address	Mandatory	String
transactionNotes	Additional Notes for order	Optional	String
cityName	Customer's City Name	Mandatory	String
invoiceDivision	Split Airway Bills for Larger orders that have multiple packaging envelops	Mandatory	Number
items	Number of Pieces in Order	Mandatory	Number
pickupAddressCode	Address code to identify pickup address	Optional	String
storeAddressCode	Address code to identify pickup address store wise	Optional	String
orderType	A variable to identify order type orderType can only have 3 values: 1. Normal 2. Reverse 3. Replacement	Mandatory	String

Request Parameters (JSON Format)

```
{
  "cityName": "string",
  "customerName": "string",
  "customerPhone": "string",
```

```
"deliveryAddress": "string",
"invoiceDivision": 0,
"invoicePayment": 0,
"items": 0,
"orderDetail": "string",
"orderRefNumber": "string",
"orderType": "string",
"transactionNotes": "string",
"pickupAddressCode": "string"
"storeAddressCode": "string"

}
```

3.5.3 Response Parameters

Parameter	Explanation	Condition	Data Type
Response			
trackingNumber	A unique tracking number to track the order over PostEx website as well as Merchant Application	Mandatory	String

Response Parameters (JSON Format)

```
{
  "statusCode": "200",
  "statusMessage": "ORDER HAS BEEN CREATED",
  "dist": {
    "trackingNumber": "CX-XXXXXXXXXXXX",
    "orderStatus": "UnBooked",
    "orderDate": "yyyy-mm-dd hh:mm:ss"
  }
}
```

3.6 List Un-booked Orders

3.6.1 URL

<https://api.postex.pk/services/integration/api/order/v2/get-unbooked-orders>

3.6.2 Request Parameters (GET)

Parameter	Explanation	Condition	Data Type
Header			
token	A Unique token Specific to identify the Super Merchant request Parameters	Mandatory	String
startDate	Start date of orders with status Un-booked	Mandatory	String
endDate	End date of orders with status Un-booked	Mandatory	String
cityName	Pickup City	Optional	String

Request Parameters (JSON Format)

```
{
  "startDate": "yyyy-mm-dd",
  "endDate": "yyyy-mm-dd",
  "cityName": "String",
}
```

3.6.3 Response Parameters

Parameter	Explanation	Condition	Data Type
Response			
customerName	Customer complete name	Mandatory	String
customerPhone	Format: 03xxxxxxxx	Mandatory	String
deliveryAddress	Customer's email address	Mandatory	String
invoicePayment	Transaction Amount	Mandatory	Decimal
orderDetail	Detail About Order or Product purchases, Quantity, SKU etc	Optional	String
orderPickupDate	Order Pickup Date	Optional	Date
orderDeliveryDate	Order Delivery Date	Optional	Date
orderRefNumber	Order Reference Number provided by the Merchant at time of posting order	Mandatory	String
transactionTax	Transaction Tax	Optional	Decimal
transactionFee	Transaction Fee	Optional	Decimal

trackingNumber	A unique tracking number to track the order over PostEx website as well as Merchant Application	Mandatory	String
transactionDate	Order Creation Date	Mandatory	
upfrontPayment	Upfront Payment Amount	Optional	Decimal
upfrontPaymentDate	Upfront Payment Date	Optional	Date
merchantName	Merchant Registered Name at PostEx	Mandatory	String
transactionStatus	Order's current status	Optional	String
reversalTax	Transaction Fee in case of Reversal	Optional	Decimal
reversalFee	Transaction Tax in case of Reversal	Optional	Decimal
cityName	City Name	Mandatory	String
transactionNotes	Additional Notes provided by the Merchant at time of posting order	Optional	String
reservePayment	Order's Reserve Amount	Optional	Decimal
reservePaymentDate	Order's Date when the Reserve Payment is made	Optional	Date
balancePayment	Order's Balance Amount in case of reversal	Optional	Decimal

Response Parameters (JSON Format)

```

{
  "statusCode": "200",
  "statusMessage": "SUCCESSFULLY OPERATED",
  "dist": [
    {
      "customerName": "",
      "customerPhone": "",
      "deliveryAddress": "",
      "invoicePayment": 0,
      "orderDetail": "",
      "orderRefNumber": "",
      "transactionTax": 0,
      "transactionFee": 0,
      "trackingNumber": "CX-XXXXXXXXXXXX ",
      "transactionDate": "YYYY-MM-DD",
      "upfrontPayment": 0,
      "merchantName": "",
      "transactionStatus": "",
      "reversalTax": 0,
      "reversalFee": 0,
      "cityName": "",
      "transactionNotes": "",
      "balancePayment": 0,
      "items": 0,
      "invoiceDivision": 0
    }
  ],

```

```

{
  "customerName": "",
  "customerPhone": "",
  "deliveryAddress": "",
  "invoicePayment": 0,
  "orderDetail": "",
  "orderRefNumber": "",
  "transactionTax": 0,
  "transactionFee": 0,
  "trackingNumber": "CX-XXXXXXXXXXXX ",
  "transactionDate": "YYYY-MM-DD",
  "upfrontPayment": 0,
  "merchantName": "",
  "transactionStatus": "",
  "reversalTax": 0,
  "reversalFee": 0,
  "cityName": "",
  "transactionNotes": "",
  "balancePayment": 0,
  "items": 0,
  "invoiceDivision": 0
}
]
}

```

3.7 Generate Load Sheet

3.7.1 URL

<https://api.postex.pk/services/integration/api/order/v2/generate-load-sheet>

3.7.2 Request Parameters (POST)

Parameter	Explanation	Condition	Data Type
Header			
token	A Unique token Specific to identify the Super Merchant request Parameters	Mandatory	String
Request			
trackingNumbers	PostEx provided tracking numbers of orders	Mandatory	List of String
pickupAddress	Pickup address from where parcel will be picked	Optional	String

Request Parameters (JSON Format)

```

{
  "pickupAddress": "Pickup Address",
  "trackingNumbers": [

```



```
        "TrackingNumber1",  
        " TrackingNumber2",  
    " TrackingNumber3"  
    ]  
}
```

3.7.3 Response Parameters

Parameter	Explanation	Condition	Data Type
Response			
PDF	PDF File	Mandatory	PDF

3.8 Order Tracking API

3.8.1 URL

<https://api.postex.pk/services/integration/api/order/v1/track-order/{trackingNumber}>

3.8.2 Request Parameters (GET)

Parameter	Explanation	Condition	Data Type
Header			
token A Unique token	Specific to identify the Merchant request Parameters	Mandatory	String
Request			
trackingNumber	A unique tracking number to track the order over PostEx website as well as Merchant Application	Mandatory	String

3.8.3 Response Parameters

Parameter	Explanation	Condition	Data Type
Response			
customerName	Customer complete name	Mandatory	String
customerPhone	Format: 03xxxxxxxx	Mandatory	String
deliveryAddress	Customer's email address	Mandatory	String
invoicePayment	Transaction Amount	Mandatory	Decimal
orderDetail	Detail About Order or Product purchases, Quantity, SKU etc	Optional	String
orderPickupDate	Order Pickup Date	Optional	Date
orderDeliveryDate	Order Delivery Date	Optional	Date
orderRefNumber	Order Reference Number provided by the Merchant at time of posting order	Mandatory	String
transactionTax	Transaction Tax	Optional	Decimal
transactionFee	Transaction Fee	Optional	Decimal
trackingNumber	A unique tracking number to track the order over PostEx website as well as Merchant Application	Mandatory	String
transactionDate	Order Creation Date	Mandatory	
upfrontPayment	Upfront Payment Amount	Optional	Decimal
upfrontPaymentDate	Upfront Payment Date	Optional	Date
merchantName	Merchant Registered Name at PostEx	Mandatory	String
transactionStatus	Order's current status	Optional	String
reversalTax	Transaction Fee in case of Reversal	Optional	Decimal
reversalFee	Transaction Tax in case of Reversal	Optional	Decimal
cityName	City Name	Mandatory	String
transactionNotes	Additional Notes provided by the Merchant at time of posting order	Optional	String
reservePayment	Order's Reserve Amount	Optional	Decimal
reservePaymentDate	Order's Date when the Reserve Payment is made	Optional	Date
balancePayment	Order's Balance Amount in case of reversal	Optional	Decimal

transactionStatusHistory	ack of Order Journey. Below are the possible values against MessageCodes	Optional	String
	0001 At Merchant's Warehouse		
	0002 Returned		
	0003 At PostEx Warehouse		
	0004 Package on Root		
	0005 Delivered		
	0006 Returned		
	0007 Returned		
	0008 Delivery Under Review		
	0013 Attempt Made: <i>Reason Here</i>		

Response Parameters (JSON Format)

```

{
  "statusCode": "200",
  "statusMessage": "SUCCESSFULLY OPERATED",
  "dist": {
    "customerName": "",
    "customerPhone": "",
    "deliveryAddress": "",
    "invoicePayment": 0,
    "orderDetail": "",
    "orderRefNumber": "",
    "transactionTax": 0,
    "transactionFee": 0,
    "trackingNumber": "",
    "transactionDate": "",
    "upfrontPayment": 0,
    "merchantName": "",
    "transactionStatus": "",
    "reversalTax": 0,
    "reversalFee": 0,
    "reservePayment": 0,
    "reservePaymentDate": "",
    "balancePayment": 0,
    "cityName": "",
    "transactionNotes": "",
    "transactionStatusHistory": [
      {
        "transactionStatusMessage": "At Merchant's Warehouse",
        "transactionStatusMessageCode": "0001"
      }
    ]
  }
}

```

3.9 Bulk Order Tracking API

3.9.1 URL

<https://api.postex.pk/services/integration/api/order/v1/track-bulk-order>

3.9.2 Request Parameters (GET)

Parameter	Explanation	Condition	Data Type
Header			
token	A Unique token Specific to identify the Merchant request Parameters	Mandatory	String
Request			
trackingNumber	List of commas separated unique tracking numbers	Mandatory	Array of Strings

Request Parameters (JSON Format)

```
{
  "trackingNumber": [
    "TrackingNumber1",
    " TrackingNumber2",
    " TrackingNumber3"
  ]
}
```

3.9.3 Response Parameters

Parameter	Explanation	Condition	Data Type
Response			
customerName	Customer complete name	Mandatory	String
customerPhone	Format: 03xxxxxxxxx	Mandatory	String
deliveryAddress	Customer's email address	Mandatory	String
invoicePayment	Transaction Amount	Mandatory	Decimal
orderDetail	Detail About Order or Product purchases, Quantity, SKU etc	Optional	String
orderPickupDate	Order Pickup Date	Optional	Date
orderDeliveryDate	Order Delivery Date	Optional	Date
orderRefNumber	Order Reference Number provided by the Merchant at time of posting order	Mandatory	String
transactionTax	Transaction Tax	Optional	Decimal
transactionFee	Transaction Fee	Optional	Decimal

trackingNumber	A unique tracking number to track the order over PostEx website as well as Merchant Application	Mandatory	String
transactionDate	Order Creation Date	Mandatory	
upfrontPayment	Upfront Payment Amount	Optional	Decimal
upfrontPaymentDate	Upfront Payment Date	Optional	Date
merchantName	Merchant Registered Name at PostEx	Mandatory	String
transactionStatus	Order's current status	Optional	String
reversalTax	Transaction Fee in case of Reversal	Optional	Decimal
reversalFee	Transaction Tax in case of Reversal	Optional	Decimal
cityName	City Name	Mandatory	String
transactionNotes	Additional Notes provided by the Merchant at time of posting order	Optional	String
reservePayment	Order's Reserve Amount	Optional	Decimal
reservePaymentDate	Order's Date when the Reserve Payment is made	Optional	Date
balancePayment	Order's Balance Amount in case of reversal	Optional	Decimal
transactionStatusHistory	The Complete Track of Order Journey. Below are the possible Values against MessageCodes	Optional	String
Parameter	Explanation	Condition	Data Type
	0001 At Merchant's Warehouse		
	0002 Returned		
	0003 At PostEx Warehouse		
	0004 Package on Root		
	0005 Delivered		
	0006 Returned		
	0007 Returned		
	0008 Delivery Under Review		
	0013 Attempt Made: <i>Reason Here</i>		

Response Parameters (JSON Format)

```

{
  "statusCode": "200",
  "statusMessage": "SUCCESSFULLY OPERATED",
  "dist": [
    {
      "trackingResponse": {
        "customerName": "",
        "customerPhone": "",
        "deliveryAddress": "",
        "invoicePayment": 0,

```

```

        "orderDetail": "",
        "orderRefNumber": "",
        "transactionTax": 0,
        "transactionFee": 0,
        "trackingNumber": "TrackingNumber1",
        "transactionDate": "yyyy-mm-dd",
        "upfrontPayment": 0,
        "merchantName": "",
        "transactionStatus": "",
        "reversalTax": 0,
        "reversalFee": 0,
        "cityName": "",
        "transactionNotes": "",
        "balancePayment": 0,
        "items": 0,
    "invoiceDivision": 0
    },
    "trackingNumber": "TrackingNumber1",
    "message": "SUCCESSFULLY RETRIEVE ORDER"
},
{
    "trackingResponse": {
        "customerName": "",
        "customerPhone": "",
        "deliveryAddress": "",
        "invoicePayment": 0,
        "orderDetail": "",
        "orderRefNumber": "",
        "transactionTax": 0,
        "transactionDate": "yyyy-mm-dd",
        "upfrontPayment": 0,
        "merchantName": "",
        "transactionStatus": "",
        "reversalTax": 0,
        "reversalFee": 0,
        "cityName": "",
        "transactionNotes": "",
        "balancePayment": 0,
        "items": 0,
        "transactionFee": 0,
    }
    "trackingNumber": "TrackingNumber2",
    "message": "SUCCESSFULLY RETRIEVE ORDER"
}
]
}

```

3.10 Airway Bill API

3.10.1 URL (GET)

<https://api.postex.pk/services/integration/api/order/v1/get-invoice?trackingNumbers=CXXXXXXXXXX1,CX-XXXXXXXXXX2>

3.10.2 Response Parameters

Parameter	Explanation	Condition	Data Type
Response			
PDF	PDF File	Mandatory	PDF

3.10.3 Note

PDF will be generated for a maximum of 10 tracking numbers.

3.11 Save Shipper Advice API

3.11.1 URL

<https://api.postex.pk/service/integration/api/order/v2/save-shipper-advice>

3.11.2 Request Parameters (PUT)

Parameter	Explanation	Condition	Data Type
Header			
token	A Unique token Specific to identify the Merchant request Parameters	Mandatory	String
Request			
trackingNumber	A unique tracking number to track the order over PostEx website as well as Merchant Application	Mandatory	String
statusId	A unique status ID to give shipper advice on any attempted parcel. 1 – Mark Return Requested 2 – Mark Retry Attempt	Mandatory	Decimal
remarks	Remarks against tracking Number	Mandatory	String

Request Parameters (JSON Format)

```
{
  "trackingNumber": "CX-XXXXXXXXXX",
  "statusId": 0,
  "remarks": ""
}
```

3.11.3 Response Parameters

Parameter	Explanation	Condition	Data Type
Response			
HTTP Status	200 if success 400 if bad request	Mandatory	Number

3.12 Get Shipper Advice API

3.12.1 URL

<https://api.postex.pk/service/integration/api/order/v1/get-shipper-advice/{trackingNumber}>

3.12.2 Request Parameters (GET)

Parameter	Explanation	Condition	Data Type
Header			
token	A Unique token Specific to identify the Merchant request Parameters	Mandatory	String
Request			
trackingNumber	A unique tracking number to track the order over PostEx website as well as Merchant Application	Mandatory	String

3.12.3 Response Parameters

Parameter	Explanation	Condition	Data Type
Response			
trackingNumber	A unique tracking number to track the order over PostEx website as well as Merchant Application	Mandatory	String
remarks	Saved remarks against shipper advice	Mandatory	String
remarksDate	Date and Time of remarks entered	Mandatory	String
Username	User who saved the remarks	Mandatory	String

Response Parameters (JSON Format)

```
{
  "statusCode": "200",
  "statusMessage": "SUCCESSFULLY OPERATED",
  "dist": [
    {
      "trackingNumber": "CX-XXXXXXXXXXXX",
      "message": "SUCCESSFULLY Operated",
      "trackingResponse": [
        {
          "remarks": "",
          "remarksDate": "yyyy-mm-dd",
          "username": ""
        },
        {
          "remarks": "",

```

```

        "remarksDate": "yyyy-mm-dd",
        "username": ""
    }
}
]
}

```

3.13 Order Cancel API

3.13.1 URL

<https://api.postex.pk/services/integration/api/order/v1/cancel-order>

3.13.2 Request Parameters (PUT)

Parameter	Explanation	Condition	Data Type
Header			
Token	A Unique token Specific to identify the Merchant request Parameters	Mandatory	String
Request			
trackingNumber	A provided tracking number to cancel the order	Mandatory	String

3.13.3 Response Parameters

Parameter	Explanation	Condition	Data Type
Response			
Http Status	200 – Successfully Cancelled 404 – Order Not Found	Mandatory	Number

3.14 Payment Status API

3.14.1 URL

<https://api.postex.pk/services/integration/api/order/v1/payment-status/{trackingNumber}>

3.14.2 Request Parameters (GET)

Parameter	Explanation	Condition	Data Type
Header			
token	A Unique token Specific to identify the Merchant request Parameters	Mandatory	String

trackingNumber	A provided tracking number to unbook order from cancel state	Mandatory	String
----------------	--	-----------	--------

3.14.3 Response Parameters

Parameter	Explanation	Condition	Data Type
Response			
Http Status	404 – Order Not Found	Mandatory	Number
	200 – SUCCESSFULLY OPERATED		
orderRefNumber	Order Reference Number shared by the Merchant.	Mandatory	String
trackingNumber	A unique tracking number to track the order over PostEx website as well as Merchant Application	Mandatory	String
settle	A flag to indicate either the payment is made or not.	Mandatory	Boolean
settlementDate	Date for which the final settlement was made.	Optional	Date
upfrontPaymentDate	Date for which the upfront payment was made	Optional	Date
cprNumber_1	Cash Payment Receipt number for upfront payment	Optional	String
reservePaymentDate	Date for which the reserve payment was made	Optional	Date
cprNumber_2	Cash Payment Receipt number for reserve payment	Optional	String

Response Parameters (JSON Format)

```
{
  "statusCode": "200",
  "statusMessage": "SUCCESSFULLY OPERATED",
  "dist": {
    "orderRefNumber": "",
    "trackingNumber": "CX-XXXXXXXXXXXX",
    "settle": true,
    "settlementDate": "",
    "upfrontPaymentDate": "",
    "cprNumber_1": "",
    "reservePaymentDate": "",
    "cprNumber_2": ""
  }
}
```

```
}

```

3.15 Order Status API

3.15.1 URL

<https://api.postex.pk/services/integration/api/order/v1/get-order-status>

3.15.2 Request Parameters (GET)

Parameter	Explanation	Condition	Data Type
Header			
token	A Unique token Specific to identify the Merchant request Parameters	Mandatory	String

3.15.3 Response Parameters

Parameter	Explanation	Condition	Data Type
Response			
statusCode	200 /400	Mandatory	Number
statusMessage	Successfully Operated	Mandatory	String
dist	String of Values as below 1. Unbooked 2. Booked 3. PostEx WareHouse 4. Out For Delivery 5. Delivered 6. Returned 7. Un-Assigned By Me 8. Expired 9. Delivery Under Review 15 Picked By PostEx 16 Out For Return 17 Attempted 18 En-Route to PostEx warehouse	Mandatory	String

Response Parameters (JSON Format)

```
{
  "statusCode": "200",
  "statusMessage": "SUCCESSFULLY OPERATED",
  "dist": [

```

```
    "Unbooked",
    "Booked",
    "PostEx WareHouse",
    "Out For Delivery",
    "Delivered",
    "Returned",
    "Un-Assigned By Me",
    "Expired",
    "Delivery Under Review",
    "Picked By PostEx",
    "Out For Return",
    "Attempted",
    "En-Route to PostEx warehouse"
  ]
}
```

3.16 List Orders API

3.16.1 URL

<https://api.postex.pk/services/integration/api/order/v1/get-all-order>

3.16.2 Request Parameters (GET)

Parameter	Explanation	Condition	Data Type
Header			
token	A Unique token Specific to identify the Merchant request Parameters	Mandatory	String
Request			

orderStatusID	Order Status ID. Possible Values are 1. Unbooked 2. Booked 3. PostEx WareHouse 4. Out For Delivery 5. Delivered 6. Returned 7. Un-Assigned By Me 8. Expired 9. Delivery Under Review 15 Picked By PostEx 16. Out For Return 17 Attempted 18. En-Route to PostEx warehouse Note: Use Zero (0) to list All Orders	Mandatory	Number
fromDate	Order Creation Start Date	Mandatory	Date
toDate	Order Creation End Date	Mandatory	Date

Request Parameters (JSON Format)

```
{
  "orderStatusID": 0,
  "fromDate": "yyyy-mm-dd",
  "toDate": "yyyy-mm-dd"
}
```

3.16.3 Response Parameters

Parameter	Explanation	Condition	Data Type
Response			
customerName	Customer complete name	Mandatory	String
customerPhone	Format: 03xxxxxxxxx	Mandatory	String
deliveryAddress	Customer's email address	Mandatory	String
invoicePayment	Transaction Amount	Mandatory	Decimal
orderDetail	Detail About Order or Product purchases, Quantity, SKU etc	Optional	String
orderPickupDate	Order Pickup Date	Optional	Date

orderDeliveryDate	Order Delivery Date	Optional	Date
orderRefNumber	Order Reference Number provided by the Merchant at time of posting order	Mandatory	String
transactionTax	Transaction Tax	Optional	Decimal
transactionFee	Transaction Fee	Optional	Decimal
trackingNumber	A unique tracking number to track the order over PostEx website as well as Merchant Application	Mandatory	String
transactionDate	Order Creation Date	Mandatory	
upfrontPayment	Upfront Payment Amount	Optional	Decimal
upfrontPaymentDate	Upfront Payment Date	Optional	Date
merchantName	Merchant Registered Name at PostEx	Mandatory	String
transactionStatus	Order's current status	Optional	String
reversalTax	Transaction Fee in case of Reversal	Optional	Decimal
reversalFee	Transaction Tax in case of Reversal	Optional	Decimal
cityName	City Name	Mandatory	String
transactionNotes	Additional Notes provided by the Merchant at time of posting order	Optional	String
reservePayment	Order's Reserve Amount	Optional	Decimal
reservePaymentDate	Order's Date when the Reserve Payment is made	Optional	Date
balancePayment	Order's Balance Amount in case of reversal	Optional	Decimal
transactionStatusHistory	<p>ack of Order Journey. Below are the possible values against MessageCodes</p> <p>0001 At Merchant's Warehouse</p> <p>0002 Returned</p> <p>0003 At PostEx Warehouse</p>	Optional	String
Parameter	Explanation	Condition	Data Type
	<p>0004 Package on Root</p> <p>0005 Delivered</p> <p>0006 Returned</p> <p>0007 Returned</p> <p>0008 Delivery Under Review</p> <p>0013 Attempt Made: <i>Reason Here</i></p>		

Response Parameters (JSON Format)

```
{
  "statusCode": "200",
  "statusMessage": "SUCCESSFULLY OPERATED",
```

```
"dist": [  
  {  
    "trackingResponse": {  
      "customerName": "",  
      "customerPhone": "",  
      "deliveryAddress": "",  
      "invoicePayment": 0,  
      "orderDetail": "",  
      "orderRefNumber": "",  
      "transactionTax": 0,  
      "transactionFee": 0,  
      "trackingNumber": "TrackingNumber1",  
      "transactionDate": "yyyy-mm-dd",  
      "upfrontPayment": 0,  
      "merchantName": "",  
      "transactionStatus": "",  
      "reversalTax": 0,  
      "reversalFee": 0,  
      "cityName": "",  
      "transactionNotes": "",  
      "balancePayment": 0,  
      "items": 0,  
      "invoiceDivision": 0  
    },  
    "trackingNumber": "TrackingNumber1",  
    "message": "SUCCESSFULLY RETRIEVE ORDER"  
  },  
  {  
    "trackingResponse": {  
      "customerName": "",  
      "customerPhone": "",  
      "deliveryAddress": "",  
      "invoicePayment": 0,  
      "orderDetail": "",  
      "orderRefNumber": "",  
      "transactionTax": 0,  
      "transactionFee": 0,  
      "trackingNumber": "TrackingNumber1",  
      "transactionDate": "yyyy-mm-dd",  
      "upfrontPayment": 0,  
      "merchantName": "",  
      "transactionStatus": "",  
      "reversalTax": 0,  
      "reversalFee": 0,  
      "cityName": "",  
      "transactionNotes": "",  
      "balancePayment": 0,  
      "items": 0,  
      "invoiceDivision": 0  
    },  
    "trackingNumber": "TrackingNumber1",  
    "message": "SUCCESSFULLY RETRIEVE ORDER"  
  }  
]
```



```
    "orderDetail": "",
    "orderRefNumber": "",
    "transactionTax": 0,
    "transactionFee": 0,
    "trackingNumber": "TrackingNumber2",
    "transactionDate": "yyyy-mm-dd",
    "upfrontPayment": 0,
    "merchantName": "",
    "transactionStatus": "",
    "reversalTax": 0,
    "reversalFee": 0,
    "cityName": "",
    "transactionNotes": "",
    "balancePayment": 0,
    "items": 0,
    "invoiceDivision": 0
  },
  "trackingNumber": "TrackingNumber2",
  "message": "SUCCESSFULLY RETRIEVE ORDER"
}
]
```

Note: Please feel free to write at support@postex.pk in case of any query(s).