


YOUR FIRST APPLICATION


Kamal Beydoun

Lebanese University – Faculty of Sciences I

Kamal.beydoun@ul.edu.lb




A BRIEF OVERVIEW OF AN ASP.NET CORE APPLICATION



CREATE NEW WEB APPLICATION

- Visual Studio

UNDERSTANDING THE PROJECT LAYOUT



.CSPROJ PROJECT FILE: DECLARING YOUR DEPENDENCIES

- **Purpose of .csproj file.**
 - Project file for .NET applications.
- **Key Details in .csproj:**
 - Information necessary for .NET tooling to build the project.
- **Project Type Definition.**
 - Specifies the type of project (web app, console app, or library).
- **Targeted Platforms.**
 - Defines the platforms the project targets (e.g., .NET Core 3.1, .NET 7).
- **Dependency Management.**
 - Lists the NuGet packages the project depends on.

PROGRAM.CS FILE: DEFINING YOUR APPLICATION

- **ASP.NET Core Application Initialization:**
 - All ASP.NET Core applications **begin** as a **.NET Console application**.
- **Transition in .NET 6:**
 - In .NET 6, ASP.NET Core applications typically start as programs with top-level statements.
- **Top-Level Statements:**
 - Startup code is directly written in a file instead of inside a static void Main function.
 - You can write the body of this method directly in the file, and the compiler generates the Main method for you.

PROGRAM.CS FILE: DEFINING YOUR APPLICATION

```
WebApplicationBuilder builder = WebApplication.CreateBuilder(args); ❶  
WebApplication app = builder.Build();                                ❷  
  
app.MapGet("/", () => "Hello World!");                             ❸  
  
app.Run();                                                         ❹
```

- ❶ Creates a `WebApplicationBuilder` using the `CreateBuilder` method
- ❷ Builds and returns an instance of `WebApplication` from the `WebApplicationBuilder`
- ❸ Defines an endpoint for your application, which returns `Hello World!` when the path `"/"` is called
- ❹ Runs the `WebApplication` to start listening for requests and generating responses

ADDING FUNCTIONALITY TO YOUR APPLICATION

```
using Microsoft.AspNetCore.HttpLogging;

WebApplicationBuilder builder = WebApplication.CreateBuilder(args);

builder.Services.AddHttpLogging(opts =>           ❶
    opts.LoggingFields = HttpLoggingFields.RequestProperties); ❶

builder.Logging.AddFilter(                        ❷
    "Microsoft.AspNetCore.HttpLogging", LogLevel.Information); ❷

WebApplication app = builder.Build();

if (app.Environment.IsDevelopment())              ❸
{
    app.UseHttpLogging();                          ❹
}

app.MapGet("/", () => "Hello World!");

app.MapGet("/person", () => new Person("Andrew", "Lock")); ❺

app.Run();

public record Person(string FirstName, string LastName); ❻
```

- ❶ You can customize features by adding or customizing the services of the application.
- ❷ Ensures that logs added by the HTTP logging middleware are visible in the log output
- ❸ You can add middleware conditionally, depending on the runtime environment.
- ❹ The HTTP logging middleware logs each request to your application in the log output.
- ❺ Creates a new endpoint that returns the C# object serialized as JSON
- ❻ Creates a record type

ADDING FUNCTIONALITY TO YOUR APPLICATION




Figure 3.8 Calling the `/person` endpoint returns a JSON-serialized version of the `Person` record instance. Details about each request are logged to the console by the `HttpLoggingMiddleware`.

ADDING AND CONFIGURING SERVICES

- **ASP.NET Core Design Approach:**
 - Utilizes small modular components for **distinct** features.
 - Enables independent evolution of features with **loose coupling**.
- **Modular Components in Applications:**
 - Exposed as one or more services within the application.
 - These services are used by the application.

DEFINING HOW REQUESTS ARE HANDLED WITH MIDDLEWARE AND ENDPOINTS

WebApplication Instance Abilities:

- **Add Middleware to Pipeline:**
 - Middleware, **small components** executed sequentially on HTTP requests.
 - logging, user identification, static file serving, error handling.
 - Added using Use* extension methods.
 - Sequence of Use* calls in the builder determines execution order in the final pipeline.
- **Map Endpoints:**
 - Generate response for requests by endpoint mapping.
 - Defines application responses to specific requests.
- **Run the Application:**
 - Execute application by calling Run() method.

DEFINING HOW REQUESTS ARE HANDLED WITH MIDDLEWARE AND ENDPOINTS

- WebApplication automatically adds more middleware, including two of the most important and substantial pieces of middleware in the pipeline:
 - the **routing** middleware
 - the **endpoint** middleware.

```
app.MapGet("/", () => "Hello World!");  
app.MapGet("/person", () => new Person("Andrew", "Lock"));
```

