


<b>Course Title:</b>	Signals and Systems II
<b>Course Number:</b>	ELE632
<b>Semester/Year (e.g.F2016)</b>	W2022

<b>Instructor:</b>	Dimitri Androutsos
--------------------	--------------------

<i>Assignment/Lab Number:</i>	2
<i>Assignment/Lab Title:</i>	Time-Domain Analysis of Discrete-Time Systems - Part 2

<i>Submission Date:</i>	Tuesday, February 20 <sup>th</sup> , 2022
<i>Due Date:</i>	Tuesday, February 20 <sup>th</sup> , 2022

<b>Student LAST Name</b>	<b>Student FIRST Name</b>	<b>Student Number</b>	<b>Section</b>	<b>Signature*</b>
Fahmy	Ahmad	500913092	9	

*\*By signing above, you attest that you have contributed to this submission and confirm that all work you have contributed to this submission is your own work. Any suspicion of copying or plagiarism in this work will result in an investigation of Academic Misconduct and may result in a "0" on the work, an "F" in the course, or possibly more severe penalties, as well as a Disciplinary Notice on your academic record under the Student Code of Academic Conduct, which can be found online at:*

<https://www.ryerson.ca/senate/policies/pol60.pdf>

## **Appendix**

<b><u>A) Unit Impulse Response</u></b> .....	3
Part 1 - Filter to Recieve Unit Impulse Response .....	3
Function I .....	3
Function II-.....	4
Part 2 - Hand Calculations .....	6
Part 3 - Comparison of Hand & MATLAB Calculations .....	8
<b><u>B) Zero Input Response</u></b> .....	9
<b><u>C) Zero State Response</u></b> .....	10
<b><u>D) Total Response</u></b> .....	11
Part I - Total response .....	10
Part II - Total response by Summation of Zero Input and Zero state.....	12
Responses .....	12
<b><u>E) Convolution and System Stability</u></b> .....	13
Part I - conv command .....	13
Part II.....	14
Part III .....	15
<b><u>F) Moving Average Filter</u></b> .....	15
Part I - Constant Coefficient Difference Equation with $h[n]$ Impulse .....	15
Response.....	15
Part II & III - MATLAB Function for N-point moving-average filter .....	15

## A) Unit Impulse Response


### Part 1 - Filter to Receive Unit Impulse Response Function I

```
n = 0:10;

b = [1/3 0 0];
a = [1 1/6 -1/6];
% delta = 1.0.*((n)==0);
delta = (n)==0;
% figure;
% stem(n, delta);
% title('Part A.1 - Unit Impulse')
% axis([-0.5 0.5 -0.1 1.2])
% xlabel('n')

h = filter(b, a, delta);

figure;
stem(n, h, 'k');
title('Part A.1 - Function I Unit Impulse Response')
axis([-0.5 10.5 -0.1 0.5])
xlabel('n')
ylabel('h[n]')
```



## Function II

```

n = 0:10;


b = [1 0 0];
a = [1 0 1/4];
delta = (n)==0;

h = filter(b, a, delta(n));
clf;

stem(n, h, 'k');
title('Part A.1 - Function II Unit Impulse Response')
axis([-0.5 10.5 -0.3 1.1])
xlabel('n')
ylabel('h[n]')

```

### Part A.1 - Function II Unit Impulse Response



## Part 2 – Hand Calculations

### A.2 - Function I

$$x^2 + \frac{1}{6}x - \frac{1}{8} = 0$$

$$x_{1,2} = \frac{-1/6 \pm \sqrt{(1/6)^2 - 4(-1/8)}}{2}$$

$$= \frac{-1/6 \pm 5/6}{2}$$

$$x_{1,2} = 1/3, -1/2$$

$$y[n] = C_1 (1/3)^n + C_2 (-1/2)^n$$

$$h[n] + 1/6 h[n-1] - 1/6 h[n-2] = 1/3 \delta[n]$$

$$h[-1] = h[-2] = 0$$

$$\textcircled{n=0} \quad h[0] + 1/6 h[-1] - 1/6 h[-2] = \frac{1}{3} \quad (1)$$

$$h[0] = 1/3$$

$$\textcircled{n=1} \quad h[1] + 1/6 h[0] - 1/6 h[-1]$$

$$h[1] + 1/6 (1/3) - 0 = 1/3 \quad (2)$$

$$h[1] = -1/18$$

$$h[n] = C_1 (1/3)^n + C_2 (-1/2)^n$$

$$h[0] = 1/3, \quad h[1] = -1/18$$

$$\textcircled{n=0} \quad 1/3 = C_1 + C_2 \quad (1)$$

$$-1/18 = C_1 (1/3) + C_2 (-1/2) \quad (2)$$

$$\Rightarrow C_1 = 1/3 - C_2 \quad (3)$$

$$(1) \rightarrow (2) \Rightarrow -1/18 = 1/9 - 1/3 C_2 - 1/2 C_2$$

$$-\frac{5}{6} C_2 = -1/6$$

$$C_2 = 1/5$$

$$\Delta \text{ into (3)} \quad C_1 = 1/3 - 1/5$$

$$C_1 = 2/15$$

$$\therefore h[n] = \left[ \frac{2}{15} (1/3)^n + \frac{1}{5} (-1/2)^n \right] u[n]$$

## A.2 - Function II

$$x^2 + \frac{1}{4} = 0$$

$$x_{1,2} = \frac{0 \pm \sqrt{0 - 4(1/4)}}{2}$$

$$x_{1,2} = \frac{1}{2}j, -\frac{1}{2}j$$

$$y[n] = C_1 (0.5j)^n + C_2 (-0.5j)^n$$

$$h[n] + \frac{1}{4} h[n-2] = \delta[n]$$

$$@ n=0 \quad h[0] + \frac{1}{4} h[-2] = 1$$

$$\bullet h[-2] = 0$$

$$\Rightarrow h[0] = 1$$

$$@ n=1 \quad h[1] + \frac{1}{4} h[-1] = 0 \quad \bullet h[-1] = 0$$

$$h[1] = 0$$

$$h[n] = C_1 (0.5j)^n + C_2 (-0.5j)^n$$

$$@ n=0 \quad h[0] = C_1 (0.5j)^0 + C_2 (-0.5j)^0$$

$$1 = C_1 + C_2 \Rightarrow C_1 = 1 - C_2$$

$$@ n=1 \quad h[1] = C_1 (0.5j)^1 + C_2 (-0.5j)^1$$

$$0 = (1 - C_2)(0.5j) + C_2 (-0.5j)$$

$$0 = 0.5j + C_2 (-0.5j) + C_2 (-0.5j)$$

$$-0.5j = 2 C_2 (-0.5j)$$

$$(2) \frac{-0.5j}{-0.5j} = C_2 \Rightarrow$$

$$\Rightarrow C_2 = 1/2$$

$$C_1 = 1 - 1/2$$

$$C_1 = 1/2$$

$$\therefore h[n] = \left[ \frac{1}{2} (0.5j)^n + \frac{1}{2} (-0.5j)^n \right] u[n]$$

### Part 3 – Comparison of Hand & MATLAB Calculations

#### A.2 - Function I

$$h[n] = \left[ \frac{2}{15} \left( \frac{1}{3} \right)^n + \frac{1}{5} \left( -\frac{1}{2} \right)^n \right] u[n]$$

$$h[3] = \frac{2}{15} \left( \frac{1}{3} \right)^3 + \frac{1}{5} \left( -\frac{1}{2} \right)^3$$
$$= \frac{2}{15} \left( \frac{1}{27} \right) + \frac{1}{5} \left( -\frac{1}{8} \right)$$


$$h[3] = -13/648$$

#### A.2 - Function II


$$h[n] = \left[ \frac{1}{2} (0.5j)^n + \frac{1}{2} (-0.5j)^n \right] u[n]$$

$$h[3] = \frac{1}{2} (0.5j)^3 + \frac{1}{2} (-0.5j)^3$$
$$= -1/16j + 1/16j$$

$$h[3] = 0$$







Therefore, the  $h[3]$  values match accordingly.


## B) Zero Input Response

```
n = 0:50;

b = [2 0 0];
a = [1 -3/10 -1/10];

z_i = firlt(b, a, [1 2]);
y_0 = filter(b, a, zeros(size(n)), z_i);

figure
stem(n, y_0, 'k');
title('Part B - Zero Input Response')
axis([-2 10.5 -0.3 1.1])
xlabel('n')
ylabel('y0[n]')
```



### C) Zero State Response

```


n = -50:50;
u = (mod(n,1)==0)*1.0.*(n>=0);
u2 = (mod(n,1)==0)*1.0.*(n>=10);

b = [2 0 0];
a = [1 -3/10 -1/10];
x = 2.*cos((2.*pi.*n)./6).*(u-u2);

z_i = filtic(b, a, 0);
y_0 = filter(b, a, x, z_i);

figure
stem(n, y_0, 'k');
title('Part C - Zero State Response')
axis([-2 18 -4 4.1])
xlabel('n')
ylabel('y0[n]')

```



## D) Total Response

### Part I - Total response

```

n = -50:50;
u = (mod(n,1)==0)*1.0.*(n>=0);
u2 = (mod(n,1)==0)*1.0.*(n>=10);


b = [2 0 0];
a = [1 -3/10 -1/10];
x = 2.*cos((2.*pi.*n)/6).*(u-u2);

z_i = filtic(b, a, [1 2]);
y_0 = filter(b, a, x, z_i);

figure
stem(n, y_0, 'k');
title('Part D.I - Total Response')
axis([-1 18 -4 4.1])

```

```
xlabel('n')
ylabel('y0[n]')
```



## Part II - Total response by Summation of Zero Input and Zero state Responses


```
n = -50:50;
u = (mod(n,1)==0)*1.0.*(n>=0);
u2 = (mod(n,1)==0)*1.0.*(n>=10);
b = [2 0 0];
a = [1 -3/10 -1/10];
x = 2.*cos((2.*pi.*n)/6).*(u-u2);

z_i = filtic(b, a, [1 2]);
y_0i = filter(b, a, zeros(size(n)), z_i);

z_i2 = filtic(b, a, 0);
y_0 = filter(b, a, x, z_i2);

yt = y_0 + y_0i;
```

```
figure
stem(n, y_0, 'k');
title('Part D.II - Total Response by Summation')
axis([-1 18 -4 4.1])
xlabel('n')
ylabel('y0[n]')
```



## E) Convolution and System Stability

### Part I - conv command

```
n = 0:50;
u = (mod(n,1)==0)*1.0.*(n>=0);
u2 = (mod(n,1)==0)*1.0.*(n>=10);
b = [2 0 0];
a = [1 -3/10 -1/10];
x = 2.*cos((2.*pi.*n)/6).*(u-u2);
%delta = @(n) 1.0.*(n==0);

delta = (n)==0;

h = filter(b, a, delta(n));
```


```

y = conv(x, h);

n = 0:100;

figure
stem(n, y, 'k');
title('Part E - Zero State Response with Conv Function')
axis([-1 18 -4 4.1])
xlabel('n')
ylabel('y0[n]')

```



## Part II

Yes, the results in the plots “Part E – Zero State Response with Conv Function” and “Part C – Zero State Response” are the same.

### Part III

Yes, the system is asymptotically stable, this is because the system's Characteristic Equation has two real roots ( $E^2 - (3/10)E - (1/10) \rightarrow E_1 = 0.5$  and  $E_2 = -0.2$ ) within the unit circle in the Complex Plane which is shown as a decreasing cone shaped trajectory in the plot "Part E – Zero State Response with Conv Function".

### F) Moving Average Filter

Part I - Constant Coefficient Difference Equation with  $h[n]$  Impulse Response

Part F.1.

$$y[n] = \frac{1}{N} \left( (1) x[n] + (1) x[n-1] + \dots + (1) x[n-(N-1)] \right)$$

Part II & III - MATLAB Function for N-point moving-average filter

```
n = 0:1:45;
d = (n-30)==0;
d2 = (n-35)==0;
a = 1;

x = cos((pi.*n)/5)+d-d2;

%original function
figure
stem(n, x);
title('Part F - x[n]')
axis([0 45 -4 4.1])
xlabel('n')
ylabel('h[n]')

%N=4
filterN = 4;

b = (1/filterN)*ones(1, filterN);
h = filter(b, a, x);
figure
stem(n, h);
title('Part F - x[n] after Moving Average Filter of Window Size 4')
axis([0 45 -4 4.1])
```

```

xlabel('n')
ylabel('h[n]')

%N=8
filterN = 8;
b = (1/filterN)*ones(1, filterN);
h = filter(b, a, x);
figure
stem(n, h);
title('Part F - x[n] after Moving Average Filter of Window Size 8')
axis([0 45 -4 4.1])
xlabel('n')
ylabel('h[n]')

%N=12
filterN = 12;
b = (1/filterN)*ones(1, filterN);
h = filter(b, a, x);
figure
stem(n, h);
title('Part F - x[n] after Moving Average Filter of Window Size 12')
axis([0 45 -4 4.1])
xlabel('n')
ylabel('h[n]')

```

As the window size (filterN) of the moving-average filter increases the amplitude of the resulting sinusoidal signal decreases. This is due to the filter taking an average over a larger number of data points while the number of repeating y-values and the number of y-value that cancel out increases. This is a common method to smooth out noisy data (outlier data) that would otherwise give an incorrect representation of trajectory of the actual signal.



