

# Neural Networks

## AI4003-Applied Machine Learning

Dr. Mohsin Kamal

Department of Electrical Engineering  
National University of Computer and Emerging Sciences, Lahore, Pakistan

- 1 Neural Networks
- 2 Non-linear hypotheses
- 3 Neurons and the brain
- 4 Model representation
- 5 Examples and intuitions
- 6 Multi-class classification

# 1 Neural Networks

## 2 Non-linear hypotheses


## 3 Neurons and the brain

## 4 Model representation

## 5 Examples and intuitions

## 6 Multi-class classification

## Motivation:



- The brain is a complex, nonlinear and distributed computer having neurons as its basic information processing units (different than traditional computers).
- The brain has the ability to perform several tasks such as pattern recognition, perception and motor control very well, despite being slow in information processing.
- Therefore, the motivation is to mimic the functioning neurons and neural networks *in-silico* so as to build machines that have very high capabilities.


## Artificial Neural Networks - History

- 1943: computational model for neural networks (McCulloch & Pitts)
- 1958: Perceptron was created (Rosenblatt)
- 1969: was shown that Perceptrons were not powerful (Minsky & Papert)
- 1986: multi-layer perceptrons (Rumelhart & McClelland)
- 1990: IEEE Transactions on Neural Networks
- 2010– : Deep learning, wide number of applications

- 1 Neural Networks
- 2 Non-linear hypotheses**
- 3 Neurons and the brain
- 4 Model representation
- 5 Examples and intuitions
- 6 Multi-class classification

Consider a supervised learning classification problem...  
If you apply the logistic machine learning algorithm, then

### Non-linear Classification




$$g(\theta_0 + \theta_1 x_1 + \theta_2 x_2 + \theta_3 x_1 x_2 + \theta_4 x_1^2 x_2 + \theta_5 x_1^3 x_2 + \theta_6 x_1 x_2^2 + \dots)$$

- If you have more features, e.g,  $x_1 = \text{size}$ ,  $x_2 = \# \text{ of bedrooms}$ ,  $x_3 = \# \text{ of rooms}$ ,  $x_4 = \text{age}$   $\cdots$ ,  $x_{100} = \# \text{ of floors}$  and for example, you want to predict that what are the odds that the house will be sold out in next six months?
- Here, we came up with  $n = 100$ .
- If we have to include all the 2-order polynomials, then we will get  $\approx 5000$  features having complexity  $O(n^2)$ .
- $x_1^2, x_1x_2, x_1x_3, \cdots, x_2^2, x_2x_3, \cdots$
- The features can be reduced by choosing only squared polynomials i.e.,  $x_1^2, x_2^2, x_3^2, \cdots$
- This does not provide a good fit of hypothesis.
- If 3-order or cubic polynomials are included with the squared ones then having  $n = 100$ , we can have 170000 cubic features which will make it reach to  $O(n^3)$ .



For many machine learning problems,  $n$  will be very large. For example




Source: <https://www.analyticsvidhya.com/blog/2021/03/getting-started-with-computer-vision-basics-and-starter-projects/>

# Computer Vision: Car detection



Cars




Not a car


Testing:



What is this?

Lets examine why we need non-linear hypothesis:






$x$  will be having values from 0-255 if considering grey scale image and 7500 if RGB.

- 1 Neural Networks
- 2 Non-linear hypotheses
- 3 Neurons and the brain**
- 4 Model representation
- 5 Examples and intuitions
- 6 Multi-class classification


# Neural Networks

- **Origins:** Algorithms that try to mimic the brain.
- Was very widely used in 80s and early 90s; popularity diminished in late 90s.
- Recent resurgence: State-of-the-art technique for many applications

# Neuron in the brain



# Neuron in the brain






## NEURON:

- On the average, humans have 86 billion neurons in their brain and approximately 100 trillion synapses. There are 16 billion neurons in the forebrain.
- Neuron consists of a cell body, dendrites and an axon
- Neurons are massively interconnected by synapses
- Synapse is an interconnection between the axon of one neuron and a dendrite of another neuron
- Information propagation is achieved via electro-chemical signals

- 1 Neural Networks
- 2 Non-linear hypotheses
- 3 Neurons and the brain
- 4 Model representation**
- 5 Examples and intuitions
- 6 Multi-class classification

## Artificial Neurons:




$$v_k = b_k + \sum_{i=1}^m w_{ki} x_i = \sum_{i=0}^m w_{ki} x_i, \quad w_{k0} = b_k, x_0 = 1$$

# Activation Functions

## Threshold function:

Neurons with this activation function can only be in two states: "on" and "off".


$$\varphi(u) = \begin{cases} 1, & u \geq u_{th}, \\ 0, & u < u_{th} \end{cases}$$



## Logistic Sigmoid function:

The slope shows how fast a neuron moves from the "off" state to the "on" state:


$$\varphi(u) = \frac{1}{1 + e^{-au}}$$



# Activation Functions


**Hyperbolic function:**

$$\varphi(u) = \tanh(u)$$



**Rectifier Linear Unit (ReLU):**


$$\varphi(u) = \max(0, u) \triangleq u^+$$



**Softplus or SmoothReLU:**

$$\varphi(u) = \ln(1 + e^u)$$

# Neuron model: Logistic unit




$$\text{Where } x = \begin{bmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \end{bmatrix} \quad \theta = \begin{bmatrix} \theta_0 \\ \theta_1 \\ \theta_2 \\ \theta_3 \end{bmatrix}$$

Sometimes we say that it is artificial neuron having Sigmoid (logistic) activation function.

# Neural Network


Neural network is a group of neurons.







# Forward propagation: Vectorized implementation



Layer 1

Layer 2

Layer 3

$$a_1^{(2)} = g(\Theta_{10}^{(1)} x_0 + \Theta_{11}^{(1)} x_1 + \Theta_{12}^{(1)} x_2 + \Theta_{13}^{(1)} x_3)$$

$$a_2^{(2)} = g(\Theta_{20}^{(1)} x_0 + \Theta_{21}^{(1)} x_1 + \Theta_{22}^{(1)} x_2 + \Theta_{23}^{(1)} x_3)$$

$$a_3^{(2)} = g(\Theta_{30}^{(1)} x_0 + \Theta_{31}^{(1)} x_1 + \Theta_{32}^{(1)} x_2 + \Theta_{33}^{(1)} x_3)$$

$$h_{\Theta}(x) = a_1^{(3)} = g(\Theta_{10}^{(2)} a_0^{(2)} + \Theta_{11}^{(2)} a_1^{(2)} + \Theta_{12}^{(2)} a_2^{(2)} + \Theta_{13}^{(2)} a_3^{(2)})$$

$$x = \begin{bmatrix} x_0 \\ x_1 \\ x_2 \\ x_3 \end{bmatrix} \quad z^{(2)} = \begin{bmatrix} z_1^{(2)} \\ z_2^{(2)} \\ z_3^{(2)} \end{bmatrix}$$

$$z^{(2)} = \Theta^{(1)} a^{(1)}$$


$$a^{(2)} = g(z^{(2)})$$

$$\text{Add } a_0^{(2)} = 1$$


$$z^{(3)} = \Theta^{(2)} a^{(2)}$$

$$h_{\Theta}(x) = a^{(3)} = g(z^{(3)})$$

# Neural Network learning its own features




# Other network architectures




- 1 Neural Networks
- 2 Non-linear hypotheses
- 3 Neurons and the brain
- 4 Model representation
- 5 Examples and intuitions**
- 6 Multi-class classification

# Non-linear classification example: XOR/XNOR

$x_1, x_2$  are binary (0 or 1).




$$y = x_1 \text{ XOR } x_2$$
$$x_1 \text{ XNOR } x_2$$
$$\text{NOT } (x_1 \text{ XOR } x_2)$$




# Simple example: AND

$$x_1, x_2 \in \{0, 1\}$$
$$y = x_1 \text{ AND } x_2$$




$$h_{\Theta}(x) = g(-30 + 20x_1 + 20x_2)$$




# Example: OR function

$$x_1, x_2 \in \{0, 1\}$$

$$y = x_1 \text{ OR } x_2$$




$$h_{\Theta}(x) = g(-10 + 20x_1 + 20x_2)$$



# Example: NOT function

$$x_1 \in \{0, 1\}$$

$$y = \text{NOT}(x_1)$$







$$h_{\Theta}(x) = g(10 - 20x_1)$$

$x_1$	$h_{\Theta}(x)$
0	
1	




# Putting it together: $x_1$ XNOR $x_2$



$x_1$	$x_2$	$a_1^{(2)}$	$a_2^{(2)}$	$h_{\Theta}(x)$
0	0			
0	1			
1	0			
1	1			

# Handwritten digit classification



- 1 Neural Networks
- 2 Non-linear hypotheses
- 3 Neurons and the brain
- 4 Model representation
- 5 Examples and intuitions
- 6 Multi-class classification**

# Multiple output units: One-vs-all.



Pedestrian




Car



Motorcycle




Truck



$$h_{\Theta}(x) \in \mathbb{R}^4$$

Want  $h_{\Theta}(x) \approx \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix}$ ,  $h_{\Theta}(x) \approx \begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix}$ ,  $h_{\Theta}(x) \approx \begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix}$ , etc.  
when pedestrian      when car      when motorcycle

# Multiple output units: One-vs-all.



$$h_{\Theta}(x) \in \mathbb{R}^4$$

Want  $h_{\Theta}(x) \approx \begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix}$ ,  $h_{\Theta}(x) \approx \begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix}$ ,  $h_{\Theta}(x) \approx \begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix}$ , etc.  
 when pedestrian      when car      when motorcycle

Training set:  $(x^{(1)}, y^{(1)}), (x^{(2)}, y^{(2)}), \dots, (x^{(m)}, y^{(m)})$

$y^{(i)}$  one of  $\begin{bmatrix} 1 \\ 0 \\ 0 \\ 0 \end{bmatrix}$ ,  $\begin{bmatrix} 0 \\ 1 \\ 0 \\ 0 \end{bmatrix}$ ,  $\begin{bmatrix} 0 \\ 0 \\ 1 \\ 0 \end{bmatrix}$ ,  $\begin{bmatrix} 0 \\ 0 \\ 0 \\ 1 \end{bmatrix}$   
 pedestrian    car    motorcycle    truck