

Securing Digital Ecosystems with Public Key Infrastructure (PKI)

This slide introduces the concept of Public Key Infrastructure (PKI) and its role in securing digital ecosystems.

Introduction to PKI



PKI is a security framework that uses public-key cryptography to establish trust in digital communications.



Secure Transactions

PKI enables secure transactions, such as online banking and e-commerce, through the use of digital certificates



Identity Verification

PKI provides a reliable way to verify the identity of entities communicating over networks, ensuring trust in digital interactions.



Encryption

PKI facilitates the use of encryption to protect sensitive data during transmission, ensuring confidentiality in digital communications.

PKI is a comprehensive security solution that leverages public-key cryptography to establish trust, enable secure transactions, verify identities, and protect sensitive data in digital communications.

Key Distribution in PKI

Public Key Distribution

Private Key Storage Key Exchange Protocols Secure
Communication
Protocols


Public keys are securely distributed through digital certificates, which contain the public key and identity information of an entity. This enables safe exchange of public keys without the need for direct communication.

Private keys must be kept confidential and secure, never stored in plaintext.
Organizations use hardware security modules (HSMs), encrypted key vaults, and secure hardware like smart cards and USB tokens to protect private keys.

Protocols like Diffie-Hellman and RSA-based encryption enable the secure exchange of symmetric session keys used for encrypted communication. PKI provides the necessary trust and identity verification for these key exchange mechanisms.

PKI-based protocols like
TLS (Transport Layer
Security) and IPsec rely
on digital certificates to
distribute encryption keys
and establish trusted
connections between
communicating entities.





Certificate and Key Storage

Digital certificates and cryptographic keys must be stored securely to prevent unauthorized access or tampering. Private keys are protected using hardware security modules (HSMs), secure enclaves, and encrypted key vaults to ensure the integrity and confidentiality of sensitive cryptographic material.

PKI Registration Process

- Entity Requests Certificate
 An individual or organization requests a digital certificate from the PKI system.
- RA Authenticates Entity
 The Registration Authority (RA) verifies the identity of the requesting entity by collecting and validating credentials, such as legal documents, business registrations, and domain ownership records.
- RA Forwards Request to CA
 Once the entity's identity is confirmed, the RA forwards the certificate request to the Certificate Authority (CA) for processing.
 - The CA generates and issues a digital certificate that binds the entity's public key to its verified identity, following the X.509 standard.



Organizational Authentication for Certificates

Domain Validation (DV)

The CA confirms the organization's control over a domain by requiring DNS record modifications or email verification.

Organization Validation (OV)

The CA verifies the organization's business registration details and contacts the organization for confirmation.

Extended Validation (EV)

A more rigorous verification process that includes detailed legal checks, requiring the organization to meet strict authentication requirements.

Verifying Organizational Legitimacy

The organization must submit legal documents, business registrations, and domain ownership records to prove its legitimacy to the CA.

Preventing Fraudulent Certificates

These validation methods ensure that certificates are issued only to verified entities, reducing the risk of fraudulent or malicious use.



Individual Authentication for Certificate Requests

Company Email Verification

Job Role Confirmation

Two-Factor Authentication

Legal Authorization Documents



Certificate Issuance

X.509 Standard

The digital certificate follows the X.509 standard, which defines the format and fields for a certificate.

Public Key Binding

The certificate binds the entity's public key to its identity, enabling secure encryption and authentication.

Identity Details

The certificate includes the subject's identity, such as organization name, domain, or individual name.

Validity Period

The certificate specifies the validity period, including the expiration date, ensuring it is only used within the intended timeframe.


CA Digital Signature

The issuing Certificate Authority (CA) digitally signs the certificate, ensuring its authenticity and integrity.



PKI Trust Models

Comparison of key characteristics of PKI trust models (0-100 scale)





Subordinate Hierarchy and Cross-Certified Mesh

SubordinateHierarchy

Root CA issues certificates to subordinate/intermediate CAs, isolating root from direct exposure Security Benefit

Even if an intermediate CA is compromised, the root CA remains protected Interoperability

Enables organizations with different PKI systems to securely interoperate

Intermediate CAs

Manage specific domains, departments, or use cases under the overall PKI hierarchy Cross-Certified

Mesh

Multiple CAs establish mutual trust through cross-certification agreements Use Cases

Commonly used in federal agencies, multinational corporations, and industry consortiums



Certificate Chains and Revocation

Certificate Chains

Verifying Certificate Chains

Certificate Revocation

Certificate
Revocation Lists
(CRLs)

Certificate chains link an end-user certificate to a trusted root Certificate Authority (CA) through a hierarchy of intermediate CAs. This chain of trust ensures the validity and integrity of the certificate.

When a system or browser encounters a certificate, it verifies the entire certificate chain to ensure the certificate originates from a trusted root CA. If any certificate in the chain is invalid or revoked, the verification process fails, and the connection is marked as untrusted.

Certificate revocation is the process of invalidating a certificate that has been compromised, expired, or is no longer required. Revoking a certificate prevents its misuse by malicious actors, ensuring the security of the PKI system.

The traditional Certificate
Revocation List (CRL)
model involves the CA
periodically publishing a
list of revoked
certificates. Systems
must download and check
the CRLs to verify the
validity of a certificate, but
this method can be slow
and inefficient for largescale PKI deployments.

