



Imran Wahab

imran.sargodha@gmail.com



IT department Govt ambala muslim graduate college@gmail.com

Hashtable in Java

Difficulty Level : Medium • Last Updated : 11 May, 2022

The **Hashtable** class implements a hash table, which maps keys to values. Any non-null object can be used as a key or as a value. To successfully store and retrieve objects from a hashtable, the objects used as keys must implement the hashCode method and the equals method.



Java Collection Framework - Fundamentals

Beginner to Advance Level ★★★★★

Learn all important concepts such as data structures, classes, interfaces, algorithms and others with in-depth explanation using the Java Collection Framework.

Explore Now

Features of Hashtable

- It is similar to HashMap, but is synchronized.
- Hashtable stores key/value pair in hash table.
- In Hashtable we specify an object that is used as a key, and the value we want to associate to that key. The key is then hashed, and the resulting hash code is used as the index at which the value is stored within the table.
- The initial default capacity of Hashtable class is 11 whereas loadFactor is 0.75.

Start Your Coding Journey Now

```
public class Hashtable<K,V> extends
```



Sign in to GeeksforGeeks with Google



Imran Wahab

imran.sargodha@gmail.com




IT department Govt ambala muslim graduate college@gmail.com

Type Parameters:

- **K** – the type of keys maintained by this class
- **V** – the type of mapped values

The Hierarchy of Hashtable



Hashtable implements **Serializable**, **Cloneable**, [Map<K,V>](#) interfaces and extends [Dictionary<K,V>](#). The direct subclasses are [Properties](#), [UIDefaults](#).

Constructors:

In order to create a Hashtable, we need to import it from **java.util.Hashtable**. There are various ways in which we can create a Hashtable.

Start Your Coding Journey Now



Sign in to GeeksforGeeks with Google



Imran Wahab

imran.sargodha@gmail.com



IT department Govt ambala muslim graduate college@gmail.com

Java

```
// Java program to demonstrate
// adding elements to Hashtable

import java.io.*;
import java.util.*;

class AddElementsToHashtable {
    public static void main(String args[])
    {
        // No need to mention the
        // Generic type twice
        Hashtable<Integer, String> ht1 = new Hashtable<>();

        // Initialization of a Hashtable
        // using Generics
        Hashtable<Integer, String> ht2
            = new Hashtable<Integer, String>();

        // Inserting the Elements
        // using put() method
        ht1.put(1, "one");
        ht1.put(2, "two");
        ht1.put(3, "three");

        ht2.put(4, "four");
        ht2.put(5, "five");
        ht2.put(6, "six");

        // Print mappings to the console
        System.out.println("Mappings of ht1 : " + ht1);
        System.out.println("Mappings of ht2 : " + ht2);
    }
}
```

Output

Start Your Coding Journey Now

```
Hashtable<K, V> ht = new Hashtable<
```



Sign in to GeeksforGeeks with Google



Imran Wahab

imran.sargodha@gmail.com



IT department Govt ambala muslim graduate

college@gmail.com

Java

```
// Java program to demonstrate
// adding elements to Hashtable

import java.io.*;
import java.util.*;

class AddElementsToHashtable {
    public static void main(String args[])
    {
        // No need to mention the
        // Generic type twice
        Hashtable<Integer, String> ht1 = new Hashtable<>(4);

        // Initialization of a Hashtable
        // using Generics
        Hashtable<Integer, String> ht2
            = new Hashtable<Integer, String>(2);

        // Inserting the Elements
        // using put() method
        ht1.put(1, "one");
        ht1.put(2, "two");
        ht1.put(3, "three");

        ht2.put(4, "four");
        ht2.put(5, "five");
        ht2.put(6, "six");

        // Print mappings to the console
        System.out.println("Mappings of ht1 : " + ht1);
        System.out.println("Mappings of ht2 : " + ht2);
    }
}
```

Start Your Coding Journey Now

Mappings of ht2 : {4=four, 6=six,

3. Hashtable(int size, float fillRatio): The size specified by size and fill ratio specifies how full a hash table can be before it is resized to 1.0.



Sign in to GeeksforGeeks with Google



Imran Wahab

imran.sargodha@gmail.com



IT department Govt ambala muslim graduate college@gmail.com

```
Hashtable<K, V> ht = new Hashtable<K, V>(int size, float fillRatio);
```

Java

```
// Java program to demonstrate
// adding elements to Hashtable

import java.io.*;
import java.util.*;

class AddElementsToHashtable {
    public static void main(String args[])
    {
        // No need to mention the
        // Generic type twice
        Hashtable<Integer, String> ht1
            = new Hashtable<>(4, 0.75f);

        // Initialization of a Hashtable
        // using Generics
        Hashtable<Integer, String> ht2
            = new Hashtable<Integer, String>(3, 0.5f);

        // Inserting the Elements
        // using put() method
        ht1.put(1, "one");
        ht1.put(2, "two");
        ht1.put(3, "three");

        ht2.put(4, "four");
```

Start Your Coding Journey Now

```
        System.out.println("Mappings of ht1 : " + ht1);
    }
}
```

Output

```
Mappings of ht1 : {3=three, 2=two, 1=one}
Mappings of ht2 : {6=six, 5=five, 4=four}
```

4. Hashtable(Map<? extends K,? extends V> m): This creates a hash table that is initialized with the elements in m.

```
Hashtable<K, V> ht = new Hashtable<K, V>(Map m);
```

Java

```
// Java program to demonstrate
// adding elements to Hashtable

import java.io.*;
import java.util.*;

class AddElementsToHashtable {
    public static void main(String args[])
    {
        // No need to mention the
        // Generic type twice
        Map<Integer, String> hm = new HashMap<>();

        // Inserting the Elements
        // using put() method
        hm.put(1, "one");
        hm.put(2, "two");
        hm.put(3, "three");

        // Initialization of a Hashtable
    }
}
```



Sign in to GeeksforGeeks with Google



Imran Wahab

imran.sargodha@gmail.com



IT department Govt ambala muslim graduate college@gmail.com

Start Your Coding Journey Now



Sign in to GeeksforGeeks with Google



Imran Wahab

imran.sargodha@gmail.com



IT department Govt ambala muslim graduate college@gmail.com

```
        System.out.println("Mappings of ht2 : " + ht2);
    }
}
```

Output

Mappings of ht2 : {3=three, 2=two, 1=one}

Example:

Java

```
// Java program to illustrate
// Java.util.Hashtable

import java.util.*;

public class GFG {
    public static void main(String[] args)
    {
        // Create an empty Hashtable
        Hashtable<String, Integer> ht = new Hashtable<>();

        // Add elements to the hashtable
        ht.put("vishal", 10);
        ht.put("sachin", 30);
        ht.put("vaibhav", 20);

        // Print size and content
        System.out.println("Size of map is:- " + ht.size());
        System.out.println(ht);

        // Check if a key is present and if
        // present, print value
        if (ht.containsKey("vishal")) {
            Integer a = ht.get("vishal");
            System.out.println("value for key"
                               + " \"vishal\" is:- " + a);
        }
    }
}
```

Start Your Coding Journey Now



Sign in to GeeksforGeeks with Google



Imran Wahab

imran.sargodha@gmail.com



IT department Govt ambala muslim graduate college@gmail.com

Output

```
Size of map is:- 3
{vaibhav=20, vishal=10, sachin=30}
value for key "vishal" is:- 10
```

Performing Various Operations on Hashtable

1. Adding Elements: In order to add an element to the hashtable, we can use the [put\(\)](#) method. However, the insertion order is not retained in the hashtable. Internally, for every element, a separate hash is generated and the elements are indexed based on this hash to make it more efficient.

Java

```
// Java program to demonstrate
// adding elements to Hashtable

import java.io.*;
import java.util.*;

class AddElementsToHashtable {
    public static void main(String args[])
    {
        // No need to mention the
        // Generic type twice
        Hashtable<Integer, String> ht1 = new Hashtable<>();

        // Initialization of a Hashtable
        // using Generics
        Hashtable<Integer, String> ht2
            = new Hashtable<Integer, String>();

        // Inserting the Elements
        // using put() method
        ht1.put(1, "Geeks");
        ht1.put(2, "For");
        ht1.put(3, "Geeks");
```


Start Your Coding Journey Now

```
System.out.println("Mappings of ht1 : {3=Geeks, 2=For, 1=Geeks}");
System.out.println("Mappings of ht2 : {3=Geeks, 2=For, 1=Geeks}");
    }
}
```



Sign in to GeeksforGeeks with Google



Imran Wahab

imran.sargodha@gmail.com



IT department Govt ambala muslim graduate college@gmail.com

Output

```
Mappings of ht1 : {3=Geeks, 2=For, 1=Geeks}
Mappings of ht2 : {3=Geeks, 2=For, 1=Geeks}
```

2. Changing Elements: After adding the elements if we wish to change the element, it can be done by again adding the element with the `put()` method. Since the elements in the hashtable are indexed using the keys, the value of the key can be changed by simply inserting the updated value for the key for which we wish to change.

Java

```
// Java program to demonstrate
// updating Hashtable

import java.io.*;
import java.util.*;
class UpdatesOnHashtable {
    public static void main(String args[])
    {

        // Initialization of a Hashtable
        Hashtable<Integer, String> ht
            = new Hashtable<Integer, String>();

        // Inserting the Elements
        // using put method
        ht.put(1, "Geeks");
        ht.put(2, "Geeks");
        ht.put(3, "Geeks");

        // print initial map to the console
    }
}
```

Start Your Coding Journey Now

```
// print the updated map
System.out.println("Updated Map:");
}
}
```



Sign in to GeeksforGeeks with Google



Imran Wahab

imran.sargodha@gmail.com



IT department Govt ambala muslim graduate college@gmail.com

Output

Initial Map {3=Geeks, 2=Geeks, 1=Geeks}

Updated Map {3=Geeks, 2=For, 1=Geeks}

3. Removing Element: In order to remove an element from the Map, we can use the [remove\(\)](#) method. This method takes the key value and removes the mapping for a key from this map if it is present in the map.

Java

```
// Java program to demonstrate
// the removing mappings from Hashtable

import java.io.*;
import java.util.*;
class RemovingMappingsFromHashtable {

    public static void main(String args[])
    {
        // Initialization of a Hashtable
        Map<Integer, String> ht
            = new Hashtable<Integer, String>();

        // Inserting the Elements
        // using put method
        ht.put(1, "Geeks");
        ht.put(2, "For");
        ht.put(3, "Geeks");
        ht.put(4, "For");

        // Initial HashMap
```

Start Your Coding Journey Now

```
        System.out.println("Updated map : ");
    }
}
```

Output

Initial map : {4=For, 3=Geeks, 2=For, 1=Geeks}
Updated map : {3=Geeks, 2=For, 1=Geeks}

4. Traversal of a Hashtable: To iterate the table, we can make use of an [advanced for loop](#). Below is the example of iterating a hashtable.

Java

```
// Java program to illustrate
// traversal of Hashtable

import java.util.Hashtable;
import java.util.Map;

public class IteratingHashtable {
    public static void main(String[] args)
    {
        // Create an instance of Hashtable
        Hashtable<String, Integer> ht = new Hashtable<>();

        // Adding elements using put method
        ht.put("vishal", 10);
        ht.put("sachin", 30);
        ht.put("vaibhav", 20);

        // Iterating using enhanced for loop
        for (Map.Entry<String, Integer> e : ht.entrySet())
            System.out.println(e.getKey() + " "
                               + e.getValue());
    }
}
```



Sign in to GeeksforGeeks with Google



Imran Wahab

imran.sargodha@gmail.com



IT department Govt ambala muslim graduate

college@gmail.com

Start Your Coding Journey Now

sachin 30


Internal Working

Hashtable datastructure is an array of buckets.

It makes use of **hashCode() method** to determine which bucket the key/value pair should map.

The hash function helps to determine the location for a given key in the bucket list. Generally, hashCode is a non-negative integer that is equal for equal Objects and may or may not be equal for unequal Objects. To determine whether two objects are equal or not, hashtable makes use of the equals() method.

It is possible that two unequal Objects have the same hashCode. This is called a **collision**. To resolve collisions, hashtable uses an array of lists. The pairs mapped to a single bucket (array index) are stored in a list and list reference is stored in the array index.



Methods of Hashtable

We use cookies to ensure you have the best browsing experience on our website. By using our site, you acknowledge that you have read and understood our [Cookie Policy](#) & [Privacy Policy](#).

Got It !



Sign in to GeeksforGeeks with Google



Imran Wahab

imran.sargodha@gmail.com



IT department Govt ambala muslim graduate college@gmail.com

Start Your Coding Journey Now



Sign in to GeeksforGeeks with Google



Imran Wahab

imran.sargodha@gmail.com



IT department Govt ambala muslim graduate college@gmail.com

METHOD

[clear\(\)](#)

Clears this

[clone\(\)](#)

Creates a shallow copy of this hashtable.

[compute\(K key,
BiFunction<? super
K,? super V,? extends V>
remappingFunction\)](#)

Attempts to compute a mapping for the specified key and its current mapped value (or null if there is no current mapping).

[computeIfAbsent\(K key,
Function<? super K,?
extends V>
mappingFunction\)](#)

If the specified key is not already associated with a value (or is mapped to null), attempts to compute its value using the given mapping function and enters it into this map unless null.

[computeIfPresent\(K key,
BiFunction<? super K,?
super V,? extends V>
remappingFunction\)](#)

If the value for the specified key is present and non-null, attempts to compute a new mapping given the key and its current mapped value.

[contains\(Object value\)](#)

Tests if some key maps into the specified value in this hashtable.

[containsKey\(Object key\)](#)

Tests if the specified object is a key in this hashtable.

[containsValue\(Object
value\)](#)

Returns true if this hashtable maps one or more keys to this value.

Start Your Coding Journey Now



Sign in to GeeksforGeeks with Google



Imran Wahab

imran.sargodha@gmail.com



IT department Govt ambala muslim graduate college@gmail.com

[elements\(\)](#)

Returns a

`entrySet()`

Returns a

`equals(Object o)`

Compares

as per the definition in the Map interface.

[get\(Object key\)](#)

Returns the value to which the specified key is mapped, or null if this map contains no mapping for the key.

`hashCode()`

Returns the hash code value for this Map as per the definition in the Map interface.

[isEmpty\(\)](#)

Tests if this hashtable maps no keys to values.

[keys\(\)](#)

Returns an enumeration of the keys in this hashtable.

`keySet()`

Returns a Set view of the keys contained in this map.

`merge(K key, V value,
BiFunction<? super V,?
super V,? extends V>
remappingFunction)`

If the specified key is not already associated with a value or is associated with null, associates it with the given non-null value.

[put\(K key, V value\)](#)

Maps the specified key to the specified value in this hashtable.

`putAll(Map<? extends K,?
extends V> t)`

Copies all of the mappings from the specified map to this hashtable.

Start Your Coding Journey Now



Sign in to GeeksforGeeks with Google



Imran Wahab

imran.sargodha@gmail.com



IT department Govt ambala muslim graduate college@gmail.com

rehash()

Increases
hashtable
more effi

remove(Object key)

Removes
hashtable.

[size\(\)](#)

Returns the number of keys in this hashtable.

[toString\(\)](#)

Returns a string representation of this Hashtable object in the form of a set of entries, enclosed in braces and separated by the ASCII characters ", " (comma and space).

values()

Returns a Collection view of the values contained in this map.

Methods declared in interface java.util.Map

METHOD

DESCRIPTION

[forEach\(\[BiConsumer\]\(#\)<?
\[super K\]\(#\),? \[super V\]\(#\)>
\[action\]\(#\)\)](#)

Performs the given action for each entry in this map until all entries have been processed or the action throws an exception.

getOrDefault(Object
key, V defaultValue)

Returns the value to which the specified key is mapped, or defaultValue if this map contains no mapping for the key.

putIfAbsent(K key, V
value)

If the specified key is not already associated with a value (or is mapped to null) associates it with the given value and

Start Your Coding Journey Now

remove(Object key,
Object value)

Removes the
mapped to the

replace(K key, V value)

Replaces the
mapped to some value.

replace(K key, V
oldValue, V newValue)

Replaces the entry for the specified key only if currently
mapped to the specified value.

replaceAll(BiFunction<?
super K, ? super V, ?
extends V> function)

Replaces each entry's value with the result of invoking the
given function on that entry until all entries have been
processed or the function throws an exception.



Sign in to GeeksforGeeks with Google



Imran Wahab

imran.sargodha@gmail.com



IT department Govt ambala muslim graduate
college@gmail.com

Must Read:

- [Differences between HashMap and Hashtable in Java](#)

Reference:

<https://docs.oracle.com/en/java/javase/11/docs/api/java.base/java/util/Hashtable.html>

Master Java
Collection
Framework

- ✓ Classes
- ✓ Data Structures
- ✓ In-built functions
- ✓ Interfaces

Start Learning



Like 50



Imran Wahab

imran.sargodha@gmail.com



IT department Govt ambala muslim graduate college@gmail.com

RECOMMENDED ARTICLES

Page : 1 2 3

- | | |
|---|--|
| 01 Differences between HashMap and Hashtable in Java
20, Aug 15 | 05 Hashtable containsValue() Method in Java
26, Jun 18 |
| 02 Hashtable toString() Method in Java
26, Jun 18 | 06 Hashtable containsKey() Method in Java
26, Jun 18 |
| 03 Hashtable elements() Method in Java
26, Jun 18 | 07 Hashtable put() Method in Java
26, Jun 18 |
| 04 Hashtable keys() Method in Java
26, Jun 18 | 08 Hashtable get() Method in Java
26, Jun 18 |

Start Your Coding Journey Now



Vote for difficulty

Current difficulty : [Medium](#)

Easy

Normal

Medium

Hard

Expert



Sign in to GeeksforGeeks with Google



Imran Wahab

imran.sargodha@gmail.com



IT department Govt ambala muslim graduate college@gmail.com

Improved By : [OwiesAAlomari](#), [nidhi_biet](#), [bishnoisunil007](#), [Ganeshchowdharysadanala](#)

Article Tags : [HashTable](#), [Java - util package](#), [Java-Collections](#), [Java-HashTable](#), [Java](#)

Practice Tags : [Java](#), [Java-Collections](#)

Improve Article

Report Issue

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Load Comments



GeeksforGeeks

A-143, 9th Floor, Sovereign Corporate Tower,
Sector-136, Noida, Uttar Pradesh - 201305

feedback@geeksforgeeks.org

Start Your Coding Journey Now

[In Media](#)
[Contact Us](#)
[Privacy Policy](#)
[Copyright Policy](#)



Sign in to GeeksforGeeks with Google



Imran Wahab

imran.sargodha@gmail.com



IT department Govt ambala muslim graduate college

college@gmail.com

News

[Top News](#)
[Technology](#)
[Work & Career](#)
[Business](#)
[Finance](#)
[Lifestyle](#)
[Knowledge](#)

Languages

[Python](#)
[Java](#)
[CPP](#)
[Golang](#)
[C#](#)
[SQL](#)
[Kotlin](#)

Web Development

[Web Tutorials](#)
[Django Tutorial](#)
[HTML](#)
[JavaScript](#)
[Bootstrap](#)
[ReactJS](#)
[NodeJS](#)

Contribute

[Write an Article](#)
[Improve an Article](#)
[Pick Topics to Write](#)
[Write Interview Experience](#)
[Internships](#)
[Video Internship](#)

@geeksforgeeks , Some rights reserved