
How Our Research Is Different

Muhammad Ahmad Khan · AdaptiShield · 15 October 2026

1. The problem


An AI agent reads emails, web pages and tool results. An attacker can hide an instruction inside that text. The agent may follow it.



This attack is called **indirect prompt injection**. Every paper below is about it.

2. What others do, and what we do

Earlier work defends in one of three ways. We use a fourth.




Way	What it looks at	Example	Weak point
1. Mark the text	the text	Spotlighting [3]	making the attack easier to read can make it easier to follow
2. Limit the actions	the action	AgentDojo tool filter [2]	the attack often needs the same actions as the real task
3. Check the text	the text	PIShield and eight similar detectors [4]	catching more attacks also means more false alarms
4. **Check the effect**	**the link between text and action**	AgentSentry [9] and **our work**	needs a visible change in the action (section 5)

Way 4 is the least studied, which is why it was worth testing.

---

3. How our method works


We run the agent **twice**: once with the untrusted text, once with it hidden. If the action changes, the text caused it.



---

4. Our work next to each paper

4.1 The closest paper: AgentSentry [9]



- **Same:** the run-twice idea and cleaning the input. We do not claim these.
- **Different:** we tested **where the method works and where it does not**, on attacks written by other researchers, and added three rules of our own.

4.2 Every paper in one table

Paper	What they did	What we did differently
InjecAgent [1]	a set of attacks to test agents; no defence	used it as an **outside exam** for our defence
AgentDojo [2]	a test environment with a few defences, one number each	used its safe documents to count false alarms, and its attacks as a test we **locked before looking**
Spotlighting [3]	marking the text cut attacks from over 50% to under 2% on GPT models	on our small models it made no difference: **34.8% → 33.3%** (p = 1.00)
PIShield and others [4]	check a piece of text	we check one step of a working agent, and split results by attack type
MCP papers [10–14]	protocol attacks, signed tools, training with GRPO	used as the base of our design; we claim nothing for those parts


4.3 How we test, compared with most papers

	Most papers	Our work
Results	one overall number	**split by attack type**, with confidence ranges
Attacks used	written by the authors	also written by **other researchers**
Fixes	tested on the same data	tested on **data locked beforehand**
Limits	rarely measured	**measured**
Reproducible	sometimes	**all code on GitHub**

---

5. Our main result


The method works very well when the attack names a **clear target**: an email address or a website link that the agent's action can copy.



Test set	Detection
Our own attacks	**96.7%**
InjecAgent attacks **with** a clear target	**93.3%**
InjecAgent attacks **without** a target	10.0%

An easy way to picture it: a lost-property office. If an item has a **name tag**, you can find its owner. If it has none, even the best detective cannot. The clear target is the name tag.

Three separate tests point to the same reason:



Because three different tests agree, this is a real finding, not bad luck. It tells users exactly **when the method can be trusted**.

---


6. Things still to improve

- **Small models only.** Both models have 3–4 billion parameters.
- **Close to AgentSentry.** A reviewer may say so. Our answer: the idea is theirs, the measured working range is ours.
- **Papers still to cite:** TaskTracker, AttentionTracker, and Du et al.
- **Small samples in places:** 60 safe documents (all that exist) and 5 multi-step conversations per run.
- **One number to fix:** the overall figure appears as both 51.7% and 53.3%. Say which run each comes from.

---

7. What comes next: paper 2

Paper 2 starts where paper 1 stops: attacks with no clear target. (Plan only, nothing measured yet. Full plan: `paper2-plan.md`.)



Idea	Closest existing work	How paper 2 differs
Is the action part of the task?	Task Shield **(to check and cite)**	still compares runs with and without the text
Smooth score	AgentSentry [9], MELON **(to check)**	a calibrated score from a small local model
Learns while running	the survey [13] asks for this; MCP-RiskCue [14] retrains the model	changes a few readable settings, each approved by a human
Attacks on the learning	none found yet **(to check)**	measures whether the human check stops them

---

8. Summary

In one box

The problem: hidden instructions in emails or web pages can take over an AI agent.

What others do: mark the text, limit the actions, or check whether the text looks like an attack.

What we do: run the agent twice, with and without the text. If the action changes, the text caused it.

How we are different: we tested on attacks written by other researchers, split the results by attack type, and measured where the method works.

Main result: 96.7% of our own attacks caught, and 93.3% of outside attacks that name a clear target.

Next step: paper 2 extends the method to attacks with no clear target.

All code is on GitHub, so every result can be reproduced.