FYP-2 Mid Evaluation — 5-Minute Speaking Script

S26-017-R-GASR · FAST NUCES Islamabad · Supervisor: Dr Akhtar Jamil

Written against the 12-slide deck, cut to the FYP committee's required structure. Slides 1–7 are the spoken talk and the only ones that count against the five minutes; 8–12 carry the live demonstration and the preliminary results.

Member	Slides	Words	Time	Section
Ahmad Rashad 22i-1175	1 – 3	259	1:51 – 2:04	Goals and objectives · faculty feedback addressed
Shehroz Kashif 22i-0771	4 – 6	283	2:01 – 2:16	Progress: architecture, what we measured, the base papers
Humair Khan 22i-2623	7	82	0:35 – 0:39	Remaining work, then drives the live demonstration
Total		**624**	**4:27 – 4:60**	Counted from the spoken lines only. Fast end 140 wpm, slow end 125 wpm.

Two rules this script follows. (1) Numbers stay on the slides. A figure is spoken aloud only when it means something on its own — "all ten videos", "one camera instead of two". Error scores, correlations and decibels are on screen where the panel can read them at their own pace, and are described in words instead. **(2) Nothing is read off a slide.** The deck carries the detail; you carry the argument.

Hard constraints from the committee. The 4–5 minutes are **uninterrupted** — do not stop for questions during slides 1–7, and do not overrun; every minute borrowed is a minute taken from the demonstration. Everything on **one laptop**. The demonstration must be the **live system**, not a video.

Ahmad Rashad (22i-1175) — Slides 1 to 3

Slide 1 — From Reconstruction to Anticipation · 28 words · 12 s

Good morning. I'm Ahmad Rashad, with Shehroz Kashif and Humair. Our supervisor is Dr Akhtar Jamil. Project S26-017 — a research FYP on 4D surgical reconstruction and deformation prediction.

Slide 2 — What the project is for · 99 words · 42 s

A surgeon operating through one laparoscope sees a flat image of the present. Our goal is a system that reconstructs that scene in 3D and anticipates how the tissue deforms next — from one camera, no depth sensor, no annotation.

Point along the four cards. Say every status — the panel is marking progress.

Four objectives: reconstruct in 3D, learn the deformation without labels, predict forward with confidence, and evaluate against the literature. The first two are complete, the third is implemented, the fourth in progress.

Pause. Read the question slowly — it is the sentence they should remember.

So the research question is this. Can future tissue geometry be predicted from ordinary surgical video — and can the system tell us when to trust it?

Slide 3 — Faculty feedback from FYP-1 · 132 words · 57 s

Name the specifics — the panel gave this feedback and will recognise whether you acted on it. The file names and the full method lists are on the slide; do not read those out.

We had four pieces of feedback after FYP-1, and all four are implemented.

Implement a base paper for comparative analysis — we implemented two. PointRNN, by Fan and Yang, the closest published method to ours; and Luo and Hu's CVPR 2021 paper, the first diffusion model over 3D point clouds.

Implement state-of-the-art methods — eleven on one protocol. Five classical, from zero-motion up to a two-state Kalman filter; five learned, from a plain MLP up to PointLSTM.

A detailed tuning and optimisation analysis — Module 8, four studies: inference cost against accuracy, context length, optimiser sensitivity, and diffusion ablations.

And begin a paper in conference format — a six-page IEEE manuscript, 22 references, covering FYP-1 and FYP-2 as one comparative study.

All four are written. Two still need their compute runs.

Step back from the laptop.

Shehroz Kashif.

Slide 4 — Architecture, Modules 5 and 6 · 101 words · 43 s

The figure is the methodology. Trace it with your hand, bottom to top, left plate first. Do not read the boxes out — name the three things below and let the diagram carry the rest.

Thank you, Ahmad. This is what we built. Read it bottom to top: the last four frames go up the left, the noisy candidate up the right.

Point at the orange block between the two columns.

The block in the middle is the one to single out: it tells the model how far ahead it is predicting, and it feeds *both* sides. Without it the task cannot be learned.

It also predicts the *correction* to a straight-line guess rather than the motion itself — so even when it learns little, it beats guessing naively.

Move to the right plate.

The right half is Module 6: it takes the checkpoint, never trains, and asks three questions.

Slide 5 — Metrics chosen, and what they measured · 92 words · 39 s

Lead with the three questions, not the metric names. The figures are on the slide.

We measure three things: is the shape in the right place, is the motion pointing the right way, and does the model know when it is unsure.

The second matters because a shape score alone cannot separate a model that learned nothing from one that learned the right direction but the wrong distance.

Three answer cards, right side. Say what each means, not its value.

The answers. On accuracy we are not ahead, and we lose on all ten videos. But the direction is clearly learned, and the model's confidence tracks its real error — so the failure is *how far*, not *which way*.

Slide 6 — What we build on, and where we go past it · 90 words · 39 s

The comparison slide, and it deserves its time. Four rows, left then right.

EndoGaussian and Deform3DGS reconstruct surgical scenes beautifully — but with two cameras, and only what already happened. We match them from one camera, then predict forward.

PointRNN — the one Ahmad mentioned — was built for rigid outdoor scenes, and gives one answer with no confidence attached.

Luo and Hu's diffusion generates plausible shapes, not futures. Ours is conditional on time.

And surgical anticipation does predict the future — but in flat pixels, and only when told the instrument's action.

Read the gold line as your closing sentence.

No published method does all of it at once.

Step back.

Humair.

Humair Khan (22i-2623) — Slide 7, then the demonstration

Slide 7 — Remaining work until the final evaluation · 82 words · 35 s

Give each item a status, not a hope.

Five things remain, in the order they have to happen.

One: run the full comparison and the tuning studies. Both are written and tested — what is left is compute, not code.

Two: evaluate the two corrections already implemented — one needs no retraining.

Three: hold out an entire video rather than frames from videos we train on.

Four: fold the finished results into the manuscript.

Five: submit, and grow the dataset.

Go straight into the demo. Do not pause for questions.

And with that, let me show you the system running.

The Demonstration — Humair drives, slides 8 to 12

No verbatim script, because a live system will not run to one. These are the lines to have ready while cells execute.

Slide 8 — while the notebook loads

Everything from here is live — nothing is pre-rendered. We load the trained model, check the data it is being tested on, predict a moment it has never seen, draw that prediction as an actual video frame, compare it against the real one, and then run past the end of the recording.

Slide 9 — while the render cell runs

There is a gap to bridge here. The prediction moves a few hundred tracked points; a picture needs the whole scene, which is tens of thousands. So the motion of the tracked points is carried outward onto everything around them.

Two honest notes about what you are seeing. Tissue moves only a pixel or two between frames, which is invisible, so the arrows are magnified — and that magnification is printed on the panel and never applied to any measurement. And the forecast runs past the end of the recording: the real-video panel stops and says so, while the predicted panel keeps going. That is the only output that shows prediction rather than describing it.

Slides 10 to 12 — describing the results

Agree beforehand whether you or Shehroz Kashif narrates these. One of you, not both.

The key finding: the model knows which way the tissue moves, not how far. Then uncertainty — when the model's own samples disagree with each other, its prediction really is worse, which means it can flag its own weak moments. A system that is confidently wrong is unusable in theatre; one that says "don't trust me here" is usable even when imperfect. And finally the full comparison against both simple baselines.

> **Demo checklist — the day before, not on the day.**
>
> - Runtime connected, GPU confirmed, checkpoint verified loadable.
> - Run the whole demo path end to end twice. Time the slowest cell; know what you will say over it.
> - Deck, notebook, checkpoint and outputs on **one laptop**.
> - Fallback: if the runtime dies, show the already-executed notebook and say plainly that it is not re-executing. Do not pretend.
> - Screen resolution set so notebook text is readable from the back of the room.

Questions

The deck is now twelve slides, so most answers live on a slide you have already shown. Do not recite figures from memory — turn to the slide.

If the question is about…	Answers · slide

How the model works, the forward pass, the conditioning, why diffusion	**Ahmad** · 4
Goals, scope, how the FYP-1 feedback was addressed	**Ahmad** · 2, 3
Metrics, baselines, evaluation integrity, the direction finding, uncertainty, the comparison numbers	**Shehroz Kashif** · 5, 10, 11, 12
Literature positioning and the base papers	**Humair** · 6
The demo, rendering, the forecast, the dataset	**Humair** · 8, 9
Anything needing the training curve, each module in detail, the problems-and-fixes tables, or the full literature table	Not in this cut — say so, and offer to show it after

The one answer to agree on. "Your model doesn't beat a simple baseline — why should this pass?" One person answers: *"Because we can tell you exactly why it doesn't. We measured that it learns which way tissue moves and fails only on how far; we tested and ruled out the two obvious alternative explanations; and we have implemented the two corrections that follow. We also get a confidence estimate that none of the baselines can give you. For a research project, a measured negative with an identified cause is worth more than an unexplained positive."*