AHMADREZA SAMADI

A smaller bill. A higher unit cost.

Both can be true when fewer results are accepted.

	Manual	AI
Total cost	24.00	18.40
Accepted results	3	2
Per accepted result	8.00	9.20

FICTIONAL TEACHING EXAMPLE

Start with the decision.

Same recorded IDs. Different outcomes.

Both fictional ledgers contain the same three result IDs. The acceptance counts differ.

	A	B	C
Manual	accepted	accepted	accepted
AI	accepted	accepted	error

AHMADREZA SAMADI

24 divided by 3. That is 8.

Manual ledger: 24 units spent, 3 results accepted.

$$\frac{24.00}{3 \text{ accepted}} = 8.00$$

units per accepted result

FICTIONAL TEACHING EXAMPLE

Start with the decision.

18.40 divided by 2. That is 9.20.

AI ledger: 18.40 units spent, 2 results accepted.

$$\frac{18.40}{2 \text{ accepted}} = 9.20$$

units per accepted result

Count every recorded attempt.

Include failed runs, retries and review costs. An unknown cost is an input error, not zero.

- **Model**
- **Tools**
- **Review**
- **Other**

Record zero only when known.

FICTIONAL TEACHING EXAMPLE

Start with the decision.

AHMADREZA SAMADI

Define acceptance. Then compare.

Same IDs alone do not prove fairness or quality. Keep the acceptance rule and cost coverage consistent.

Decision | **Acceptance rule** | **Full costs**

Read accepted counts beside costs.

FICTIONAL TEACHING EXAMPLE

Start with the decision.