Explore

coursera

<u>°</u>

Q

Convolutional Neural Networks

- Video: Computer Vision 5 min
- Video: Edge Detection
 Example
 11 min
- Video: More Edge Detection 7 min
- Video: Padding 9 min
- Video: Strided Convolutions
 9 min
- Reading: Strided convolutions
 CORRECTION

 1 min
- Video: Convolutions Over
 Volume
 10 min
- Video: One Layer of a
 Convolutional Network
 16 min
- Video: Simple Convolutional Network Example 8 min
- Reading: Simple
 Convolutional Network
 Example *CORRECTION*
 1 min
- Video: Pooling Layers
 10 min
- Video: CNN Example 12 min
- Reading: CNN Example

CNN Example *CORRECTION*

Starting from 9:45, please note that the calculation of the number of parameters is incorrect.

Here is a screenshot of that slide:

Neural network example

	Activation shape	Activation Size	# parameters
Input:	(32,32,3)	_ 3,072 a ^{Tol}	0
CONV1 (f=5, s=1)	(28,28,8)	6,272	208 <
POOL1	(14,14,8)	1,568	0 ←
CONV2 (f=5, s=1)	(10,10,16)	1,600	416 <
POOL2	(5,5,16)	400	0 ←
FC3	(120,1)	120	48,001
FC4	(84,1)	84	10,081
Softmax	(10,1)	10	841

Andrew Ng

Here are the 5 typos:

- 1. 208 should be (5*5*3 + 1) * 8 = 608
- 2. 416 should be (5*5*8 + 1) * 16 = 3216
- 3. In the FC3, 48001 should be 400*120 + 120 = 48120, since the bias should have 120 parameters, not 1
- 4. Similarly, in the FC4, 10081 should be 120*84 + 84 (not 1) = 10164

(Here, the bias is for the fully connected layer. In fully connected layers, there will be one bias for each neuron, so the bias become In FC3 there were 120 neurons so 120 biases.)

5. Finally, in the softmax, 841 should be 84*10 + 10 = 850