Cybersecurity Research with Industrial CPS Data

A research agenda and methodological guide

Prepared for the repository maintained by **Dr Ahmad Mohsin**
Dataset release 1.0.0

Abstract

This guide examines how a curated industrial cyber-physical systems dataset supports research in exposure analysis, knowledge graphs, grounded threat intelligence, behavioral monitoring, digital twins and governed AI agents. It distinguishes structural, synthetic, observational and expected-decision evidence, and identifies the additional labels, mappings and validation needed for stronger claims. Research questions are paired with suitable inputs, comparison designs, evaluation measures and limitations. The opening schematics establish the relationship between physical services, digital representations and analytical authority. Proposed experiments are distinguished from the release's recorded offline validation.

Research lineage. This programme of research began in 2023 with Mohsin and colleagues' shift-left/shift-right security digital-twin work [15]. It subsequently developed through the AI/XAI review [16], lifecycle security and privacy analysis [17], and later graph-grounded, LLM-enabled and sector-specific studies [1–4,18].




Figure 1: Conceptual scope. Solid arrows relate system concepts; the dashed path requires validation and a separate authority decision. Original TikZ figure.

Scope. The data support bounded offline research. They do not constitute a complete operational plant, a universal intrusion benchmark or authorization for autonomous process control. Figures 3–14 are generated scientific illustrations. Graphs, curve icons and supplementary symbols are schematic, not measured results.

Repository. https://github.com/ahmadspm/industrial-cps-security-datasets

Keywords: industrial cybersecurity; critical infrastructure; digital twins; knowledge graphs; agentic AI; reproducibility.

Context I: cyber-physical systems and critical infrastructure

A critical service relies on physical processes, control systems and organizational supervision. Cybersecurity failures can affect the integrity of observations, the availability of control or the correctness of decisions. An anomaly in a released record is not, by itself, evidence of a physical consequence. Figure 2 locates these dependencies within a representative CPS architecture [12].



Water systems Energy systems Manufacturing




Figure 2: Critical-infrastructure contexts above a representative CPS feedback loop. AI-generated, photorealistic infrastructure illustrations are shown above the conceptual control loop. They do not depict identified sites or dataset collection locations.

Dataset connection. Inventory and dataflow tables describe selected structural relationships. Operational features describe pseudonymized event sequences. Synthetic logs support controlled comparisons. They support exposure, monitoring and evidence-interpretation studies; measured service loss requires additional process and incident evidence.

Interpretation. Commands and measurements are distinct information flows. A study should specify which flow is observed or perturbed, and what evidence links a deviation to an operational outcome. No live connection between this repository and physical equipment is asserted.

Context II: digital twins and governed agentic AI

Digital twins represent selected entities, states and transitions for observation and analysis. Their usefulness depends on the credibility of the representation and its intended use [13]. An agent adds planning and tool selection, creating a separate question about permission to act. Recent agentic-AI guidance emphasizes bounded tasks, oversight and monitoring [14].




Figure 3: Digital-twin and agentic-AI research architecture. The policy gate is external to the generated plan. Feedback requires a declared evaluation rule; audit-log features are proposed rather than supplied. The release supplies selected representations and fixtures, not this complete integrated runtime.

Research implication. Twin fidelity, answer correctness, policy agreement and operational safety are different constructs. The 400 expected agent decisions support fixture-level evaluation; the 29 event traces support bounded sequence research. Neither alone certifies the combined architecture.

Context sources. [12] Stouffer et al. (2023), *Guide to OT Security*, NIST SP 800-82r3. [13] Voas et al. (2025), *Security and Trust Considerations for Digital Twin Technology*, NIST IR 8356. [14] ASD and international partners (1 May 2026), *Careful adoption of agentic AI services*.

1 Research lineage: lifecycle security to evidence-grounded AI

The research programme underlying this collection began in 2023 with *Digital Twins and the Future of Their Use Enabling Shift Left and Shift Right Cybersecurity Operations*, by Mohsin, Janicke, Nepal and Holmes [15]. Its September 2023 preprint and TPS-ISA 2023 record establish this starting point. The work placed security digital twins across the CPS lifecycle: *shift left* brings security analysis into design, while *shift right* supports analysis during operation. This history concerns the research programme; it does not imply that every released data record was collected in 2023.

From lifecycle models to interpretable security analysis

The subsequent state-of-the-art AI/XAI review by Sarker, Janicke, Mohsin, Gill and Maglaras [16] organized AI and explainable-AI methods for cybersecurity in digital-twin environments. It provides a methodological foundation for examining the quality and interpretability of security analytics. The later chapter *Security risks and privacy challenges in digital twins* [17] extended the lifecycle perspective to security, privacy and architectural concerns, including a smart-factory case study.

LLM-enabled reasoning represents a later strand of this programme rather than a capability that should be attributed retrospectively to every earlier publication. The guide's graph-grounded CTI and query-generation studies connect to NeuroGraph [2]; its separation of recommendations from permission to act also relates to the trusted-autonomy work [3]. BRIDG-ICS [1] and HySecTwin [4] provide further context for graph integration and hybrid reasoning. These connections motivate the research questions; they do not establish that the public subset reproduces each article's experiments.

Sector-specific modelling and the present research resource

The supplied railway paper, *A Secure-by-Design Virtual Twin Framework for AI-Driven Threat Modeling in Railway OT Systems* [18], places virtual-twin threat modelling in a transport-OT setting. It is included as a related sector-specific work. Railway records are not asserted to be present in this industrial dataset, and transfer of a method requires the independent validation described in the cross-sector study.

Research strand	Prior-work connection	Use in this guide
Lifecycle security	Shift-left/shift-right digital twins [15]	Design-stage topology studies and operational monitoring questions
Interpretable analytics	AI/XAI methods and taxonomy [16]	Baseline comparisons, explanation support and error analysis
Security and privacy	Digital-twin lifecycle and architecture [17]	Provenance, pseudonymization and evidence limitations
LLMs and reasoning	NeuroGraph and trusted autonomy [2,3]	Grounded answers, semantic queries and bounded decisions
Sector application	Railway virtual-twin work [18]	Transfer questions and sector-specific validation requirements

The present collection makes selected representations and offline fixtures available for further investigation of these themes. Its value lies in enabling transparent, bounded experiments across structural, synthetic, observational and expected-decision evidence. Researchers should cite the relevant intellectual foundations as well as this particular dataset release.

2 Contemporary security problems, 2025-2026

Loss of monitoring and control through exposed PLCs

A July 2026 FBI/EPA announcement reports water-sector incidents involving internet-facing PLCs, with changes to configurations and credentials causing loss of monitoring or control [9]. This motivates research on communication boundaries, trusted configuration evidence and restoration priorities. The inventory and graph tables support an abstract comparison of exposure-reduction policies; they contain neither packet captures nor forensic records of those incidents.

Authority and reliability in AI-enabled OT

The December 2025 joint guidance on secure AI integration in OT emphasizes suitability assessment, governance, oversight and lifecycle testing [10]. A research implication is that model accuracy and permission to act should be evaluated separately. The agent fixtures can test tool eligibility and stop decisions. Their expected outputs cannot establish the safety of direct process control.

Manipulated inputs and ungrounded explanations

NIST 2025 adversarial machine-learning taxonomy covers attacks across the AI lifecycle [11]. For this corpus, a tractable research question concerns whether controlled corruption of graph facts or retrieved evidence changes an analytical conclusion. Such experiments require newly constructed perturbations with explicit attacker capabilities; the release does not supply a validated poisoning or prompt-injection benchmark.

Sources: [9] FBI/EPA, 30 July 2026: Water-sector PLC warning. [10] ASD and international partners, 4 December 2025: Secure AI integration in OT. [11] Vassilev et al., March 2025: NIST AI 100-2 E2025.

These connections are proposed research uses, not claims that the dataset contains contemporary campaigns. The security contribution should be stated at the level actually evaluated: topology, reference mapping, controlled robustness or fixture-level decision behavior.

3 Potential research areas and open problems

Area / open problem	**Testable question**	**Inputs and expected contribution**
Exposure and segmentation	Can boundary-aware monitoring improve weighted flow coverage at the same budget?	Inventory + topology; resource-allocation method
Explainable graph inference	Does relation typing improve held-out link ranking without inverse-edge leakage?	Knowledge graph; auditable structural inference
Grounded CTI analytics	Does graph evidence reduce unsupported identifiers at matched answer coverage?	CTI benchmarks + graph; calibrated mapping
Security query generation	Does adaptation generalize beyond familiar query templates?	Training pairs + new disjoint test set; semantic validation
Behavioral anomaly analysis	Can unusual transitions be detected across held-out traces?	Operational traces; exploratory or adjudicated evaluation
Adversarial AI robustness	How much controlled evidence corruption changes a decision?	Derived graph/CTI variants; robustness characterization
Agent governance	Do policy guards reduce prohibited decisions under held-out scenario families?	Expected-decision fixtures; explicit policy evaluation
Human-centered triage	Does a traceable evidence chain improve reviewer accuracy and review time?	Validated joins + new analyst study; decision-support evaluation

The interpretability questions are informed by the earlier AI/XAI review [16]. The questions are deliberately comparative. A new model name or higher score alone is insufficient: the experiment should isolate the proposed mechanism, define the independent evaluation unit and identify the practical meaning of the observed difference. No novelty claim is implied without a separate literature review.

4 Dataset suitability and evidence gaps

Suitability is assessed for a specified research claim rather than for an algorithm in isolation. Direct support means that the necessary released inputs exist for a bounded offline task. Conditional support means that labels, mappings or an evaluation set must be added. Unsupported claims require a different empirical basis.

Data family	**Suitability in this release**	**Additional evidence for broader claims**
Inventory	Direct: topology, boundary coverage and prioritization	Observed configurations, controls and exposure validation
Knowledge graph	Direct: typed relation analysis; conditional: risk inference	Adjudicated relations; time-stamped updates; measured outcomes
CTI benchmarks	Direct: reference-label mapping comparisons	Independent label review; evidence corpus for faithfulness
Training pairs	Conditional: adaptation and query generation	Template-disjoint held-out prompts; semantic oracle
Synthetic	Direct: controlled sensitivity experiments	Real incident labels and external operational validation
Operational	Direct: sequence description; conditional: intrusion detection	Attack/fault adjudication; signal meanings; physical context
Agent scenarios	Direct: expected-policy agreement	Actual execution traces; independent outcome and safety criteria
Cross-source fusion	Conditional: only validated joins	Identity/time mappings and a documented coverage audit

The corpus alone is unsuitable for measuring field intrusion-detection effectiveness, certifying autonomous control, estimating sector-wide attack prevalence, proving causal physical consequences, or establishing a current vulnerability risk score. These are evidence limitations, not conclusions about the usefulness of the data.

5 A focused study of adversarial AI robustness

A defensible extension is to examine whether analytical outputs remain stable when a bounded portion of their evidence is manipulated. The independent variable is the perturbation budget; the primary outcome is the change in correctness or unsupported-claim rate relative to a clean evaluation. The threat model must specify access, knowledge and the records that an adversary can modify.




Figure 4: Controlled evidence manipulation. Blue: evidence; amber: design; grey/green: comparison; purple: evaluation; teal: reporting.

Researchers may remove relations, introduce type-consistent false relations, or add conflicting retrieved statements to derived copies. Each variant should record affected IDs and its construction rule. Label leakage, malformed inputs and plausible but incorrect evidence should be analyzed separately. Prompt injection requires a separately constructed textual corpus and task-specific success criteria; no such benchmark is supplied.

Useful outcomes include degradation curves, false-evidence acceptance, abstention under contradiction and recovery after evidence removal. Results support a claim about the declared perturbation model, not about resistance to all adaptive adversaries.

6 Cross-sector relevance and transfer limits




Figure 5: Evidence required for cross-sector transfer.

Application context	Transferable research method	Required sector-specific additions
Water and wastewater	Boundary analysis; change/anomaly triage	Hydraulic/process model, asset mapping, quality/pressure limits
Electricity and DER	Evidence-grounded prioritization; guarded recommendations	Electrical topology, grid dynamics, protection and timing constraints
Manufacturing	Flow coverage; sequence analysis; agent fixture evaluation	Verified station semantics, production modes and incident labels
Transport services	Dependency reasoning and evidence provenance	Relevant control systems, interlocks, operational and safety outcomes

Cross-sector applicability is a hypothesis to test. Similar network protocols do not imply equivalent dynamics, hazards or response authority. The transfer diagram identifies the additional evidence required to evaluate that hypothesis.

7 Threats to validity and research interpretation

Construct validity

A proxy must be distinguished from the phenomenon of interest. Coverage of declared flows measures monitoring placement, not prevention of compromise. Expected policy agreement measures consistency with an oracle, not physical safety. Unusual event sequences measure deviation, not necessarily malicious behavior.

Internal validity

Duplicate descriptions, repeated attackability tables and inverse graph relations can contaminate a comparison. Preprocessing, retrieval indexing and hyperparameter selection must follow the split. For LLM studies, expected answers and direct answer-bearing records should be excluded from the evaluated input. Model pretraining contamination remains a separate uncertainty.

External validity

The industrial setting, pseudonymization, synthetic assumptions and small number of independent traces restrict generalization. A large row count does not substitute for independent sites, operating modes or incidents. Transfer studies should evaluate an additional, independently curated dataset and disclose differences in sensors, protocols and labels.

Statistical conclusion validity

Repeated windows from one trace are correlated. Confidence intervals should reflect grouping by trace, entity, description or scenario family. Multiple model comparisons should be distinguished from a prespecified primary analysis. Effect sizes and failure distributions are more informative than isolated best-run scores.

A manuscript should acknowledge these limitations where the relevant result is interpreted, rather than relying only on a general limitations paragraph.

8 Study protocol and figure conventions

From research problem to an assessable claim

The lifecycle framing follows the shift-left/shift-right research [15,17]. A study protocol should state the operational motivation, the hypothesized mechanism, the released evidence, the intervention or model variation, and the outcome that could refute the hypothesis. A primary endpoint and evaluation split should be frozen before tuning. The baseline should represent a credible simpler approach under the same information and resource budget.

For example: under a fixed monitoring budget, a boundary-aware policy is hypothesized to cover a larger weighted proportion of declared cross-zone flows than degree ranking. A negative or negligible difference would refute the proposed benefit for this topology. The conclusion would concern the declared graph, with no claim about measured attack reduction.

Consistent meaning of workflow colours

Colour	**Role in the experimental argument**
Blue	Released evidence or frozen inputs
Amber	Study design, split construction or eligibility checks
Grey	Baseline or reference condition
Green	Proposed method or permitted branch
Coral	Held, rejected or unsupported branch
Purple	Common evaluation or evidence review
Teal	Reported outputs, uncertainty and provenance

Each box also states its role in text so the diagrams remain interpretable in greyscale. Comparison diagrams share inputs and evaluation conditions. Decision diagrams distinguish permitted and held branches. All workflows describe proposed research procedures, rather than newly measured experimental results.

The following sections document the evidence inventory, data loading, study protocols, evaluation measures and reproducibility requirements. Use the PDF bookmarks to navigate the guide.

9 Choose the evidence and the question

Folder / evidence	Release size	Research use
inventory / structural tables	94 master assets; 53 component records; 120 flows; 6 zones; 5 conduits	Segmentation and exposure
knowledge_graph / typed structure	305,167 nodes; 276,420 edges	Link prediction and graph reasoning
benchmarks / upstream reference labels	2,047 CTI records	CTI extraction and mapping
training / instruction-output examples	358 unique pairs	Query generation and adaptation
synthetic / generated assumptions and logs	340 attackability rows; 9,880 protocol rows	Controlled perturbations
operational / pseudonymized observations	14,124 events; 29 traces	Sequence and anomaly studies
agent_scenarios / expected fixtures	20 scenarios; 400 cases	Governed decision behavior

Folder counts are not independent evidence units. Some attackability tables are repeated in the graph and synthetic folders; do not count the same rows as independent replications.

Evidence classes matter

An observed event is not automatically an attack. A synthetic risk score is an assumption, not a measured compromise probability. A reference answer is not a newly adjudicated label. An expected agent output is a test oracle, not a successful tool execution. Graph referential integrity is not semantic truth.

Read data/README.md, the selected folder README, docs/SCHEMAS.md, docs/DATASET_CARD.md and metadata/licenses.csv before selecting features. Use metadata/provenance.csv and `metadata/research_file_map.csv` to trace inputs and related research.

10 Obtain, freeze and load the release

```
git clone https://github.com/ahmadspm/industrial-cps-security-datasets.git
cd industrial-cps-security-datasets
git rev-parse HEAD
python scripts/validate_release.py
```

Record the full commit, Python version and file SHA-256 values from metadata/checksums.csv. Run the validator from the repository root. Work in a separate output directory and retain the original compressed inputs unchanged.

CSV and compressed CSV: standard-library loader

```
from pathlib import Path
import csv, gzip, json

def rows(path):
    path = Path(path)
    opener = gzip.open if path.suffix == ".gz" else open
    with opener(path, "rt", encoding="utf-8-sig", newline="") as f:
        yield from csv.DictReader(f)

flows = list(rows("data/inventory/Dataflows.csv"))
cves = rows("data/knowledge_graph/cve_node_000.csv.gz")
first_cve = next(cves)
with gzip.open("data/operational/event_features.jsonl.gz",
               "rt", encoding="utf-8") as f:
    first_event = json.loads(next(f))
with open("data/training/fine_tuning.json", encoding="utf-8") as f:
    instruction_pairs = json.load(f)
```

CSV values load as strings. Convert numeric and boolean columns explicitly from the schema; distinguish missing values from zero. Stream all 15 CVE shards for the full CVE table. Do not load a plain CSV sibling in addition to its compressed release file.

No database service is needed to inspect the data. A graph store, embedding model or LLM is a researcher-selected addition and must be versioned separately.

11 Design an experiment before fitting

Specify one primary question, unit of analysis, eligibility criteria and testable outcome. Select a baseline before inspecting held-out results. Separate data quality checks from the security hypothesis.




Figure 6: Evidence quality determines which evaluation claims are supportable.

Use group-based splits when records share a description, flow, trace, entity or scenario template. Keep related versions and inverse graph facts on the same side of the split. Record exclusions and split identifiers before tuning. Fit transformations only on training data [8].

Use MITRE ATT&CK for ICS as a vocabulary for analyst-reviewed mappings [7]. A technique association does not itself establish that an attack occurred. NIST CSF 2.0 can organize research outcomes; this dataset does not establish compliance [6].

12 Inventory: segmentation and exposure

Research area. Asset-centric exposure analysis
Problem statement. Incomplete knowledge of communication boundaries complicates the allocation of scarce monitoring resources.

Research question. Can a graph-aware monitoring policy cover important cross-zone flows more efficiently than a simple priority rule?

Materials and suitability. Use Dataflows.csv with assets-Master.csv, ZONES.csv and zones_conduits.csv. Treat the separate 53-record component inventory as a source requiring explicit mapping. Direct support for structural comparisons; measured intrusion likelihood and operational disruption require additional evidence.

Experimental design. Check asset/zone keys and join coverage; retain unmatched rows in an audit. Construct a directed asset-flow graph. Declare protocol/port and zone rules. Compare policies under equal sensor or intervention budgets.




Figure 7: A shared topology and budget enable a fair monitoring comparison. Network and curve icons are schematic, not the released topology or measured results.

Interpretation and limitations. Give cross-zone flow coverage, weighted coverage, selected locations and sensitivity to criticality weights. Reachability reflects declared connectivity, not proven exploitability. Removed identities and addresses cannot support deployment-specific claims.

13 Knowledge graph: inference and prioritization

Research area. Explainable threat intelligence and graph learning
Problem statement. A plausible association between a weakness, product and technique may be unsupported or produced by leakage between training and evaluation graphs.

Research question. Does a typed graph method recover held-out relations better than a relation-frequency baseline?

Materials and suitability. Use node and edge CSV/CSV.GZ files with metadata/graph_node_keys.json and graph_relation_rules.json. The release contains 291,577 CVE rows across 15 shards. Direct support for typed structural inference; temporal forecasting requires dated snapshots and verified future outcomes.

Experimental design. Select one relation and a transductive or entity-disjoint task. Split before creating inverse edges, embeddings or derived features. Remove held-out facts and equivalent inverse/derived facts from training. Use type-correct candidates; document negative sampling.




Figure 8: Split construction precedes graph feature generation.

Interpretation and limitations. Report MRR and Hits@k with candidate counts, or precision/recall on a defined labeled task. Unknown edges are not verified negatives. Zero unmatched endpoints confirms structure only. CVSS/EPSS/KEV attributes are historical snapshots; they are not current risk advice. The graph lacks a full narrative corpus.

14 CTI benchmarks: grounded answers

Research area. Evidence-grounded LLM security analytics
Problem statement. Fluent threat explanations may include incorrect identifiers or claims that are not entailed by retrieved evidence.

Research question. Does graph grounding improve technique or weakness mapping over the same model without retrieval?

Materials and suitability. Use 60 CTI-ATE, 996 CTI-RCM and 991 CTI-RCM-2021 records. GT is an upstream reference label. CTIBench is external work by Alam et al. [5], not authored by this repository maintainer. Direct support for reference-label mapping; citation faithfulness requires a separately adjudicated evidence set.

Experimental design. Use metadata/benchmark_split_groups.csv to keep related descriptions together across files. Hide GT and any direct answer-bearing path from the model input and retrieval index. Freeze prompts and retrieval budget. Normalize output to declared identifier sets; score abstentions explicitly.




Figure 9: Retrieval gains must be measured independently from answer leakage. CTI category icons illustrate the analytical setting, not an inventory of released benchmark labels.

Interpretation and limitations. Report exact-set match and micro/macro label precision, recall and F1 as appropriate to the GT representation. Distinguish parsing failures, wrong mappings and unsupported claims. Thirteen records from five conflicting-description groups were excluded during release preparation. Evaluate retained labels rather than assuming universal correctness. CTIBench terms include noncommercial/share-alike conditions.

15 Training pairs: query generation

Research area. Domain adaptation for security query generation
Problem statement. A model may memorize query templates while failing to generate semantically correct queries for unseen analytical tasks.

Research question. Can instruction tuning improve schema-valid, semantically correct query generation on unseen query families?

Materials and suitability. fine_tuning.json contains 358 unique instruction/output pairs after removal of 129 exact duplicates. These are development examples, not an official held-out benchmark. Conditional support: researchers must construct a disjoint evaluation set and validate query semantics.

Experimental design. Group near-duplicate instructions and query templates. Create train/dev/test groups and publish IDs. Reserve the test set before prompt engineering or adaptation. Compare a fixed base model with the adapted model on the same held-out prompts. Validate queries in a read-only sandbox if execution is part of the task.




Figure 10: Template separation reduces memorization-based evaluation.

Interpretation and limitations. Report syntactic validity, schema validity, execution success and semantic correctness separately. Textual exact match alone may reject equivalent queries. The release does not supply a ready-made hosted database or tuning pipeline. State any external examples, compute budget and model license; test contamination remains a limitation.

16 Synthetic data: controlled anomaly studies

Research area. Robust detection under controlled perturbations
Problem statement. A detector can learn generation artifacts instead of behavior relevant to an intrusion or operational anomaly.

Research question. How robust is an anomaly detector to documented timing or volume perturbations under different protocols?

Materials and suitability. Use 9,880 generated protocol rows and 340 attackability rows. Protocols include OPC UA, Modbus TCP, MQTT/MQTTS, HTTPS, SSH, RDP, S7comm and EtherNet/IP. Suitable for controlled algorithm comparison; field detection claims require independently labeled operational incidents.

Experimental design. Inspect protocol-specific fields before harmonizing. Split by flow or generation/scenario group where supported. Add perturbations to a derived copy with a recorded seed and explicit injection labels. Keep training and test generation groups disjoint. Compare equal-threshold-budget methods.




Figure 11: Labels introduced by the experiment stay separate from released values.

Interpretation and limitations. Give precision/recall, PR-AUC and false alarms per declared unit for the controlled task. Status/result fields are not universal malicious labels. ATTACKABLE controlStrength, pExploit, attackCost_min and riskWeight are synthetic assumptions, not empirical compromise outcomes. Test whether a model merely reconstructs the formula used to create its target.

17 Operational traces: sequence research

Research area. Behavioral monitoring and sequence modelling
Problem statement. Unusual sequences can reflect legitimate operating modes, incomplete observations or faults as well as malicious activity.

Research question. Can a sequence model identify unusual transitions more consistently than a local transition-frequency baseline?

Materials and suitability. event_features.jsonl.gz contains 14,124 records in 29 traces. Fields include trace_id, record_index, relative_seconds, event_class, signal_id, value, previous_value and ok. Suitable for exploratory sequence analysis; attack classification is conditional on new, verified labels.

Experimental design. Order within each trace using record_index and relative time; inspect missing or repeated times. Split whole traces before creating windows. Fit encoders and thresholds on training traces only. If no independent attack labels exist, use descriptive anomaly analysis or separately labeled controlled perturbations.




Figure 12: Trace boundaries and label availability constrain inference.

Interpretation and limitations. Report unusual-transition rates and review agreement for exploratory studies; use attack metrics only with justified labels. The ok field is not an attack label. Relative clocks are per trace. String values are state_ pseudonyms; units and original signal semantics may be unavailable. Do not infer physical meaning or align cross-trace clocks without evidence.

18 Agent scenarios: governed decisions

Research area. Assurance of agentic security workflows
Problem statement. An AI agent may select nonexistent tools, exceed a risk condition or continue after a required stop.

Research question. Does a policy guard reduce invalid tool selections and missed stop conditions relative to an unguarded decision policy?

Materials and suitability. Use 400 expected cases across 20 JSON scenarios. Each provides inputs and expected outputs/final decisions. These fixtures are distinct from the historical twin replay suites. Direct support for fixture-based policy evaluation; live tool safety and mission success are outside the fixture evidence.

Experimental design. Build a local fixture evaluator that reads tests and records actual outputs. Keep expected fields out of model prompts. Group by scenario family for held-out testing where feasible. Route proposals through tool-catalog, risk and stop checks before any simulated execution. Use deterministic mock tools for comparison.




Figure 13: The decision gate produces auditable allow/hold outcomes. Additional governance controls illustrate a proposed evaluator; they are not all encoded in the released fixtures.

Interpretation and limitations. Report case-level agreement, unsafe-decision rate, stop-condition recall, invalid-tool rate and bounded termination. Specify denominators and oracle limitations. Relevant fixtures cover unavailable tools, hallucinated tools, risk thresholds, loop guards and simulation-only eligibility. Expected outputs are policy references, not evidence of live attacks or operational safety certification.

19 Integrated study: evidence to review

Research area. Human-centered evidence fusion
Problem statement. Combining incompatible identities or clocks can create convincing but false cross-source explanations.

Research question. Can traceable evidence improve analyst prioritization compared with an inventory-only ranking?

Materials and suitability. Combine only demonstrably compatible inventory keys, graph relations and event identifiers. Different sources may not share identities or clocks. Conditional support: only explicitly validated identity and temporal mappings justify integrated analyses.

Experimental design. Create a mapping table with source keys, mapping rationale and confidence. Measure join coverage and unresolved records before fusion. Require supported joins for each evidence chain; retain unresolved records for review rather than guessing. Compare the same analyst tasks and time budget.




Figure 14: Evidence joins are an eligibility gate, not an assumption.

Interpretation and limitations. Report supported-join coverage, unsupported-claim rate, analyst agreement and review time with the study protocol. Blind reviewers to method where practical. Do not interpret a connected path as a confirmed attack chain. Explain how pseudonymization and missing semantics affect causal interpretation.

20 Metrics, uncertainty and fair comparisons

Task	Primary measures	Essential denominator / caveat
Label mapping	Exact set match; micro/macro F1	All eligible prompts; disclose parse failures and abstentions
Graph ranking	MRR; Hits@k	Candidate set size; filtered-known-fact rule; unknown negatives
Anomaly detection	PR-AUC; precision/recall; false alarms	Verified or injected labels; alarms per trace/time unit
Inventory optimization	Coverage; cost; uncovered critical flows	Fixed budget and declared weights; unmatched joins
Query generation	Syntax, schema and semantic validity	All test prompts; distinguish equivalent queries
Agent decisions	Agreement; invalid-tool and stop-failure rates	All eligible cases; independent failures may overlap

Define TP, FP and FN for the chosen positive unit. Precision = TP/(TP+FP); recall = TP/(TP+FN); F1 = 2PR/(P+R). State how zero denominators are handled. Accuracy alone can obscure rare-event failure.

Use identical splits, candidate sets, prompts and resource budgets across methods. Report multiple seeds for stochastic training. Bootstrap or summarize at the independent unit, such as trace, description group or scenario family; row-level resampling can understate uncertainty.

Use ablations that answer a question: remove graph evidence, remove policy guards, or replace a learned detector with a simple threshold. Report confidence intervals with method and sample size, practical effect size, failure cases and computational cost. Small numbers of independent groups limit generalization.

21 Replay the reference experiments

The release includes curated historical code under code/twin_reference and an offline orchestration script. Replaying this code checks reproducibility of its included fixtures. It does not train every proposed model in this guide or reproduce every paper claim.

```
python -m venv .venv
# Activate this environment using your platform convention.
python -m pip install -r code/requirements-replay.txt
python scripts/replay_offline.py --help
python scripts/replay_offline.py --source-root . --output replay_output
```

Use a clean environment and retain the installed package versions. Inspect scripts/replay_offline.py and docs/VALIDATION.md for the dependency-directory option and current execution behavior. Keep replay_output outside the published source manifest.

Interpret the recorded baseline correctly

validation/replay_summary.json records the prior release replay: 24 suites, 285 tests and 10 deterministic experiments. These are recorded validation results for the curated code, not a fresh model benchmark or a pass count for the 400 agent-scenario cases. A new run must report its own result and environment.

What to retain from a new run

- Exact repository commit, input checksums, command line and dependency versions.
- Per-suite exit status, test totals, experiment outputs and failure logs.
- Any local patches, model/provider configuration, seeds and elapsed time.
- A comparison of expected versus actual outputs; explain deviations without overwriting the reference result.

Offline fixtures do not require physical equipment, model weights, a hosted graph database or live network actions. If a separate study introduces those components, describe them as additional experimental infrastructure and report the authorization and isolation appropriate to that study.

22 Prepare a reusable research package

Minimal experiment manifest - fill in actual values

```
study_id: your-study-id
dataset_commit: FULL_COMMIT_SHA
input_paths: [SELECTED_RELEASE_FILES]
input_sha256_manifest: metadata/checksums.csv
question: PREDECLARED_QUESTION
unit_of_analysis: trace_or_group_or_entity
label_source: reference_or_adjudicated_or_injected_or_none
split_ids: path/to/frozen_split_ids.json
seed: YOUR_SEED
baseline: VERSION_AND_CONFIGURATION
method: VERSION_AND_CONFIGURATION
fit_scope: training_only
primary_metric: METRIC_AND_DENOMINATOR
uncertainty: METHOD_AND_RESAMPLING_UNIT
outputs: path/to/results
exclusions_and_limitations: path/to/audit.md
```

Before submission or release

State the cybersecurity question and threat assumptions; describe the exact subset and independent sample count; publish group splits and exclusions; separate observations from synthetic or expected values; include baselines and ablations; report all eligible outcomes, uncertainty and failures; and disclose external enrichment, model versions and compute.

Cite this dataset using CITATION.cff and cite the relevant original works [1-5]. Read LICENSE, LICENSE-CODE, THIRD_PARTY_NOTICES.md and metadata/licenses.csv: the compilation, code and third-party subsets have different terms. CTIBench is CC BY-NC-SA 4.0; a top-level badge does not override subset conditions.

Keep pseudonymized identifiers as released. Do not restore private identities or publish unreviewed source material. Share derived labels with their creation protocol and clear provenance. A public dataset paper should describe collection, curation, schema, permitted uses, quality checks and limitations separately from a method paper's performance claims.

23 Articles and methodological references

Article attribution and publication status follow docs/RELATED_PUBLICATIONS.md. A related article is context for a research theme, not proof that this curated subset reproduces its results.

[1] BRIDG-ICS: AI-grounded knowledge graphs for intelligent threat analytics in Industry 5.0 cyber-physical systems
Nandiya et al. (2026). Cybersecurity 9, article 167. Published journal article.
https://doi.org/10.1186/s42400-026-00597-0

[2] NeuroGraph: An AI Graph-Driven Neuro-Symbolic Framework for Explainable Threat Reasoning in Advanced Manufacturing
Nandiya et al. (2026). Preprint arXiv:2609.00604. Author reports acceptance in International Journal of Information Security; final journal DOI not supplied.
https://arxiv.org/abs/2609.00604

[3] A Unified Framework for Human-AI Collaboration in Security Operations Centers with Trusted Autonomy
Mohsin et al. (2026). ACM Transactions on Internet Technology. Journal DOI below; preprint arXiv:2505.23397.
https://doi.org/10.1145/3837073

[4] HySecTwin: A Knowledge-Driven Digital Twin Framework Augmented with Hybrid Reasoning for Cyber-Physical Systems
Holmes et al. (2026). Preprint arXiv:2605.11682. Related project: HybridSec-Digital-Twin-CSP-Modelling, ahmadspm on GitHub.
https://arxiv.org/abs/2605.11682

[4a] Autonomous Cyber-Physical Security Assessment in Smart Manufacturing with a Behavioural Digital Twin and Agentic AI
Nandiya, Mohsin, Lohmann, Ekelhart, Sarker and Janicke (n.d.). Author-supplied manuscript; no public article URL or final publication metadata supplied.
Related-publications record in this repository

[5] CTIBench: A benchmark for evaluating LLMs in cyber threat intelligence
Alam, Bhusal, Nguyen and Rastogi (2024). NeurIPS 37, 50805-50825. External benchmark; not authored by the maintainer.
https://doi.org/10.52202/079017-1607

[6] The NIST Cybersecurity Framework (CSF) 2.0
NIST (2024). CSWP 29. Outcome vocabulary for framing research; not an evaluation certificate.
https://doi.org/10.6028/NIST.CSWP.29

[7] ATT&CK for ICS matrix
MITRE. Technique and tactic vocabulary. preserve the version used for mappings.
https://attack.mitre.org/matrices/ics/

[8] Common pitfalls and recommended practices
scikit-learn documentation. Train/test separation and leakage prevention.
https://scikit-learn.org/stable/common_pitfalls.html

Earlier foundations and related sector application

[15] Digital Twins and the Future of Their Use Enabling Shift Left and Shift Right Cybersecurity Operations
Mohsin, A., Janicke, H., Nepal, S., and Holmes, D. (2023). In *2023 5th IEEE International Conference on Trust, Privacy and Security in Intelligent Systems and Applications (TPS-ISA)*, pp. 277–286.
doi:10.1109/TPS-ISA58951.2023.00042; September 2023 preprint.

[16] Explainable AI for cybersecurity automation, intelligence and trustworthiness in digital twin: Methods, taxonomy, challenges and prospects
Sarker, I. H., Janicke, H., Mohsin, A., Gill, A., and Maglaras, L. (2024). *ICT Express*, 10(4), 935–958.
doi:10.1016/j.icte.2024.05.007.

[17] Security risks and privacy challenges in digital twins
Mohsin et al. (2026). In *Foundations of Digital Twins*, pp. 239–252. Elsevier.
doi:10.1016/B978-0-443-43896-7.00016-9.

[18] A Secure-by-Design Virtual Twin Framework for AI-Driven Threat Modeling in Railway OT Systems
Neupane, N., Mohsin, A., Sarker, I. H., Sikos, L. F., and Janicke, H. (2026). KES 2026 work; bibliographic attribution supplied by the author. The linked record was supplied for this edition; final publisher DOI and pagination have not been independently verified.
Author-supplied ResearchGate record.