

# The option "level-seed" is not present in server.properties by default

[MC-244137](#) DEDICATED SERVER

|                 |                                    |
|-----------------|------------------------------------|
| Status          | Resolved / Fixed                   |
| Affected        | 1.18; 1.18.1 Pre-release 1; 1.18.1 |
| Fixed in        | 1.18.2 Pre-release 1               |
| Reported        | 2021-12-03                         |
| Mojira category | Dedicated Server                   |

## REPRODUCTION TARGET

Use version: 1.18

Affected versions (3):

1.18

1.18.1 Pre-release 1

1.18.1

Environment:

Minecraft: Java Edition 1.18 dedicated server running from a new, otherwise empty local working directory. Use Java 17 or newer, a terminal or command prompt, and a plain-text editor. Keep the historical server local and do not expose it to the public internet; no Minecraft client connection is required for this reproduction.

## PRECONDITIONS

---

- Obtain the dedicated-server JAR for exactly Minecraft: Java Edition 1.18; do not use 1.18.2 Pre-release 1 or another fix/newer version.
- Install Java 17 or newer and ensure the `java` executable is available from the terminal or command prompt.
- Be able to accept the Minecraft EULA by editing the generated `eula.txt` file after reviewing it.
- Use a new server directory that does not already contain `server.properties`, `eula.txt`, a world, or files generated by a different server version.
- Have permission to create, edit, and read files in the selected server directory.

## STEPS TO REPRODUCE

### 1 INFERRED

Create a new empty directory dedicated to this reproduction. Do not copy an existing `server.properties` file or an existing world into it.

**SUCCESS CUE** The reproduction directory exists and contains no files.

### 2 INFERRED

Place the dedicated-server JAR for exactly Java Edition 1.18 in the empty directory and rename it to `server.jar` so that the launch command below can be used unchanged.

**INPUT** `server.jar`

**SUCCESS CUE** The directory contains only the Java Edition 1.18 server JAR named `server.jar`.

### 3 INFERRED

Open a terminal or command prompt with the reproduction directory as its current working directory.

**SUCCESS CUE** The terminal's current directory is the same directory that contains `server.jar`.

### 4 VERIFIED

Check the Java runtime available to the terminal. Enter the command and press Enter.

**INPUT** `java -version`

**SUCCESS CUE** The command completes and reports Java version 17 or newer.

### 5 INFERRED

Perform the server's initial launch so it can create the EULA file. Enter the command exactly as shown and press Enter. `nogui` runs the dedicated server through this terminal rather than opening the server GUI.

**INPUT** `java -jar server.jar nogui`

**SUCCESS CUE** The process creates `eula.txt` and then stops because the EULA has not yet been accepted.

### 6 INFERRED

Open `eula.txt` in a plain-text editor. After reviewing and accepting the referenced EULA, replace the line `eula=false` with `eula=true`, save the file, and close the editor. Do not create or edit `server.properties` manually.

**INPUT** `eula=true`

**SUCCESS CUE** The saved `eula.txt` file contains `eula=true`, while `server.properties` has not been manually modified or supplied.

### 7 REPORT TRIGGER

Return to the terminal in the server directory and start the Java Edition 1.18 dedicated server again. Enter the command exactly as shown and press Enter. This successful startup is the action that causes the default server files, including `server.properties`, to be generated.

**INPUT** `java -jar server.jar nogui`

**SUCCESS CUE** The server process remains running and begins loading or generating its world and configuration files.

## 8 **REPORT**

Wait for startup to finish. Do not continue while the server is still preparing the spawn area or generating the world.

**SUCCESS CUE** The server console displays its normal `Done` startup message and presents the server console input prompt, indicating that initialization has completed.

## 9 **INFERRED**

Shut down the server cleanly from the running server console. Type `stop` without a leading slash and press Enter.

**INPUT** stop

**SUCCESS CUE** The console reports that the server is saving and stopping, and the Java process exits back to the operating-system terminal prompt.

## 10 **REPORT**

Open the reproduction directory in the operating system's file manager and locate the newly generated file named exactly `server.properties`.

**INPUT** server.properties

**SUCCESS CUE** A generated `server.properties` file is present in the same directory as `server.jar` and `eula.txt`.

## 11 **REPORT**

Open the generated `server.properties` file with a plain-text editor. Do not add, delete, reorder, or save any lines.

**INPUT** server.properties

**SUCCESS CUE** The generated file is open as plain text and is ready for inspection without having been modified.

## 12 **INFERRED**

Use the text editor's Find/Search function, commonly opened with Ctrl+F, and search for the exact property text `level-seed=`. Submit the search once, but leave interpretation of the search result to the observation subsystem.

**INPUT** level-seed=

**SUCCESS CUE** The exact-text search has completed and the editor is displaying its result state; no changes have been saved to the file.

## HANDOFF TO OBSERVATION

---

The Java Edition 1.18 dedicated server has completed one successful startup in a clean directory, has been stopped cleanly, and its unmodified generated `server.properties` file is open with an exact search for `level-seed=` completed. Hand off now for inspection and recording of the generated file contents.

## UNCERTAINTIES

---

- The report does not specify an operating system, filesystem path, server memory allocation, or server-GUI preference; this plan therefore uses the portable command-line ``nogui`` launch path without optional memory flags.
- The report only says to start the server and wait for files to generate. The EULA acceptance cycle is included as a practical prerequisite for obtaining a completed dedicated-server startup in a clean directory.
- The report does not state whether the file should be inspected while the server is running. This plan stops the server cleanly before inspection so the generated file is stable and no longer being written.
- The report says to read through the file but does not require a specific editor. An exact text search for ``level-seed=`` is used as a deterministic equivalent that avoids overlooking the property.
- External verification was limited to confirming that Java Edition 1.18 uses Java 17 and that the dedicated server can be run from the command line with the ``nogui`` option; the report remains the source of truth for the affected versions and reproduction action.

MANUAL RESULT

|                  |                    |
|------------------|--------------------|
| Version used     |                    |
| Reproduced?      | YES / NO / PARTIAL |
| Trigger reached? | YES / NO           |
| Crash file       |                    |
| Notes            |                    |
| Tested by / date |                    |