

Server Management Protocol Kick command parameter mis match

MC-301735 Dedicated Server

Status	Resolved / Fixed
Affected	25w35a, 1.21.9 Pre-Release 1, 1.21.9 Pre-Release 2
Fixed in	1.21.9 Pre-Release 4
Reported	2025-09-01

STEPS TO REPRODUCE

1. Set up the Server Management Protocol connection.
2. Send an `rpc.discover` request and locate the `minecraft:players/kick` command parameters.
3. Confirm that the discovered `kick` parameter is required and has an array schema containing `kick\_player` items.
4. Send the following payload through the Management Protocol:

```
`{"method":"minecraft:players/kick","id":0,"params":[[{"players":{"name":"jSdCool"}],"message":{"literal":"kick test"}}]]`
```
5. Observe that the target player is not kicked and the server returns `Invalid params: Not a JSON object: [{"players":{"name":"jSdCool"}],"message":{"literal":"kick test"}}`.

OBSERVED BEHAVIOUR

Actual behavior

The server rejects the request with an invalid-parameters error:

```
``text
```

Invalid params: Not a JSON object: [{"players":{"name":"jSdCool"}],"message":{"literal":"kick test"}}.

```
...
```

Although `rpc.discover` describes the `kick` parameter as an array of `kick\_player` objects, the server attempts to deserialize the supplied value as a single JSON object. Because the request supplies an array as indicated by the discovered schema, the kick operation is not executed and the target player remains connected.

EXPECTED BEHAVIOUR

The `minecraft:players/kick` command should accept the array-form parameter described by `rpc.discover`, including the target player and optional message. When a valid request is submitted in that format, the server should process it successfully and disconnect the specified player with the provided message, rather than rejecting the request because it receives an array where an object was expected.

ENVIRONMENT

Minecraft Java Edition Versions: 25w35a, 1.21.9 Pre-Release 1, 1.21.9 Pre-Release 2 (includes snapshots)

ORIGINAL DESCRIPTION

According to the information provided by the `rpc.discover` command, the kick command should require an array as input. This would be consistent with other similar commands.

- Steps to reproduce the issue
- setup the Management protocol
- Attempt to send a kick command as described by the command discovery

Kick parameters provided by discovery:

```
"params": [  
{  
  "name": "kick",  
  "schema": {  
    "items": {
```

```
"$ref": "#/components/schemas/kick_player"
},
"type": "array"
},
"required": true
}
]
```

Example payload that produces the error:

```
{"method":"minecraft:players/kick","id":0,"params":[[{"players":{"name":"SdCool"},"message":{"literal":"kick test"}]]]}
```

- Expected result

The target player is kicked from the server

- Actual result

The following error is received due to the fact the server was expecting an object not an array

```
Invalid params: Not a JSON object: [{"players":[
{"name":"SdCool"}
],"message":{"literal":"kick test"}]}
```

MANUAL RESULT

Version used	
Reproduced?	YES / NO / PARTIAL
Crash file	
Notes	
Tested by / date	

Live issue: <https://bugs.mojang.com/browse/MC/issues/MC-301735>