

Loot table function `set_count` doesn't work with unstackable items anymore

MC-229209 Loot tables

Status	Resolved / Fixed
Affected	1.17, 1.17.1, 1.19.3, 1.20.2
Fixed in	1.20.5 Pre-Release 1
Reported	2021-06-15

STEPS TO REPRODUCE

1. Launch Minecraft 1.16.5 and open the attached map containing the loot tables.
2. Use the map's existing setup to generate the loot table that contains one roll, a saddle entry, and `set_count`` with an exact count of 2.
3. Observe that the generated output contains two saddles in separate inventory slots.
4. Launch Minecraft 1.17 and open the same map.
5. Use the map's existing setup to generate the same exact-count loot table.
6. Observe that the generated output contains only one saddle instead of two.
7. Repeat the generation in Minecraft 1.17 with the range definition (`min` 2, max` 4`) and the binomial definition (`n` 4, p` 1`).
8. Observe that each unstackable-item output contains only one saddle, rather than filling multiple inventory slots with the count produced by `set_count``.

OBSERVED BEHAVIOUR

Actual behavior

In Minecraft 1.17, a loot table entry using the `set_count`` function produces only one instance of an unstackable item, even when the function resolves to a count greater than 1. For example, an entry that sets a saddle's count to `2`` gives the player only one saddle.

This occurs with all tested `set_count`` formats:

- An exact integer count, such as `"count": 2``
- A range count, such as `"min": 2, "max": 4``
- A binomial count, such as `"n": 4, "p": 1``

The issue affects unstackable items such as saddles and minecarts. In 1.16 releases, the same loot tables generated the requested number of items by placing each item in a separate inventory slot. In 1.17, only one item is generated or given to the player instead. The behavior is not caused by the formatting of the loot table JSON or by the other item functions (`set_nbt`` and `set_name``).

EXPECTED BEHAVIOUR

Loot tables using the `set_count`` function should grant the full number of unstackable items specified by exact, range, or binomial count settings. Items such as saddles and minecarts should be distributed across multiple inventory slots when necessary, just as they were in 1.16, rather than being reduced to a single item. This behavior should work consistently regardless of the loot table's formatting.

ENVIRONMENT

Minecraft Java Edition Versions: 1.17, 1.17.1, 1.19.3, 1.20.2

ORIGINAL DESCRIPTION

Issue

After updating to 1.17 I discovered that the `set_count` function for a loot table only outputs a single item to the player when it had previously given the intended amount throughout the 1.16 releases. Note this applies to all count settings including exact, range, and binomial. The error only applies to unstackable items such as saddles and

minecarts, in 1.16 multiple slots would be filled with a single unstackable item but now there is only one.

Recreate

Recreating this issue is simple and all you have to do is create a loot table with one roll that uses a function to set the count of an item. To assist with this report I have attached raw code, screenshots showing the transition between versions, and a map in 1.16.5 that contains all of the necessary loot tables.

Code 1: set_count exact (format 2)

```
{
  "type": "minecraft:entity",
  "pools": [
    {
      "rolls": 1,
      "entries": [
        {
          "type": "item",
          "weight": 1,
          "name": "minecraft:saddle",
          "functions": [
            {
              "function": "set_count",
              "count": 2
            },
            {
              "function": "set_nbt",
              "tag": "{CustomModelData:7}"
            },
            {
              "function": "set_name",
              "name": [
                {
                  "text": "Exact Format 2",
                  "color": "white",
                  "bold": "true"
                }
              ]
            }
          ]
        }
      ]
    }
  ]
}
```

Code 2: set_count range

```
{
  "type": "minecraft:entity",
  "pools": [
```

```

{
  "rolls": 1,
  "entries": [
    {
      "type": "minecraft:item",
      "name": "minecraft:saddle",
      "functions": [
        {
          "function": "minecraft:set_count",
          "count": {
            "min": 2,
            "max": 4
          }
        },
        {
          "function": "minecraft:set_nbt",
          "tag": "{CustomModelData:7}"
        },
        {
          "function": "minecraft:set_name",
          "name": [
            {
              "text": "Range",
              "color": "white",
              "bold": true
            }
          ]
        }
      ]
    }
  ]
}

```

Code 3: set_count binomial

```

{
  "type": "minecraft:entity",
  "pools": [
    {
      "rolls": 1,
      "entries": [
        {
          "type": "minecraft:item",
          "name": "minecraft:saddle",
          "functions": [

```

```

{
  "function": "minecraft:set_count",
  "count": {
    "type": "minecraft:binomial",
    "n": 4,
    "p": 1
  },
  {
    "function": "minecraft:set_nbt",
    "tag": "{CustomModelData:7}"
  },
  {
    "function": "minecraft:set_name",
    "name": [
      {
        "text": "Binomial",
        "color": "white",
        "bold": true
      }
    ]
  }
]
}
]
}
]
}
]
}
]
}

```

Notes

At first I thought it was because of the

MANUAL RESULT

Version used	
Reproduced?	YES / NO / PARTIAL
Crash file	
Notes	
Tested by / date	

Live issue: <https://bugs.mojang.com/browse/MC/issues/MC-229209>