

Specifying the size of a target in post effect shaders fails

MC-275445 Resource Packs

Status	Resolved / Fixed
Affected	24w33a, 24w34a
Fixed in	24w36a
Reported	2024-08-16

STEPS TO REPRODUCE

1. Launch Minecraft 24w34a.
2. Create a resource pack using pack format 36.
3. Copy `assets/minecraft/post\_effect/transparency.json` from the vanilla files into the resource pack.
4. Replace the file's `targets` field with:

```
```json
{
 "final": {},
 "potato": {
 "width": 16,
 "height": 16
 }
}
```
```

5. Enable the resource pack.
6. Set Graphics to Fabulous through Options -> Video Settings.
7. Observe that the resource pack fails to load and the log reports `Failed to parse post chain at minecraft:post\_effect/transparency.json` with a `JsonSyntaxException`.

OBSERVED BEHAVIOUR

Actual behavior

When the `targets` object contains a target mapped to an object with `width` and `height`, the post-effect JSON fails to parse. For example:

```
```json
"targets": {
 "final": {},
 "potato": {
 "width": 16,
 "height": 16
 }
}
```
```

Loading the resource pack with Fabulous graphics reports that `minecraft:post\_effect/transparency.json` failed to parse, and the post-effect shader is not loaded. The log contains:

```
```text
Failed to parse post chain at minecraft:post_effect/transparency.json
com.google.gson.JsonSyntaxException: Both alternatives read successfully, can not pick the correct one; ...
missed input: {"potato":{"width":16,"height":16}}
```
```

A target mapped to an empty object, such as `"final": {}`, is accepted. The failure occurs specifically when the target definition includes the `width` and `height` fields, even when the target is otherwise unused.

EXPECTED BEHAVIOUR

When the post-effect shader defines a target with explicit width and height, the resource pack should load successfully with Fabulous graphics enabled. The targets object should accept the specified dimensions for the unused "potato" target without producing a post-chain parsing error or preventing the transparency shader from loading, while the existing "final" target continues to work normally.

ENVIRONMENT

Minecraft Java Edition Versions: 24w33a, 24w34a (includes snapshots)

ORIGINAL DESCRIPTION

As of 24w33a, the "targets" field of post shaders is an object, instead of an array of objects/strings. It works correctly when the name of the target is mapped to an empty object. However having the object contain fields "width" and "height" fails to load the shader file.

Steps to Reproduce:

- Create a resource pack in version 24w34a (pack format 36)
- Copy the vanilla file `assets/minecraft/post_effect/transparency.json`
- In the "targets" field, write

```
{
  "final": {},
  "potato": {
    "width": 16, "height": 16
  }
}
```

- Load the resource pack with fabulous graphics

Observed Results:

The resource pack fails loading, and the game logs raise this error:

`deobf_latest.log`

Failed to parse post chain at `minecraft:post_effect/transparency.json`

`com.google.gson.JsonSyntaxException: Both alternatives read successfully, can not pick the correct one; first: (Left[b[]], {"width":16,"height":16}) second: (Right[a[width=16, height=16]], {"width":16,"height":16}) missed input: {"potato":{"width":16,"height":16}}`

`at com.mojang.serialization.DataResult$Error.getOrThrow(DataResult.java:287)`

`at ghx.b(SourceFile:145)`

`at ghx.a(SourceFile:80)`

`at ghx.b(SourceFile:36)`

`at auz.a(SourceFile:11)`

`at java.base/java.util.concurrent.CompletableFuture$AsyncSupply.run(CompletableFuture.java:1768)`

`at java.base/java.util.concurrent.CompletableFuture$AsyncSupply.exec(CompletableFuture.java:1760)`

`at java.base/java.util.concurrent.ForkJoinTask.doExec(ForkJoinTask.java:387)`

`at java.base/java.util.concurrent.ForkJoinPool$WorkQueue.topLevelExec(ForkJoinPool.java:1312)`

`at java.base/java.util.concurrent.ForkJoinPool.scan(ForkJoinPool.java:1843)`

`at java.base/java.util.concurrent.ForkJoinPool.runWorker(ForkJoinPool.java:1808)`

`at java.base/java.util.concurrent.ForkJoinWorkerThread.run(ForkJoinWorkerThread.java:188)`

Expected Results:

Since this is the vanilla file, in which we specified an unused target (the same as the example from the article, the game should not output an error.

Notes:

From what I understood reading the output logs, it seems the json interpreter struggles with the new syntax...

Attachment

The joined zip file is a resource packs, for 24w34a.It modifies the assets/m

MANUAL RESULT

| | |
|------------------|--------------------|
| Version used | |
| Reproduced? | YES / NO / PARTIAL |
| Crash file | |
| Notes | |
| | |
| Tested by / date | |

Live issue: <https://bugs.mojang.com/browse/MC/issues/MC-275445>