

Client continues to connect to server after canceling on 'Connecting to server' screen

MC-74984 NETWORKING

Status	Resolved / Fixed
Affected	Minecraft 1.8; Minecraft 1.8.1; Minecraft 1.8.3; Minecraft 1.8.4; Minecraft 1.8.7; Minecraft 1.8.8; Minecraft 1.8.9; Minecraft 1.9.1; Minecraft 1.9.2; Minecraft 1.9.4; Minecraft 1.10; Minecraft 1.11.2; Minecraft 17w16b; Minecraft 1.12; Minecraft 1.12.2; Minecraft 1.13; Minecraft 18w31a (+more)
Fixed in	1.20 Pre-release 5
Reported	2014-12-01
Mojira category	Networking

REPRODUCTION TARGET

Use version: Minecraft 1.8

Affected versions (30):

Minecraft 1.8

Minecraft 1.8.1

Minecraft 1.8.3

Minecraft 1.8.4

Minecraft 1.8.7

Minecraft 1.8.8

Minecraft 1.8.9

Minecraft 1.9.1

Minecraft 1.9.2

Minecraft 1.9.4

Minecraft 1.10

Minecraft 1.11.2

Minecraft 17w16b

Minecraft 1.12

Minecraft 1.12.2

Minecraft 1.13

Minecraft 18w31a

Minecraft 1.13.1

1.14.4

1.15.2

20w13b

1.16 Pre-release 5

1.16.1

1.16.2

1.16.3

1.16.4

20w51a

1.16.5 Release Candidate 1

1.16.5

1.19

Environment:

A clean, unmodified Minecraft Java Edition 1.8 client using one authenticated account, plus two distinct multiplayer servers designated Server A and Server B. Both servers must accept 1.8 clients and the account must be permitted to join both. Server A must be reachable but its connection must remain on the client's "Connecting to server" screen long enough to press Cancel; a delayed DNS lookup, proxy, network shaper, or naturally slow connection may be used to create that window. Server B should be normally reachable. Keep both server entries prepared in the Multiplayer server list so Server B can be selected immediately after canceling Server A. Use a newly started client process and do not restart Minecraft between the two connection attempts.

PRECONDITIONS

- Install or select the exact affected release Minecraft 1.8; do not use the fixed version 1.20 Pre-release 5.
- Use a vanilla client without client mods, because the report was confirmed on vanilla.
- Obtain the addresses of two different servers, Server A and Server B, that are compatible with Minecraft 1.8 and can be joined by the same account.
- Configure Server A or its network path so that selecting it leaves the client on the "Connecting to server" screen for long enough to click Cancel, while still allowing the connection attempt to continue toward a real, reachable server.
- Ensure Server B is online and normally reachable before beginning the timed portion of the reproduction.
- Fully close any previous Minecraft client process before the attempt, then launch a fresh client to avoid carrying over state from an earlier attempt.
- Do not disconnect normally from Server A, restart the client, or intentionally pause between canceling Server A and starting the connection to Server B.
- The timing is important: if Server A displays its world before Cancel is clicked, that attempt is invalid and must be repeated with a longer connection delay.

STEPS TO REPRODUCE

1 **REPORT**

In the Minecraft Launcher, select an installation configured for the exact release Minecraft 1.8 and start the game.

INPUT **Minecraft 1.8**

SUCCESS CUE The Minecraft title screen is open and identifies the running game version as Minecraft 1.8.

2 **INFERRED**

From the title screen, left-click Multiplayer to open the multiplayer server list.

INPUT **Multiplayer**

SUCCESS CUE The Play Multiplayer screen is visible and no world or server is currently open.

3 **INFERRED**

If Server A is not already listed, left-click Add Server, enter a recognizable name and the delayed Server A address supplied by the test environment, and then left-click Done.

INPUT **Server Name: Server A; Server Address: <delayed Server A address>**

SUCCESS CUE A row named Server A is visible in the multiplayer server list.

4 **INFERRED**

If Server B is not already listed, left-click Add Server, enter a recognizable name and the Server B address supplied by the test environment, and then left-click Done.

INPUT **Server Name: Server B; Server Address: <Server B address>**

SUCCESS CUE Separate rows named Server A and Server B are visible in the multiplayer server list.

5 **INFERRED**

Allow the server list to update only long enough to confirm that Server B is online. Do not begin the timed connection sequence until Server A's delay mechanism is active.

SUCCESS CUE Server B is available for joining, Server A's delayed connection path is active, and both rows remain visible.

6 **INFERRED**

Left-click the Server A row once so that Server A is the selected server.

INPUT **Server A**

SUCCESS CUE Server A is highlighted in the server list and Server B is not selected.

7 **REPORT**

Start joining Server A by left-clicking Join Server or by double-clicking the Server A row.

INPUT **Join Server**

SUCCESS CUE The server list is replaced by a connection-status screen.

8 **REPORT**

Wait only until the status screen visibly says "Connecting to server" and its Cancel button is available. Do not wait for terrain, a loading world, or Server A's in-game view. If Server A's world appears before this state can be acted on, disconnect normally, return to the server list, increase Server A's connection delay, and restart the attempt from a fresh client process.

INPUT Connecting to server

SUCCESS CUE The client is still on the "Connecting to server" screen, the Cancel button is clickable, and Server A's world has not appeared.

9 **REPORT** **TRIGGER**

While the screen still says "Connecting to server", immediately left-click Cancel once.

INPUT Cancel

SUCCESS CUE The connection-status screen closes without ever displaying Server A's world, and the client returns to either the multiplayer server list or the title screen.

10 **INFERRED**

If Cancel returned the client to the title screen, immediately left-click Multiplayer. If the multiplayer server list is already visible, perform no extra navigation. Do not restart or close the game.

INPUT Multiplayer

SUCCESS CUE The multiplayer server list containing Server A and Server B is visible in the same client process used for the canceled connection.

11 **REPORT**

Without an intentional delay, left-click the Server B row once.

INPUT Server B

SUCCESS CUE Server B is highlighted in the server list.

12 **REPORT**

Immediately start joining Server B by left-clicking Join Server or by double-clicking the Server B row.

INPUT Join Server

SUCCESS CUE The client leaves the server list and begins the connection to Server B without Minecraft having been restarted.

13 **REPORT**

Wait for Server B's world to finish loading. Continue only after terrain is rendered, the in-game HUD is visible, and ordinary movement input responds. Do not disconnect, restart, or join another world before handing control to the observation subsystem.

SUCCESS CUE The player is in Server B's loaded world in the same client process, immediately following the canceled Server A attempt, and normal in-game input can be issued.

HANDOFF TO OBSERVATION

The client has just completed entry into Server B in the same Minecraft 1.8 process used to press Cancel on Server A's "Connecting to server" screen. Server A was canceled before its world appeared, Server B was joined immediately afterward, and no client restart or normal Server A disconnect occurred. Begin observing the client's connection and world state now.

UNCERTAINTIES

- The report supplies no server addresses, so the executor must provide two distinct Minecraft 1.8-compatible servers.
- The reproduction is timing-sensitive, and the report does not define a maximum delay between pressing Cancel and joining Server B. The plan therefore requires joining Server B as quickly as the UI allows, with no intentional pause.
- A comment recommends increasing Server A's DNS/IP lookup time using a proxy that forces DNS lookups through the proxy, but the report does not provide an exact proxy product or configuration procedure.
- The original report reproduces the issue in Minecraft 1.8, while some more detailed reproduction comments refer to later affected versions such as 1.8.7 and 1.16.4. This plan uses the original Minecraft 1.8 cancel-then-join sequence to preserve recommended-version fidelity.
- Server A must be delayed but still reachable. A completely offline address or a connection that immediately fails may not preserve the in-progress connection condition described by the report.
- The report does not establish a precise success rate; multiple fresh-client attempts may be necessary if the connection to Server A completes too quickly or is fully terminated before Server B is joined.

MANUAL RESULT

Version used	
Reproduced?	YES / NO / PARTIAL
Trigger reached?	YES / NO
Crash file	
Notes	
Tested by / date	