NATIONAL UNIVERSITY OF COMPUTER AND EMERGING SCIENCES

PROGRAM: SOFTWARE ENGINEERING

DATA STRUCTURES LAB

LAB TASK-05

SUBMITTED BY:

Name: Ahmed Ali

Roll No: 22P-9318

INSTRUCTOR NAME: Sir Saood Sarwar

A DEPARTMENT OF COMPUTER SCIENCE

Q1 CODE:

```
#include<iostream>
using namespace std;

class node
{
	public:
		int data;
		node *prev;
		node *next;
};

void remove(node *head, node *del_nod)		//remove node from dll
{
	if(del_nod==nullptr)
	{
		return;
	}

	if(del_nod->prev!=nullptr)
	{
		del_nod->prev->next=del_nod->next;
	}

	if(del_nod->next!=nullptr)
	{
		del_nod->next->prev=del_nod->prev;
	}
```

```
        delete del_nod;
}

void remove_duplicates(node *head)     //remove duplicates from dll
{
        if(head==nullptr)
        {
                return;
        }
        node *current=head;
        while(current!=nullptr)
        {
                node *ptr=current->next;

                while(ptr!=nullptr)
                {
                        if(ptr->data==current->data)
                        {
                                node *del_nod=ptr;
                                ptr=ptr->next;
                                remove(head, del_nod);
                        }
                        else
                        {
                                ptr=ptr->next;
                        }
                }
```

```
                current=current->next;
        }
}

void display(node *head)
{
        node *current=head;
        while(current!=nullptr)
        {
                cout<<current->data;
                if(current->next!=nullptr)
                {
       cout<<" ";
                }
                current=current->next;
        }
        cout<<endl;
}

// Utility function to insert a new node at the end of the doubly linked list
node *insert_node(node* head, int data)
{
   node *new_node=new node{data};

        if(head==nullptr)
        {
                head=new_node;
   }
        else
```

```
        {
                node *tail=head;
                while(tail->next!=nullptr)
                {
                        tail=tail->next;
                }
                tail->next=new_node;
                new_node->prev=tail;
        }
        return head;
}

int main()
{
        node *head=nullptr;
        int nodes;
        int value;

        cout<<"Enter the number of nodes: "<<endl;
        cin>>nodes;

        cout<<"Enter the values for the nodes:"<<endl;
   for(int i=0; i<nodes; i++)
        {
      cin>>value;
      head=insert_node(head, value);
   }

        cout<<"Original list:"<<endl;
```

```
    display(head);

    remove_duplicates(head);

    cout<<"List after removing duplicates:"<<endl;
    display(head);

    node *current=head;
    while(current!=nullptr)
    {
        node *temp=current;
        current=current->next;
        delete temp;
    }
    return 0;
}
```

Output-01:



Q2 CODE:

```
#include<iostream>
using namespace std;

class node
{
	public:
		int data;
		node *next;
};

node *remove(node *head, int x)
{
	if(head==nullptr)
	{
		return nullptr;
	}
	node *curr=head;
   node *prev=nullptr;
	do
	{
		if(curr->data==x)
		{
			if(curr==head)
```

```
                {
                        if(head->next==head)    //deleting head
                        {
                                delete head;
                                return nullptr;
                        }
                        else
                        {
                                node *end=head;
                                while(end->next!=head)
                                {
                                        end=end->next;
                                }
                                head=head->next;
                                end->next=head;
                                delete curr;
                                return head;
                        }
                }
                else
                {
                        prev->next=curr->next;
                        delete curr; //removing nod that isnot head
                        return head;
                }
        }
        prev=curr;
        curr=curr->next;
}
```

```
        while(curr!=head);

   return head; //means target not found
}

void display(node *head)
{
        if(head==nullptr)
        {
                cout<<"List is empty"<<endl;
                return;
        }
        node *curr=head;
        do
        {
                cout<<curr->data<<" ";
                curr=curr->next;
        }
        while(curr!=head);
        cout<<endl;
}

node *create(int data)
{
        node *newnode=new node();
        newnode->data=data;
        newnode->next=nullptr;
        return newnode;
}
```

```
node *insert(node *head, int value)       //insert in end
{
        node *newnode=create(value);
        if(head==nullptr)
        {
                newnode->next=newnode;
                return newnode;
        }
        node *curr=head;
        while(curr->next!=head)
        {
                curr=curr->next;
        }
        curr->next=newnode;
        newnode->next=head;
        return head;
}

int main()
{
   node *head=nullptr;
        int n, value, target;

        cout<<"Enter the number of nodes in the circular linked list: "<<endl;
        cin>>n;

        cout<<"Enter values for nodes:"<<endl;
        for(int i=0; i<n; i++)
```

```
        {
                cin>>value;
                head=insert(head, value);
        }
        cout<<"Original list: ";
        display(head);

        cout<<"Enter value to delete: "<<endl;
        cin>>target;
        head=remove(head, target);
        cout<<"new list: ";
        display(head);
        return 0;
}
```

Output-02: