

Bridging the AR5-L6 & LinkerHand O6 to Isaac Sim

A Comprehensive Zero-to-Hero Masterclass: Isaac Sim Physics Fixes, MoveIt 2 Kinematics, and Dexterous Mimic Joints

Researchers: Ahmed & Shahd

Target Application: Autonomous Bimanual Soft-Body Slicing

1. Milestone 1: The Isaac Sim Physics Architecture

Before any Reinforcement Learning or ROS 2 integration can occur, the physical robot must be mathematically stable in the PhysX 5 solver. Our raw URDF and USD imports completely failed this requirement initially.

1.1 The Articulation Root Trap

⚠ THE SILENT DISCONNECT

When the robot was imported, it did not move coherently, or the joints moved like loose, unconstrained objects.

💡 THE FIX & THE WHY

PhysX requires a strict hierarchical tree to solve joint constraints simultaneously. If it doesn't know where the "root" of the tree is, it treats the robot as a collection of loose physics islands. We solved this by strictly applying the `PhysicsArticulationRoot` API to the top-level parent (`ar5_o6_left_combined`).

1.2 The "Exploding Robot" (Mass Ratios & Virtual Inertia)

Upon hitting "Play", the robot instantly exploded, vibrated violently, or disappeared from the screen (PhysX returning NaN velocities).

⚠ THE PHYSICS DIVERGENCE

The AR5 arm links are heavy (several kilograms). The LinkerHand O6 phalanx links are tiny (grams). The mass ratio exceeded 1:1000. When PhysX calculates momentum transfer across a joint between heavy and ultra-light bodies, the mathematical forces approach infinity.

🤖 SOLUTION: THE ARMATURE INJECTION


We injected `physxJoint:armature = 0.05` into all joints in the USD file. Armature acts as virtual inertia. It is like adding a heavy, invisible spinning flywheel to the motor shaft. It doesn't make the robot weigh more against gravity, but it makes the motor mathematically "sluggish" and stable, allowing the physics engine to calculate momentum smoothly.

1.3 The Collapsing Noodle (Position Drive)

Without motor stiffness, gravity pulled the heavy arm down, collapsing it into a pile instantly. We solved this by adding `drive:angular:physics:stiffness = 400.0` and `damping = 40.0` to act as a virtual Proportional-Derivative (PD) controller, giving the joints the "muscle tension" needed to hold their shape against gravity.

2. Milestone 2: MoveIt 2 Kinematics & The Spine

With the physical world stabilized, we built the Brain (MoveIt 2) and the Spinal Cord (ros2_control).



2.1 Strict C++ Parameter Types

⚠️ INVALIDPARAMETERTYPEEXCEPTION

ros2 launch crashed instantly because the Setup Assistant generated `joint_limits.yaml` with integer numbers (e.g., 1). ROS 2 expects double floats. We fixed this by manually appending `.0` to all values.

2.2 The Piano Player Trap (GripperCommand)

MoveIt couldn't load the `hand_controller` action server because it mistakenly classified our 6-DoF dexterous hand as a `GripperCommand`.

💡 ANALOGY: THE SINGLE LIGHT SWITCH

A `GripperCommand` is designed for simple 1-DoF parallel-jaw claws (open or close). MoveIt was trying to control a concert pianist's 6 independent fingers using a single light switch. We rewrote `moveit_controllers.yaml` to classify the hand as a full `FollowJointTrajectory` controller.

2.3 The Self-Collision Abort

When closing the fingers into a fist, the dense collision meshes mathematically intersected. MoveIt's default safety system detected this as a physical crash and aborted planning. We resolved this by injecting `<disable_collisions>` tags into the SRDF to programmatically allow the fingers to overlap.

3. Dexterous Hand Specifics: The Mimic Joint Mathematics

The most complex challenge was bridging the active motors and passive tendons.

3.1 The Mimic Joint Planning Crash

PASSIVE JOINT PLANNING IMPOSSIBILITY

A passive unpowered joint (`lh_thumb_ip`) was accidentally included in the active planning group. MoveIt's KDL IK solvers cannot mathematically generate independent trajectories for joints that are strictly slaved to other joints. We permanently deleted it from the SRDF planning group.

3.2 The Stiff Fingers Visual Bug

In RViz/Isaac Sim, the knuckles bent, but the tips remained perfectly straight like stiff wooden boards.

THE SOLUTION: ROS2_CONTROL.XACRO INJECTION

Our fake hardware (`mock_components/GenericSystem`) only calculated angles for active motors. The unpowered tip angles were never broadcast to `/joint_states`, so Isaac Sim assumed they were `0.0`. We injected mathematical mimic parameters (`<param name="mimic">`) directly into the hardware interface definition. This forced the mock manager to natively compute the unpowered tip angles in real-time.

XACRO MATHEMATICS INJECTION

```
<joint name="lh_index_dip">
  <param name="mimic">lh_index_mcp_pitch</param>
  <param name="multiplier">0.89</param>
  <state_interface name="position" />
</joint>
```

4. The Final Isaac Sim Action Graph

To solve the execution race condition in Isaac Sim (where the controller fired before the new ROS data arrived), we rewired the Action Graph sequentially:

Tick → **Subscribe Joint State (Exec Out)** → **Articulation Controller (Exec In)**.

Milestones 1 & 2 Completed • Ready for Milestone 3 (RL Environment)