

MILESTONES 1 & 2

Created: 2026-10-08 04:57:43

Bridging ROS 2 and Isaac Sim: Theory & Execution

The definitive fusion of theoretical robotics concepts and explicit, click-by-click instructions.

Researchers: Ahmed & Shahd | **Advisor:** Prof. Shan An | **Lab:** DEX-ROB Lab (Tianjin University)

Absolute Beginner's Masterclass: Bridging ROS 2 and Isaac Sim (Milestones 1 & 2) To train a Reinforcement Learning policy to slice tomatoes, we must connect three distinct systems: - **Isaac Sim (The Body):** The physical world that handles gravity, mass, and collisions. - **MoveIt 2 (The Brain):** The spatial planner that calculates how to move the arm without hitting a wall. - **ros2_control (The Spinal Cord):** The hardware manager that translates the Brain's path into raw motor signals. This manual explains the deep theoretical *why* behind every failure we encountered, followed immediately by the exact, click-by-click instructions on *how* to fix it by hand. ---

Phase 1: Stabilizing the Isaac Sim Physics Engine (Milestone 1)

A visually beautiful robot means nothing if the math engine cannot calculate its physics. If you press "Play" on the raw robot, it will explode. Here is why, and how to fix it.

1.1 The Disconnected Skeleton (Articulation Root)

CONCEPT: THE WHY & INTUITION

If you dump a pile of human bones on the floor, they are just loose objects. To make them a skeleton, you must define a spine. PhysX 5 requires a strict mathematical tree to solve joint constraints simultaneously. If it doesn't know where the "root" of the tree is, it treats the robot as disconnected physics islands, and the joints will fall apart or ignore commands.

STEP-BY-STEP ACTION: THE HOW

1. Open Isaac Sim. In the top-left **Stage** tree, click the absolute highest-level parent folder of the robot (`ar5_o6_left_combined`).
2. Look at the **Property** panel on the right side of the screen.
3. Click the **+++ Add** button at the top of the Property panel → **Physics** → **Articulation Root**.
4. **Crucial:* Expand the entire robot tree and ensure no other link has an Articulation Root. If one does, right-click it and delete it.

1.2 The "Exploding Robot" (Mass Ratios & Armature)

CONCEPT: THE WHY & INTUITION

The AR5 arm links are made of heavy metal (kilograms). The LinkerHand O6 fingers are tiny (grams). When the physics engine calculates the momentum transfer between these two extremes (a mass ratio of 1:1000), the math approaches infinity. It's like tying a tungsten bowling ball to a piece of cardboard and swinging it—the forces tear it apart instantly, resulting in an "explosion" of NaN (Not a Number) errors.

 STEP-BY-STEP ACTION: THE HOW

1. In the **Stage** tree, hold **Ctrl** and click to select **every single revolute joint** in the arm and the hand.
2. In the **Property** panel, click **+ Add** → **Physics** → **Joint**.
3. Scroll down to the newly added Physics parameters and find the **Armature** field.
4. Type **0.05** and press **Enter**. **(This acts like a heavy, invisible flywheel on the motor. It doesn't make the robot weigh more against gravity, but makes the math sluggish and stable).**

1.3 The Collapsing Noodle (Position Drive)

 CONCEPT: THE WHY & INTUITION

If you pass out, your muscles lose tension and you collapse under gravity. The robot's motors currently have no stiffness. We must add a virtual PD (Proportional-Derivative) controller to give the joints the rigidity to hold their shape.

 STEP-BY-STEP ACTION: THE HOW

1. With all joints still selected in the Stage tree, click **+ Add** → **Physics** → **Angular Drive**.
2. Scroll down to the Drive section in the Property panel.
3. Set **Stiffness** to **400.0** and **Damping** to **40.0**.
4. To stop the robot from falling endlessly through the floor, select the base link (**AR5_5_07L_W4C4A2_base**) and check **Disable Gravity** in the Property panel.

Phase 2: Fixing The Brain (MoveIt 2 Configuration - Milestone 2)

The MoveIt Setup Assistant is a great tool, but it generates files with fatal flaws. We must fix the brain before it can plan.

2.1 The Strict C++ Parameter Crash

CONCEPT: THE WHY & INTUITION

ROS 2 is built on strict C++. The Setup Assistant auto-generated our `joint_limits.yaml` with whole numbers (e.g., `max_velocity: 1`). C++ saw an integer but strictly expected a `double` (a floating-point decimal). It panicked and crashed the launch file instantly.

STEP-BY-STEP ACTION: THE HOW

1. Open `ahmed_moveit/config/joint_limits.yaml`.
2. Find every value that is a whole number (e.g., `max_velocity: 1`).
3. Change them to floating-point decimals (e.g., `max_velocity: 1.0`) for every joint.

2.2 Time Parameterization (Acceleration Limits)

CONCEPT: THE WHY & INTUITION

MoveIt's planner only finds a geometric line through space. To execute it, it must add time and velocity. To calculate velocity, it must know the maximum acceleration. If you don't provide acceleration limits, the math assumes the robot must instantly teleport to max speed, which fails.

STEP-BY-STEP ACTION: THE HOW

In `config/joint_limits.yaml`, under every joint, add these two exact lines:

```
has_acceleration_limits: true
max_acceleration: 5.0
```

2.3 The Piano Player Trap (GripperCommand)

CONCEPT: THE WHY & INTUITION

The Setup Assistant mistakenly classified our 6-finger hand as a `GripperCommand`. A `GripperCommand` is designed for simple arcade claws (open or close). It's like trying to control a concert pianist's 6 fingers using a single light switch. We must upgrade it to a full `FollowJointTrajectory` controller.

STEP-BY-STEP ACTION: THE HOW

1. Open `config/moveit_controllers.yaml`.
2. Locate the `hand_controller` block. Change it to perfectly match this:

```
- name: hand_controller
  action_ns: follow_joint_trajectory
  default: true
  type: FollowJointTrajectory
  joints:
    - lh_thumb_cmc_yaw
    - lh_thumb_cmc_pitch
    - lh_index_mcp_pitch
    - lh_middle_mcp_pitch
    - lh_ring_mcp_pitch
    - lh_pinky_mcp_pitch
```

Phase 3: The Dexterous Hand Mathematics

3.1 The Passive Joint Planning Crash

CONCEPT: THE WHY & INTUITION

The LinkerHand O6 has powered motors at the knuckles. The tip joints are unpowered and mechanically linked via tendons (modeled using the `tag`). MoveIt's IK solver cannot mathematically generate independent trajectories for passive joints that are strictly slaved to other joints. If a slaved joint is included in the planning group, MoveIt instantly aborts.

STEP-BY-STEP ACTION: THE HOW

1. Open `config/ar5_o6_left.srdf`.
2. Delete the line `from the` block.
3. Delete it from all `blocks` (like the "thumbs" pose).

3.2 The Stiff Fingers Visual Bug

CONCEPT: THE WHY & INTUITION

In RViz/Isaac Sim, the knuckles bent, but the tips remained perfectly straight. Why? We are using a fake software hardware interface (`mock_components/GenericSystem`) instead of real motors. By default, fake hardware only calculates angles for active motors. The unpowered tip angles were never calculated or broadcast to `/joint_states`, so Isaac Sim assumed they were `0.0`.

STEP-BY-STEP ACTION: THE HOW

1. Open `config/ar5_o6_left.ros2_control.xacro`.
2. Right before the closing `tag`, paste the mathematical formulas to force the mock hardware to calculate the tips:

```
lh_index_mcp_pitch
0.89
```

3.3 The Colcon Build Trap

TRAP & SILENT FAILURE

Even after saving your text files, ROS 2 will still crash. Why? Because `ros2 launch` executes files from the compiled `install/` directory, NOT the source folder you just edited!

 STEP-BY-STEP ACTION: THE HOW

1. Open a terminal in `ros2_ws` .
2. Remove Conda from `PATH`: `export PATH=$(echo $PATH | sed -e 's|/home/omen/miniforge3/bin:||')`
3. Build the package: `colcon build --packages-select ahmed_moveit`

Phase 4: Wiring the Bridge (Isaac Sim Action Graph)

The robot still won't move until the ROS 2 data is cleanly streamed into PhysX.

4.1 Preventing the Race Condition

CONCEPT: THE WHY & INTUITION

In visual scripting, white wires determine the strict flow of time. If you wire them in parallel, the Articulation Controller fires *before* the Subscriber has finished downloading the new ROS 2 data (a race condition).

STEP-BY-STEP ACTION: THE HOW

1. In Isaac Sim, go to **Window** → **Visual Scripting** → **Action Graph**.
2. Add three nodes: On Playback Tick , ROS2 Subscribe Joint State , Articulation Controller .
3. In the Subscriber node, set `topicName` to `/joint_states` . **You MUST** press Enter after typing, or Isaac Sim will secretly revert it.
4. In the Controller node, set the **Target** to the robot's Articulation Root.
5. Wire them sequentially: **Tick (Exec Out)** → **Subscriber (Exec In)** ... **Subscriber (Exec Out)** → **Controller (Exec In)**.