Product data sheet

Specifications



Charging station, EVlink Home, 3P +N, 1xT2, 11kW, 16A, with RDC-DD

EVH4S11N2

EVlink
EVlink Home
Charging station
3P + N
Wall-mounted
Standard
11 kW 16 A 230 V
1
Socket-outlet T2 front face
Set of 1

Complementary	
Rated supply voltage	230 V AC 5060 kHz
Earthing system	TT TN-S
Number of inputs	1
Input type	Auxiliary for dynamic energy management
Control type	Red 1 emergency stop, function: 1 push-button
Local signalling	Red, green and blue 1 LED, function: status indication
Protection type	Earth-leakage protection
Height	409 mm
Width	282 mm
Depth	148 mm
Net weight	5.6 kg
Colour	White (RAL 9003)
Standards	EN 61851 IEC 61851-1 EN 61000-6-1 EN 61000-6-3
Product certifications	CE UKCA
Maximum supply current	16 A

Environment

IP degree of protection	IP55 conforming to EN/IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Ambient air temperature for operation	-3050 °C
Ambient air temperature for storage	-4085 °C
Relative humidity	595 %
Operating altitude	02000 m

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Weight	5.152 kg
Package 1 Height	22.5 cm
Package 1 width	39.5 cm
Package 1 Length	49 cm
Unit Type of Package 2	P12
Number of Units in Package 2	16
Package 2 Weight	94.5 kg
Package 2 Height	104 cm
Package 2 width	80 cm
Package 2 Length	120 cm

Offer Sustainability

EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information