



Instance Attributes

- *description*
- *key*
- *name*
- *raw_value*
- *title*
- *type*
- *value*

Description

The XmpTag define an XMP tag.

Documentation

Instanciation

class pyexiv2.xmp.XmpTag(*key*, *value=None*, *_tag=None*)
An XMP tag.

Arguments:

- *key* The key of the tag in the dotted form *familyName.groupName.tagName* where *familyName = xmp*.
- *value* The value of the tag.

Here is a correspondance table between the XMP types and the possible python types the value of a tag may take:

- alt, bag, seq: list of the contained simple type
- lang alt: dict of (language-code: value)
- Boolean: boolean
- Colorant: *[not implemented yet]*
- Date: `datetime.date`, `datetime.datetime`
- Dimensions: *[not implemented yet]*
- Font: *[not implemented yet]*
- GPSCoordinate: `pyexiv2.utils.GPSCoordinate`
- Integer: `int`
- Locale: *[not implemented yet]*
- MIMEType: 2-tuple of strings
- Rational: `fractions.Fraction`
- Real: *[not implemented yet]*
- AgentName, ProperName, Text: unicode string
- Thumbnail: *[not implemented yet]*
- URI, URL: string
- XPath: *[not implemented yet]*

Attributes