

# REACTIVE STREAMS, linking REACTIVE APPLICATIONS to SPARK STREAMING

Luc Bourlier  
Typesafe Inc.



**SPARK SUMMIT EAST**  
DATA SCIENCE AND ENGINEERING AT SCALE  
FEBRUARY 16-18, 2016 NEW YORK CITY

# Agenda

- Back pressure
- Back pressure in Spark Streaming
- Reactive Application
- Reactive Streams
- Demo



# Back Pressure



SPARK SUMMIT EAST  
2016



# Back Pressure

- a slow consumer should slow down the producer
  - the producer applies pressure
  - the consumer applies back pressure
- the classic example: TCP



# Spark Streaming



SPARK SUMMIT EAST  
2016



# Spark Streaming



# Spark Streaming

## Congestion support in Spark 1.4

### Static rate limit

- `spark.streaming.receiver.maxRate`
- conservative
- difficult to find the right limit (depends on cluster size)
- one limit to all streams



# Spark Streaming

## Back pressure in Spark 1.5

### Dynamic rate limit

- rate estimator
  - estimates the number of element that can be safely processed by system during the batch interval
- rate sent to receivers
- rate limiter
  - relies on TCP to slow down producers





# Spark Streaming

## Rate estimator

- each BatchCompleted event contains
  - processing delay, scheduling delay
  - number of element in mini-batch
- the rate is (roughly)  $\text{elements} / \text{processingDelay}$
- but what about accumulated delay?




# Spark Streaming

## Rate estimator

### Proportional-Integral-Derivative

- P, I, D constants change convergence, overshooting and oscillations



[https://en.wikipedia.org/wiki/PID\\_controller](https://en.wikipedia.org/wiki/PID_controller)

# Spark Streaming

## Back pressure in Spark 1.5


- each input has its own estimator
- work with all stream receivers

including `KafkaDirectInputStream`

- configuration

- `spark.streaming.backpressure.enable` `true`
- `spark.streaming.backpressure.minRate` `R`





# Spark Streaming

## Limitations

- linearity assumption
- records with similar execution times
- TCP back pressure accumulates in the TCP channel




# Reactive Application



SPARK SUMMIT EAST  
2016



# Reactive Application



<http://www.reactivemanifesto.org>

# Reactive Application

Responsive	responds in a timely manner
Resilient	stays responsive in the face of failure
Elastic	stays responsive under varying workload
Message Driven	relies on asynchronous message-passing





# Reactive Streams



SPARK SUMMIT EAST  
2016



# Reactive Streams

- one tool to create reactive applications
- specification for back pressure interface to connect systems supporting back pressure in the JVM
  - small: 3 interfaces, 7 methods total
- subscriber controls rate by requesting elements from producers

<http://www.reactive-streams.org>



# End to end back pressure





SPARK SUMMIT EAST  
2016



# End to end back pressure

- Reactive application with reactive streams connector
  - ⇒ back pressure enabled
- Spark Streaming 1.5+
  - ⇒ back pressure enabled
- Reactive streams Spark Streaming receiver
  - ⇒ end to end back pressure






# Demo



SPARK SUMMIT EAST  
2016



# Demo



# What's Next?

- Last bit of API change (in Spark 2.0)  
[SPARK-10420](#)
- Publish the Reactive Streams Receiver





# THANK YOU.

[luc.bourlier@typesafe.com](mailto:luc.bourlier@typesafe.com)



**SPARK SUMMIT EAST**

DATA SCIENCE AND ENGINEERING AT SCALE  
FEBRUARY 16-18, 2016 NEW YORK CITY