

Scaling up data science applications

How switching to Spark improved performance, realizability and reduced cost

Kexin Xie
Director, Data Science

kexin.xie@salesforce.com
[@realstraw](#)


Yacov Salomon
VP, Data Science

ysalomon@salesforce.com


Fastest Growing Top 5 Enterprise Software Company

“Innovator of the Decade”

Forbes September 2016



Intelligent Customer Success Platform



salesforce DMP

Right Now

Boom

Coca-Cola



L'ORÉAL



LOWE'S



Mondelēz
International



Kellogg's



KEURIG

HERSHEY'S



LIONSGATE

Turner

DURACELL

ticketmaster®



pandora

NBCUniversal

Campbell's



SONY

EXTRADE®



CARmax



jetBlue

KIT ACE



The New York Times

Time Inc.

YAHOO!



HBO

2015-2016

Casper

BUSINESS
INSIDER



News Corp


Slate

match

Bloomberg

VICE

BBC



priceline.com

In an Internet Minute

4.1 million

videos viewed

342,000

apps downloaded

156 million

emails sent

452,000

tweets sent



40,000

hours listened

3.5 million

search queries

900,000

logins

\$751,522

spent online

Salesforce DMP is at Internet Scale

4.2 million

user match requests

1.6 million

page views




4.75 million

data capture events

700,000

Ad impressions





Marketers want to find more customers like their loyal customer

- AGE: MALE 22-30
- INCOME: \$250K+
- LUXURY AUTO SPENDER
- TECH-SAVVY
- SPORTS ENTHUSIAST
- BUSINESS EXEC
- UNIVERSITY/POST-GRADUATE

LOYAL CUSTOMER



REACH

Lookalikes

Email Newsletter Subscriber

18.5M

4.9M

Last Modified

Type

Category

Standard Segment / ID: rtwch9s8p



Vail Season Ticket holder

14.4M

3.1M

JetBlue SLC, Denver, Jackson Hole Fliers

5.7M

1.5M

Lonely Planet Adventure Traveler

14.4M

3.1M

Hiking Customers - TAM

93.2M

38.1M

Hiking Customers - High Propensity

28.3M

11.1M

Email Engaged - Hiking Customers

3.8M

987.1K

Last Modified
May 16, 2017

Type
Clusters

Category
Behavioral

Sub-Category
Attributes



Email Non-Engaged - Hiking Customers

3.8M

987.1K

Last Modified
May 18, 2017

Type
Clusters

Category
Behavioral

Sub-Category
Attributes


Help

Create lookalikes for Lonely Planet Adventure Traveler

Select a point to create lookalike segments. ?

Lookalike segments

you can zoom into the chart by selecting a chart area



	Reach	Similarity
	5,603	100%
	18,968	98%
	41,317	96%
	73,335	94%
	112,160	92%
	152,564	90%
	193,435	88%
	237,750	86%
	291,049	84%
	355,732	82%

Close

Model

Naive Bayes Framework

Model

Naive Bayes Framework

Feature Selection

Linear Discriminant Analysis

Model

Naive Bayes Framework

Feature Selection

Linear Discriminant Analysis

Science / Art

Correct for autocorrelation in feature space (paper pending)



Prepare

Train

Classify



Prepare

$O(n)$



Train


$O(n^2)$




Classify


$O(nm)$






jobs







StackOverflowException

Job Stuck

Slave Node Keeps Dying


Idle Slave Nodes

Out Of Memory

Code Complexity

Intermediate Result Serialization

Reality: Framework



Big I/O Cost

Code Complexity

Flexibility

Number of Features

Total Population

Segment Populations

Segment Population Overlap

```

public static class Map1 extends Mapper<LongWritable, Text, Text, NullWritable> {
    private Text segment = new Text();

    public void map(LongWritable key, Text value, Context context)
        throws IOException, InterruptedException {
        UserSegments userSegments = UserSegments.parse(value.toString());
        segment.set(userSegments.getUserId());
        context.write(userSegments, NullWritable.get());
    }
}


public static class Reduce1 extends Reducer<Text, NullWritable, Text, NullWritable> {
    public void reduce(Text key, Iterable<NullWritable> values, Context context)
        throws IOException, InterruptedException {
        context.write(key, NullWritable.get());
    }
}

public static class Map2 extends Mapper<LongWritable, Text, Text, NullWritable> {
    private final static IntWritable one = new IntWritable(1);

    public void map(LongWritable key, Text value, Context context)
        throws IOException, InterruptedException {
        context.write(NullWritable.get(), one);
    }
}

public static class Reduce2 extends Reducer<NullWritable, IntWritable, IntWritable, NullWritable> {
    public void reduce(NullWritable key, Iterable<IntWritable> values, Context context)
        throws IOException, InterruptedException {
        int sum = 0;
        for (IntWritable val : values) {
            sum += val.get();
        }
        context.write(new IntWritable(sum), NullWritable.get());
    }
}

```



```

public static class Map
    extends Mapper<LongWritable, Text, Text, LongWritable> {
    private final static LongWritable one = new LongWritable(1);
    private Text segment = new Text();

    public void map(LongWritable key, Text value, Context context)
        throws IOException, InterruptedException {
        String line = value.toString();
        UserSegments userSegments = UserSegments.parse(value.toString());
        for (String seg : userSegments.segments) {
            segment.set(seg);
            context.write(seg, one);
        }
    }
}

public static class Reduce
    extends Reducer<Text, LongWritable, Text, LongWritable> {

    public void reduce(Text key, Iterable<LongWritable> values, Context context)
        throws IOException, InterruptedException {
        int sum = 0;
        for (LongWritable val : values) {
            sum += val.get();
        }
        context.write(key, new LongWritable(sum));
    }
}

```

```

public static class Map
    extends Mapper<LongWritable, Text, NullWritable, LongWritable> {

    private final static LongWritable one = new LongWritable(1);

    public void map(LongWritable key, Text value, Context context)
        throws IOException, InterruptedException {
        context.write(NullWritable.get(), one);
    }
}

public static class Reduce
    extends Reducer<NullWritable, LongWritable, LongWritable, NullWritable> {

    public void reduce(NullWritable key, Iterable<LongWritable> values, Context context)
        throws IOException, InterruptedException {
        long sum = 0;
        for (LongWritable val : values) {
            sum += val.get();
        }
        context.write(new LongWritable(sum), NullWritable.get());
    }
}

```

```

public static class Map
    extends Mapper<LongWritable, Text, Text, LongWritable> {
    private final static LongWritable one = new LongWritable(1);
    private Text segmentPair = new Text();

    public void map(LongWritable key, Text value, Context context)
        throws IOException, InterruptedException {
        String line = value.toString();
        StringTokenizer tokenizer = new StringTokenizer(line);
        UserSegments userSegments = UserSegments.parse(value.toString());
        for (String seg1 : userSegments.segments) {
            for (String seg2 : userSegments.segments) {
                segmentPair.set(seg1 + "," + seg2);
                context.write(segmentPair, one);
            }
        }
    }
}

public static class Reduce extends
    Reducer<Text, LongWritable, Text, LongWritable> {

    public void reduce(Text key, Iterable<LongWritable> values, Context context)
        throws IOException, InterruptedException {
        int sum = 0;
        for (LongWritable val : values) {
            sum += val.get();
        }
        context.write(key, new LongWritable(sum));
    }
}

```

```
userSegments  
  .flatMap(_ .segments)  
  .distinct  
  .count
```

```
userSegments.count
```



```
userSegments  
  .flatMap(r => r.segments.map(_ -> 1L))  
  .reduceByKey(_ + _)
```

```
val userSegmentPairs = userSegments  
  .flatMap(r => r.segments.map(r.userId -> _))  
  
userSegmentPairs  
  .join(userSegmentPairs)  
  .map { case (_, (feat1, feat2)) => (feat1, feat2) -> 1L }  
  .reduceByKey(_ + _)
```



Reality: Data in many S3 prefixes/folders

```
val inputData = Seq(  
  "s3://my-bucket/some-path/prefix1/" ,  
  "s3://my-bucket/some-path/prefix2/" ,  
  "s3://my-bucket/some-path/prefix2/" ,  
  ...  
  "s3://my-bucket/some-path/prefix2000/" ,  
)
```


How about this?

```
val myRdd = inputData  
  .map(sc.textFile)  
  .reduceLeft(_ ++ _)
```

Or this?

```
val myRdd = sc.union(inputData.map(sc.textFile))
```

Solution

```
// get the s3 objects
val s3Objects = new AmazonS3Client ()
    .listObjects ("my-bucket", "some-path")
    .getObjectSummaries ()
    .map ( _.getKey () )
    .filter (hasPrefix1to2000)
// send them to slave nodes and retrieve content
val myRdd = sc
    .parallelize (Random.shuffle (s3Objects.toSeq), parallelismFactor)
    .flatMap ( key =>
        Source
            .fromInputStream (
                new AmazonS3Client () .getObjectForKey ("my-bucket", key)
                    .getObjectContent
            )
            .getLines
    )
```

Reality: Large Scale Overlap

```
val userSegmentPairs = userSegments
    .flatMap(r => r.segments.map(r.userId -> _))

userSegmentPairs
    .join(userSegmentPairs)
    .map { case (_, (feat1, feat2)) => (feat1, feat2) -> 1L }
    .reduceByKey(_ + _)
```

user1	a, b, c
user2	a, b, c
user3	a, b, c
user4	a, c
user5	a, c

user1	a
user1	b
user1	c
user2	a
user2	b
user2	c
user3	a
user3	b
user3	c
user4	a
user4	c
user5	a
user5	c

user1	a	b
user1	a	c
user1	b	c
user2	a	b
user2	a	c
user2	b	c
user3	a	b
user3	a	c
user3	b	c
user4	a	c
user5	a	c

1	a	b
1	a	c
1	b	c
1	a	b
1	a	c
1	b	c
1	a	b
1	a	c
1	b	c
1	a	c
1	a	c

a	b	3
a	c	5
b	c	3

user1	a, b, c
user2	a, b, c
user3	a, b, c
user4	a, c
user5	a, c

hash1	a, b, c	3
hash2	a, c	2

hash1	a	3
hash1	b	3
hash1	c	3
hash2	a	2
hash2	c	2

hash1	a	b	3
hash1	a	c	3
hash1	b	c	3
hash2	a	c	2

a	b	3
a	c	5
b	c	3

Solution

```
// Reduce the user space
val aggrUserSegmentPairs = userSegmentPairs
  .map(r => r.segments -> 1L)
  .reduceByKey(_ + _)
  .flatMap { case (segments, count) =>
    segments.map(s => (hash(segments), (segment, count)))
  }

aggrUserSegmentPairs
  .join(aggrUserSegmentPairs)
  .map { case (_, (seg1, count), (seg2, _)) =>
    (seg1, seg2) -> count
  }
  .reduceByKey(_ + _)
```

Reality: Perform Join on Skewed Data

user1	a
user2	b
user3	c
user4	d
user5	e

X

user1	one
user1	two
user1	three
user1	four
user1	five
user1	six
user3	seven
user3	eight
user4	nine
user5	ten

```
data1.join(data2)
```


Executor 1

user1	a
-------	---

Executor 2

user3	c
user4	d

Executor 3

user5	e
user2	b

user1	one
user1	two
user1	three
user1	four
user1	five
user1	six

user3	seven
user3	eight
user4	nine

user5	ten
-------	-----

Executor 1

user1	salt1	a
-------	-------	---

user1	salt1	one
user1	salt1	two

Executor 2


user1	salt2	a
-------	-------	---

user1	salt2	three
user1	salt2	four

Executor 3

user1	salt3	a
-------	-------	---

user1	salt3	five
user1	salt3	six



user2	b
user3	c
user4	d
user5	e

X

user3	seven
user3	eight
user4	nine
user5	ten

Solution

```
val topKeys = data2
    .mapValues (x => 1L)
    .reduceByKey (_ + _)
    .takeOrdered(10) (Ordering[(String, Long)].on(_._2).reverse)
    .toMap
    .keys

val topData1 = sc.broadcast (
    data1.filter(r => topKeys.contains(r._1)).collect.toMap
)

val bottomData1 = data1.filter(r => !topKeys.contains(r._1))

val topJoin = data2.flatMap { case (k, v2) =>
    topData1.value.get(k).map(v1 => k -> (v1, v2))
}

topJoin ++ bottomData1.join(data2)
```

Hadoop to Spark



Maintainable codebase

Smarter retrieval of data from S3



Clients with more than 2000 S3 prefixes/folders

Before: 5 hours

After: 20 minutes

Condensed overlap algorithm




100x faster and 10x less data for segment overlap

Hybrid join algorithm




Able to process joins for highly skewed data


Failure Rate



Performance



Cost



Thank You