



Smart Scalable Feature Reduction with Random Forests

Erik Erlandson
Red Hat, Inc.

Erik Erlandson

- Software Engineer
- Radanalytics.io community
- Apache Spark on OpenShift
- Intelligent Applications in the cloud

Talk

- Motivate Feature Reduction
- Random Forest Clustering
- T-Digest Feature Sketching
- RF Feature Reduction
- Example: Tox21 Assay Data

Features




Measurable
Properties!

Model
Training



Evaluation



Feature Reduction

Full Feature Set



Identify Useful
Features




Reduced
Feature Set



Feature Sets Can Be Very Large

hundreds
thousands
...
millions



Features Cost Resources

Memory



Network




Time




Disk

Energy



Features Inject Noise



**Model Training
Without Reduction**



**With Feature
Reduction**

Features Impact Model Size




Model Without Reduction



With Reduction

Representation & Transfer Learning




Random Forests

Leo Breiman (2001)

Ensemble of Decision Tree Models


Each tree trains on random subset of data

Each split considers random subset of features




Random Forest Clustering

Features



Leaf Node IDs



RF model

Leaf IDs



Cluster these !

2 Key Benefits of RF Clustering


RF Training ignores unhelpful features

**Features Used
by RF Model**




Full Feature Set

Data with a Joint Distribution in R^2



Data with Synthetic



RF Rules for Data (non-synthetic)


```
List((x2 <= -1.32), (x1 <= 0.87))
```

```
List((x1 > -1.37), (x2 > 1.03))
```


```
List((x2 <= 2.09), (x1 <= 0.87))
```

```
List((x1 <= 2.13), (x2 <= -1.32))
```

```
List((x2 <= -2.31), (x1 <= 0.87))
```



RF Rules in Feature Space



What Features Did the RF Use?

```
List((x2 <= -1.32), (x1 <= 0.87))
```


```
List((x1 > -1.37), (x2 > 1.03))
```

```
List((x2 <= 2.09), (x1 <= 0.87))
```

```
List((x1 <= 2.13), (x2 <= -1.32))
```



```
List((x2 <= -2.31), (x1 <= 0.87))
```

```
reduced = {"x1", "x2"}
```




T-Digest Sketches a Distribution

3.4
6.0
2.5
⋮



Inverse Transform Sampling



T-Digests Can Aggregate

Data in Spark

P1

P2

⋮

Pn

Map

t-digests



|+|

result



Sketching a Feature

```
feature.aggregate(TDigest.empty()) (  
    (td, x) => td + x,  
    (td1, td2) => td1 ++ td2  
)
```


Synthesizing Data from TDigests

```
def synthesize(tdVec: Vector[TDigest],  
               n: Int) = {  
  val tdVecBC = sc.broadcast(tdVec)  
  sc.parallelize(1 to n).map { _ =>  
    tdVecBC.value.map(_.sample)  
  }  
}
```

Random Forest Training Data

```
val fvSketches = sketchFV(trainFV)
val synthFV = synthesize(fvSketches, 48000)
val trainLab = trainFV.map(_.toLabeledPoint(1.0))
val synthLab = synthFV.map(_.toLabeledPoint(0.0))
val trainFR = trainLab ++ synthLab
```


Random Forest Feature Reduction



Tox21 Data Challenge

National Institute of Health (2014)

12 Toxicity Assays

12060 compounds + 647 hold-out

<https://tripod.nih.gov/tox21/challenge/index.jsp>



DeepTox

Johannes Kepler University Linz

Institute of Bioinformatics

<http://bioinf.jku.at/research/DeepTox/tox21.html>

[Mayr2016] Mayr, A., Klambauer, G., Unterthiner, T., & Hochreiter, S. (2016). DeepTox: Toxicity Prediction using Deep Learning. *Frontiers in Environmental Science*, **3**:80.

[Huang2016] Huang, R., Xia, M., Nguyen, D. T., Zhao, T., Sakamuru, S., Zhao, J., Shahane, S., Rossoshek, A., & Simeonov, A. (2016). Tox21Challenge to build predictive models of nuclear receptor and stress response pathways as mediated by exposure to environmental chemicals and drugs. *Frontiers in Environmental Science*, **3**:85.

Tox21 Data

I used these

801 Dense Features

272K Sparse Features

Each assay represented on a different subset

compound	NR.AhR	NR.AR	NR.AR.LBD	NR.Aromatase	...
NCGC00261900-01	0	1	NA	0	
NCGC00260869-01	0	1	NA	NA	.
NCGC00261776-01	1	1	0	NA	.
NCGC00261380-01	NA	0	NA	1	.
NCGC00261842-01	0	0	0	NA	
NCGC00261662-01	1	0	0	NA	
NCGC00261190-01	NA	0	0	NA	

Experiment

Train models on all 12 assays

Perform Random Forest Feature Reduction


Train similar models on reduced feature set

Compare models on each assay


85 of 801 Features Were Used

Features		Number trees used
RNCS		21
MRVSA7		20
VSAEstate2		19
VSAEstate3		18
slogPVSA8		18
VSAEstate0		17
slogPVSA6		16
RDFM29		12
slogPVSA3		12
RDFM30		12


Full vs Reduced (Logistic Reg)



Full vs Reduced (Boosted DTE)



Full vs Reduced (SVM)



Training Times

(times in seconds)	Full (801)	Reduced (85)
Logistic Regression	68.5	46.8
SVM	35.3	33.8
GB Tree Ensemble	247	65.0

Evaluation Times

(times in seconds)	Full (801)	Reduced (85)
Logistic Regression	32.1	3.88
SVM	0.59	0.23
GB Tree Ensemble	1.33	0.88



Thank You

Erik Erlandson

eje@redhat.com

[@manyangled](#)

<https://github.com/erikerlandson/feature-reduction-talk>