



LECTURE-4

Linear Data Structures

Linked Lists

CS202: Data Structures (Fall 2025)

Dr Maryam Abdulghafur, Momina Khan

Department of Computer Science, SBASSE

Quick Recap

AbstractDataType is mathematical model of a data structure.

OR

AbstractDataType is a **contract** of a data structure.

List ADT is an **ordered** collection of items

Agenda

- Dynamic Arrays (A hack for arrays being fixed size!)
- Linked Lists

List ADT

```
template <typename T>
```

```
class List {
```

```
Public:
```

```
    virtual void insert( const T& element) = 0;
```

```
    virtual void delete( const T& element) = 0;
```

```
    virtual Node * find( const T& element) = 0;
```

```
    virtual T get( int index) = 0;
```

```
    virtual bool isEmpty() = 0;
```

```
    virtual bool size() = 0;
```

List ADT

List ADT is agnostic of implementation!

We will now debate various possible implementations of a List ADT:

- Array
- Linked List

List (Array)

- Private data members?
- Implementation of the List functions?
- Can we run out of space in this list?

List (Array)

- Pros:
 - $O(1)$ indexing
 - Easy addition to end of list.
 - Memory locality: Contiguous memory and prefetching
- Cons:
 - Pre-allocated space: Rigid in size (used or unused)
 - Have to make space in array to add something to the middle.
 - we can run out of space. So we allocate **extra** space!