

---

# Bitmasks

---

---

# Agenda

---

- **Bitwise Operations**
  - **Iterative Complete Search**
-

# Bitwise Operations

---

NOT

~

OR

|

AND

&

XOR

^

SHR

>>

SHL

<<

# NOT ~

---

A = 12 (0000 0000 0000 1100)

~A = -13 (1111 1111 1111 0011)

NOT Truth Table

A	B
0	1
1	0

# OR |

---

A = 72 (0100 1000)

B = 184 (1011 1000)

A | B = 248 (1111 1000)

OR Truth Table

A	B	Y
0	0	0
0	1	1
1	0	1
1	1	1

# AND &

---

A = 72 (0100 1000)

B = 184 (1011 1000)

A & B = 8 (0000 1000)

AND Truth Table

A	B	Y
0	0	0
0	1	0
1	0	0
1	1	1

# XOR ^

---

A = 72 (0100 1000)

B = 184 (1011 1000)

A ^ B = 240 (1111 0000)

XOR Truth Table

A	B	Y
0	0	0
0	1	1
1	0	1
1	1	0

# SHR >>

---

It's considered as division by power of 2s

$$A = 5 \text{ (00101)}$$

$$A \gg 1 = 2 \text{ (00010)}$$

$$B = 12 \text{ (01100)}$$

$$B \gg 2 = 3 \text{ (00011)}$$

---



# SHL <<

---

It's considered as multiplying by power of 2s

$$A = 5 \text{ (00101)}$$

$$A << 1 = 10 \text{ (01010)}$$

$$B = 12 \text{ (001100)}$$

$$B << 2 = 48 \text{ (110000)}$$

---

# Bit Masking

---

- **32 int:** bits take indices from 0 to 31
- **64 int:** bits take indices from 0 to 63
- Check a bit

```
(mask >> bitIndx) & 1 == 1;
```

- Set a bit to one

```
mask = mask | (1 << bitIndx);
```

- Set a bit to zero

```
mask = mask & ~(1 << bitIndx);
```

---

# Bit Masking

---

- Flip a bit

```
mask = mask ^ (1 << bitIdx);
```

- Check if a number is odd `num & 1 == 1;`
- Xor tricks

$$x \oplus y \oplus x = y$$

`x ^ y` false when `(x == y)`

- Number of ones

```
builtin_popcount(num);
```

```
__builtin_popcountll(num);
```

---

# Example

---

- Given a positive integer, find if it is a power of two or not

```
int num, cnt=0;
```

```
cin>>num;
```

```
for(int i=0; (1LL<<i) <= num; i++){
```

```
    if((num>>i) & 1)
```

```
        cnt++;
```

```
}
```

```
cout<<((cnt==1) ? "YES" : "NO")<<'\n';
```

---

# Iterative Complete Search

---

- Complete search (aka brute force) is a method for solving a problem by traversing the entire search space in search of a solution.
  - A simple example for that is printing all numbers between 1 and 100 which is divisible by 5. The brute force solution is to try each number between 1 and 100 and check if it's divisible by 5 or not.
  - Sometimes, the search space is not that easy to be implemented in one single for loop.
-

# Problem

---

Let's say you have some **unique** numbers and a target sum, and you want to get the number of subsets that sum up to the target.

**Numbers:** 1 , 5 , 2 , 7 , 3 , 9

**Target:** 6

**Number of valid subsets:** 2

{1,5}, {1,2,3}

But how to generate all different subsets  
?




# Solution

---

- The solution is to implement a **powerset** of the numbers

```
for(int mask=0; mask < (1<<n); mask++){  
    int sum=0;  
    for(int i=0; i<n; i++){  
        if((mask>>i)&1)  
            sum+=nums[i];  
        if(sum==target)  
            counter++;  
    }  
}
```

{a,b,c}



# To Solve

---

- Raising Bacteria
  - Sum It Up
-