深圳市拓普微科技开发有限公司
SHENZHEN TOPWAY TECHNOLOGY CO.,LTD.

HKT070DTA-1C
LCD Module User Manual

Prepared by:	Checked by:	Approved by:
HeHongLiang		
Date: 2017-10-25	Date:	Date:

Rev.	Descriptions	Release Date
0.1	- Preliminary Draft release	2017-02-17
0.2	- Assemble Precaution	2017-10-25

Table of Content

1   Basic Specification

TOPWAY HKT070DTA-1C is a Smart TFT Module with 32bit MCU on board. Its graphics engine provides numbers of outstanding features. It supports TOPWAY TML 3.0 for preload and pre-design display interface that simplify the host operation and development time. Suitable for industry control, instrumentation, medical electronics, power electric equipment applications.

1.1   General Specification

|	
Screen Size(Diagonal) :	7"
Resolution :	800(RGB) x 480
Color Depth :	65k color (16bit)
Pixel Configuration :	RGB Stripe
Display Mode :	Transmissive / Normal White
Viewing Direction :	6H(*1)(gray-scale inverse) 12H(*2)
Outline Dimension :	200 x 125.0 x 30 (max)(mm) (see attached drawing for details)
Active Area :	154.08 x 85.92(mm)
Backlight :	LED
Command I/F:	RS-232C
Project Download:	by PC or by U-Drive (with OTG cable)
Operating Temperature :	-20 ~ +70°C
Storage Temperature :	-30 ~ +80°C

Note:
*1. For saturated color display content (eg. pure-red, pure-green, pure-blue, or pure-colors-combinations).
*2. For "color scales" display content.
*3. Color tone may slightly change by Temperature and Driving Condition.

1.2   Block Diagram

1.3 Terminal Function

RS232 Interface Terminal (K1)

Pin No.	Pin Name	I/O	Descriptions
1	VSS	P	Ground, (0V)
2	NC	--	No connection, leave open
3	RTS(BUSY)	O	Request To Send (could function as busy BUSY signal) (eg. to PC's RS232C pin8 <9pin D-connector>)
4	TX	O	Data output (eg. to PC's RS232C pin2 <9pin D-connector>)
5	RX	I	Data Input (eg. to PC's RS232C pin3 <9pin D-connector>)
6	VDD	P	Power supply (11.0 ~ 26.0)

Note.

*1. User data and commands transfer through this terminal.

*2. HOST using command hand shake during communication is suggested.

USB Interface Terminal (K2)

Pin No.	Pin Name	I/O	Descriptions
1	VUSB	P	Power supply (5V)
2	D-	I/O	USB DATA negative signal
3	D+	I/O	USB DATA positive signal
4	ID	I	USB_ID, 1:Client , 0:HOST
5	VSS	P	Ground, (0V)

Note.

*1. TML files and image files preload through this terminal

*2. Standard "USB-drive" functions provided

*3. During the files transfer, all others display functions will be suspended

2 Absolute Maximum Ratings

Items	Symbol	Min.	Max.	Unit	Condition
Power Supply voltage	V_{dd}	-0.3	26.0	V	
Operating Temperature	T_{OP}	-20	70	°C	No Condensation
Storage Temperature	T_{ST}	-30	80	°C	No Condensation

Note:

*1. This rating applies to all parts of the module and should not be exceeded.

*2. The operating temperature only guarantees operation of the circuit. The contrast, response speed, and the other specification related to electro-optical display quality is determined at the room temperature, T_{OP}=25℃

*3. Ambient temperature when the backlight is lit (reference value)

*4. Any Stresses exceeding the Absolute Maximum Ratings may cause substantial damage to the device. Functional operation of this device at other conditions beyond those listed in the specification is not implied and prolonged exposure to extreme conditions may affect device reliability.

3   Electrical Characteristics

3.1 DC Characteristics

VSS=0V, VDD=12V, T_{OP} =25°C

Items	Symbol	MIN.	TYP.	MAX.	Unit	Applicable Pin
Operating Voltage	V_{DD}	11.0	12.0	26.0	V	VDD
Rx Input MARK(1)	V_{RxM}	-3.0	-	-15.0	V	Rx
Rx Input SPACE(0)	V_{RXS}	+3.0	-	+15.0	V	Rx
Tx Output MARK(1)	V_{TXM}	-3.0	-	-15.0	V	Tx
Tx Output SPACE(0)	V_{TXS}	+3.0	-	+15.0	V	Tx
RTS Output High	V_{TXH}	-3.0	-	-15.0	V	RTS(BUSY)
RTS Output Low	V_{TXL}	+3.0	-	+15.0	V	RTS(BUSY)
Operating Current	I_{DD}	-	315	-	mA	VDD (*1)
Operating Current (USB)	I_{VUSB}	-	200	-	mA	VUSB
Battery Supply current	I_{BAT}	-	6	-	uA	(*2)

Note.

*1. Normal display condition.

*2. For Battery driving RTC application, RTC configuration should be enabled in the project global setting. And after install/re-install the battery, it should be power-on once for correct RTC configurations.

3.2 AC Characteristics

Items	JP1,JP7=close, JP2,JP8=open (factory default)	JP1,JP8=close, JP2,JP7=open	JP1,JP8= open, JP2,JP7= close	JP1,JP7= open, JP2,JP8= close
Start bit	1	1	1	1
Data bit	8	8	8	8
Parity bit	None	None	Even	Odd
Stop bit	1	1	1	1
Baud Rate(*1)	115200 bps	9600 bps	115200 bps	115200 bps

Items	JP3=close, JP4=open (factory default)	JP3= open, JP4=close
Serial Data Flow Control	busy	Xon/Xoff

Note.

*1.Baud Rate (1200bps～115200bps) could be adjusted by software.

URL: www.topwaydisplay.com
www.topwaysz.com
Document Name: HKT070DTA-1C-Manual-Rev0.2.doc
Page: 5 of   11

4 Function Specifications

4.1 Basic Operation Function Descriptions

HKT070DTA-1C

- TML files, Picture files, ICON files are stored inside FLASH memory area.
  They are preloaded to HKT070DTA-1C for stand alone interface use.
- Those files are preloaded via USB interface as an USB drive.
- All the interface flow and the touch response are based on the preloaded TML files
- VP variables memory is inside RAM area,
  it provides real time access via UART by the HOST or display onto the TFT by TML file.
- Custom Memories are inside FLASH memory area
  It can be accessed via UART interface by the HOST.
- Control and Draw Engine executes HOST commands and response respectively
- It also reports the real time Touch Key number to the HOST

4.2   Quick Start Guide

1.	Install TOPWAY Graphics Editor	
2.	Import pictures design UI flow	
3.	Download to Smart LCD	
4.	power on & display	
5.	Connect to host Show real time data	

4.3   Command Descriptions

Please refer to "SMART LCD Command Manual" .

5 Optical Characteristics

Item		Symbol	Condition	Min	Typ	Max	Unit	Remark
View Angles		θT	CR≧10	70	80	-	Degree	Note2,3
		θB		50	60	-		
		θL		70	80	-		
		θR		70	80	-		
Contrast Ratio		CR	θ=0°	700	900	-		Note 3
Response Time		T$_{ON}$	25℃	-	20	30	ms	Note 4
		T$_{OFF}$						
Chromaticity	**White**	x	Backlight is on	0.255	0.305	0.355		Note 1,5
		y		0.277	0.327	0.377		
	Red	x		0.534	0.584	0.634		Note 1,5
		y		0.300	0.350	0.400		
	Green	x		0.290	0.340	0.390		Note 1,5
		y		0.543	0.593	0.643		
	Blue	x		0.102	0.152	0.202		Note 1,5
		y		0.040	0.090	0.140		
Uniformity		U		75	80	-	%	Note 6
NTSC				45	50	-	%	Note 5
Luminance		L		-	500	-	cd/㎡	Note 7

1.IF= **40** mA, and the ambient temperature is 25℃.

2. The test systems refer to Note 1 and Note 2.

URL: www.topwaydisplay.com
        www.topwaysz.com
Document Name: HKT070DTA-1C-Manual-Rev0.2.doc
Page: 8 of 11

Note 1:
The data are measured after LEDs are turned on for 5 minutes. LCM displays full white. The brightness is the average value of 9 measured spots. Measurement equipment SR-3A (1°)
Measuring condition:
- Measuring surroundings: Dark room
- Measuring temperature: Ta=25℃.
- Adjust operating voltage to get optimum contrast at the center of the display.

Note 2:
The definition of viewing angle:
Refer to the graph below marked by θ and Φ

Note 3:
The definition of contrast ratio (Test LCM using SR-3A (1°)):

$$\text{Contrast Ratio(CR)} = \frac{\text{Luminance When LCD is at "White" state}}{\text{Luminance When LCD is at "Black" state}}$$

(Contrast Ratio is measured in optimum common electrode voltage)

Note 4:
Definition of Response time. (Test LCD using BM-7A(2°)):
The output signals of photo detector are measured when the input signals are changed from "black" to "white"(falling time)
and from "white" to "black"(rising time), respectively.
The response time is defined as
the time interval between the 10% and 90% of amplitudes.Refer to figure as below.

Note 5:
Definition of Color of CIE1931 Coordinate and NTSC Ratio.

Color gamut:

$$S= \frac{\text{Area of RGB triangle}}{\text{Area of NTSC triangle}} \times 100\%$$

Note 6:
The luminance uniformity is calculated by using following formula.
$\triangle Bp = Bp \text{ (Min.)} / Bp \text{ (Max.)} \times 100 \ (\%)$
Bp (Max.) = Maximum brightness in 9 measured spots
Bp (Min.) = Minimum brightness in 9 measured spots.

Note 7:
Measured the luminance of white state at center point

6 Precautions of using LCD Modules

Mounting
- Mounting must use holes arranged in four corners or four sides.
- The mounting structure so provide even force on to LCD module. Uneven force (ex. Twisted stress) should not applied to the module. And the case on which a module is mounted should have sufficient strength so that external force is not transmitted directly to the module.
- It is suggested to attach a transparent protective plate to the surface in order to protect the polarizer. It should have sufficient strength in order to the resist external force.
- The housing should adopt radiation structure to satisfy the temperature specification.
- Acetic acid type and chlorine type materials for the cover case are not desirable because the former generates corrosive gas of attacking the polarizer at high temperature and the latter causes circuit break by electro-chemical reaction.
- Do not touch, push or rub the exposed polarizers with glass, tweezers or anything harder than HB pencil lead. Never rub with dust clothes with chemical treatment. Do not touch the surface of polarizer for bare hand or greasy cloth.(Some cosmetics deteriorate the polarizer.)
- When the surface becomes dusty, please wipe gently with absorbent cotton or other soft materials like chamois soaks with petroleum benzine. Normal-hexane is recommended for cleaning the adhesives used to attach front / rear polarizers. Do not use acetone, toluene and alcohol because they cause chemical damage to the polarizer.
- Wipe off saliva or water drops as soon as possible. Their long time contact with polarizer

Operating
- The spike noise causes the mis-operation of circuits. It should be within the $\pm$200mV level (Over and under shoot voltage)
- Response time depends on the temperature.(In lower temperature, it becomes longer.)
- Brightness depends on the temperature. (In lower temperature, it becomes lower.) And in lower temperature, response time(required time that brightness is stable after turned on) becomes longer.
- Be careful for condensation at sudden temperature change. Condensation makes damage to polarizer or electrical contacted parts. And after fading condensation, smear or spot will occur.
- When fixed patterns are displayed for a long time, remnant image is likely to occur.
- Module has high frequency circuits. Sufficient suppression to the electromagnetic interference shall be done by system manufacturers. Grounding and shielding methods may be important to minimized the interference

Electrostatic Discharge Control
Since a module is composed of electronic circuits, it is not strong to electrostatic discharge. Make certain that treatment persons are connected to ground through wrist band etc. And don't touch interface pin directly.

Strong Light Exposure
Strong light exposure causes degradation of polarizer and color filter.

Storage
When storing modules as spares for a long time, the following precautions are necessary.
- Store them in a dark place. Do not expose the module to sunlight or fluorescent light. Keep the temperature between 5°C and 35°C at normal humidity.
- The polarizer surface should not come in contact with any other object. It is recommended that they be stored in the container in which they were shipped.

Protection Film
- When the protection film is peeled off, static electricity is generated between the film and polarizer. This should be peeled off slowly and carefully by people who are electrically grounded and with well ion-blown equipment or in such a condition, etc.
- The protection film is attached to the polarizer with a small amount of glue. If some stress is applied to rub the protection film against the polarizer during the time you peel off the film, the glue is apt tore main on the polarizer. Please carefully peel off the protection film without rubbing it against the polarizer.
- When the module with protection film attached is stored for a long time, sometimes there remains a very small amount of glue still on the polarizer after the protection film is peeled off.
- You can remove the glue easily. When the glue remains on the polarizer surface or its vestige is recognized, please wipe them off with absorbent cotton waste or other soft material like chamois soaked with normal-hexane.

Transportation
The LCD modules should be no falling and violent shocking during transportation, and also should avoid excessive press, water, damp and sunshine.

7   Assemble Precaution
安装注意事项

1. Customer front panel opening and thickness for TOPWAY display module should be fit for its assembling and sealing.
   - The suggested assemble gap(A) should be about 0.3~0.5mm on each side.
   - The suggested front panel thickness(B) should be about 1.5~4.0mm.

   客户面板开窗及厚度应适合 TOPWAY显示模块的安装及密封.
   - 建议每边安装间隙(A)约为0.3 ~0.5mm.
   - 建议面板厚度(B) 约为1.5~4.0mm.

2. A silicon sealing ring ships with TOPWAY display module. It should be in place before assembling to the front panel.
   TOPWAY显示模块上的硅胶密封圈在安装时确保嵌入到位.

3. It should fix the TOPWAY display module into the front panel with two steps.
   - Pre-fixing: Slightly tighten the screws on beam clamp in sequence as picture on the right side.
   - Final-fixing: Tighten the fixing screws on beam clamp in sequence as well with twist torque about 6~8kg.cm (*1) . and put the beam clamp straight.

   Note:
   *1. Over tightening might damage the shell and cause bad sealing result.

   应分两步将TOPWAY显示模块固定在面板上.
   - 预紧: 将卡扣螺钉按右图所示顺序稍加预紧.
   - 紧定:再次按顺序用**6~8kg.cm**扭力拧紧卡扣螺钉(*1),并注意卡扣置正无歪斜.

   注:
   *1. 过度拧紧可能会损坏外壳和影响密封效果.

4. It is strongly suggested to check the seal balancing of the four-side of the TOPWAY display module.
   - The suggested after assemble sealed gap(C) should be about 1.0~1.5mm.

   需注意检查TOPWAY显示模块四周在安装后保证平衡密封.
   - 建议组装后的密封间隙(C)约为1.0 ~1.5 mm.

5. Others:
   - Never hot plug the device! Power off the device before connect or disconnect the display module.
   - Don't forget to remove the cover protective film for normal operation.

   其它:
   - 视频线禁止带电插拔！ 在连接或断开显示模块之前先关闭设备电源.
   - 使用前请揭去保护膜.

深圳市拓普微科技开发有限公司
SHENZHEN TOPWAY TECHNOLOGY CO., LTD.

SMART LCD
Command V5.04
Manual

Prepared by:	Checked by:	Approved by:
liu		
Date: 2017-07-24	Date:	Date:

Rev.	Descriptions	Release Date
0.1	- Preliminary Draft release	2016-11-02
0.2	- Add a description of the 0xE8 command	2017-01-12
0.3	- 4.1, 0xE2, 0xE3 command name correction	2017-05-26
0.4	- Add a description of the 0xE7 command	2017-07-24

Table of Content

1   Basic Specifications

TOPWAY Smart LCD serial command is for real-time control and access. Host machine get the data which input through the Smart LCD interface or provide the data for display.

1.1 Hardware connection

Smart LCD serial UART interface are mainly base on RS232-C standard, by default, config as 8N1 115200bps.

2   Command Structure

2.1 Communication Packet Structure

Commands and Response Packet should be format as follow (host→module):

Seq	Code	Code type	Description
1	0xAA	Packet header	1byte
2	Cmd-code	Command code	1byte
3	Par-data	Parameter or Data	(*1)
:	:	-	-
:	:	-	-
:	:	-	-
N-3 th	0xCC	Packet tail	4byte
N-2 th	0x33		
N-1 th	0xC3		
N th	0x3C		

Note.
*1. Unless otherwise specified,
    all the multi-byte values, data, address' byte sequence are MSB first, LSB last.

2.2 Packet Acknowledgment

Packet Acknowledgment is two byte in ASCII (module → host):

Response	code	Description
Command (in packet) executed and wait for next Command	":>"	In ASCII (0x3a, 0x3e)
Command (in packet) error and wait for next Command	"!>"	In ASCII (0x21,0x3e)

Note.
*1. Packet Acknowledgement response to a valid packet only.

3   Data arrangement

3.1   Color Data Value Configuration

16 bit Color value

16 bit color value															
R4	R3	R2	R1	R0	G5	G4	G3	G2	G1	G0	B4	B3	B2	B1	B0
High byte (MSB)								Low byte (LSB)							
D7	D6	D5	D4	D3	D2	D1	D0	D7	D6	D5	D4	D3	D2	D1	D0

3.2   Data / Address / Page_ID / Location Values Configuration

64bit value

64 bit number value							
D63…D56	D55…D48	D47…D40	D39..D32	D31…D24	D23…D16	D15…D8	D7…D0
Byte7 (MSB)							Byte0 (LSB)
D7…D0	D7…D0	D7…D0	D7…D0	D7…D0	D7…D0	D7…D0	D7…D0

32bit value

32 bit number value			
D31…D24	D23…D16	D15…D8	D7…D0
Byte3 (MSB)			Byte0 (LSB)
D7…D0	D7…D0	D7…D0	D7…D0

16bit value

16 bit number value	
D15…D8	D7…D0
High Byte (MSB)	Low Byte (LSB)
D7…D0	D7…D0

4 Command Descriptions

4.1 Command table

Functions	Name	Code	Description
Config/ Status Functions	hand_shake	0x30	Read a Hand Shake
	read_version	0x31	Read firmware version
	read_pg_id	0x32	Read Current page ID
	touch_response	0x72/0x73/ 0x77/0x78/ 0x79	see also set_sys_config
	set_sys_config	0xE0	System parameter configuration and Baud Rate
	sel_project	0xE1	Specify operating project folder
	touch_calib	0xE4	Touch panel calibration
	screen_saver	0x5E	Screen saver (backlight dim down time out)
	backlight_ctrl	0x5F	backlight brightness control (64 levels)
	buzzer_touch_sound	0x79	buzzer enable time length (in 10ms step)
	buzzer_ctrl	0x7A	Buzzer control
	Flash_write	0x90	Write data to the flash
	Flash_read	0x91	Read data from the flash
	RTC_read	0x9B	Read the RTC values
	RTC_set	0x9C	Set the RTC
	USR_bin_read	0x93	Read data from the USR_bin
	U_drv_format	0xE2	Format the U_drv
	U_drv_unlock	0xE3	Unlock the U_drv with pre-stored password
Display Control Functions	disp_page	0x70	Display a pre-stored TML file (page)
	set_element_fg	0x7E	Set the foreground color of STR, N16, N32 or N64
	set_element_bg	0x7F	Set the background color of STR, N16, N32 or N64
	set_codepage	0xE7	Sets country character set and code-page character set
	suspend_vp_fresh	0xE8	Set the screen to pause the refresh and deactivate the touchkey or release the pause to refresh and enable the touchkey
VP Functions	Successive_write	0x82	Write successive value to VP_N16, VP_N32, VP_N64
	Successive_read	0x83	Read successive value from VP_N16, VP_N32, VP_N64
	BP1_write	0x4B	Write bit-map (1bpp) data to VP_BP1
	BP1_write_comp	0x4C	Write compressed bit-map (1bpp) data to VP_BP1
	G16_write	0x4D	Write 16bit (signed integer) graphic array to VP_G16
	G16_write_rotate	0x4E	Rotate the VP_G16 array data inside the module and write a 16bit (signed integer) value into end-of-array
	System Register Write	0x3B	Write System Register
	System Register Read	0x3C	Read System Register
	STR_write	0x42	Write string to VP_STR
	STR_read	0x43	Read string form VP_STR
	STR_fill	0x46	Fill strings to the VP_STR
	N16_write	0x3d	Write 16bit (signed integer) value to VP_N16
	N16_read	0x3e	Read 16bit (signed integer) value from VP_N16
	N16_fill	0x3f	Fill numbers to the VP_N16
	N32_write	0x44	Write 32bit (signed integer) value to VP_N32
	N32_read	0x45	Read 32bit (signed integer) value from VP_N32
	N32_fill	0x47	Fill numbers to the VP_N32
	N64_write	0x48	Write 64bit (signed integer) value to VP_N64
	N64_read	0x49	Read 64bit (signed integer) value from VP_N64
	N64_fill	0x4A	Fill numbers to the VP_N64

4.2 Config/ Status Function Commands Details

4.2.1 hand_shake (0x30)

seq	Cmd-code / Par-data	Descriptions
1	0x30	Read a Hand Shake

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

Response code:

Seq.	Content	Byte in Hex	Descriptions
1st	Header	0xAA	Communication packet header
2nd	Command	0x30	Command executed
3rd	"T"	0x54	"Topway HMT Ready\0" in ASCII
4th	"o"	0x6f	
5th	"P"	0x70	
6th	"w"	0x77	
7th	"a"	0x61	
8th	"y"	0x79	
9th	" "	0x20	
10th	"H"	0x48	
11th	"M"	0x4d	
12th	"T"	0x54	
13th	" "	0x20	
14th	"R"	0x52	
15th	"e"	0x65	
16th	"a"	0x61	
17th	"d"	0x64	
18th	"y"	0x79	'\0'(0x00): string end mark
19th	\0	0x00	
20th	Tail	0xCC	Communication packet tail
21st		0x33	
22nd		0xC3	
23rd		0x3C	

Note.
*1. The Response code with communication packet format (see Communication Packet Structure Section for details)

4.2.2 read_version (0x31)

Seq	Cmd-code / Par-data	Descriptions
1	0x31	Read firmware version

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

Response code:

Seq.	Content	Byte in Hex	Descriptions
1st	Header	0xAA	Communication packet header
2nd	Command	0x31	Command executed
3rd	"1"	0x31	"1.06\0" in ASCII
4th	"."	0x2e	Where firmware version is V1.06(example)
5th	"0"	0x30	
6th	"6"	0x36	
7th	\0	0x00	'\0'(0x00): string end mark
8th	Tail	0xCC	Communication packet tail
9th		0x33	
10th		0xC3	
11th		0x3C	

Note.
*1. The Response code with communication packet format (see Communication Packet Structure Section for details)

4.2.3　read_pg_id (0x32)

Seq	Cmd-code / Par-data	Descriptions
1	0x32	Read Current page ID

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

Response code:

Seq.	Content	Byte in Hex	Descriptions
1st	Header	0xAA	Communication packet header
2nd	Command	0x32	Command executed
3rd	Page ID	Page_IDh	Current Page ID in 16bit binary value
4th		Page_IDl	
5th	Tail	0xCC	Communication packet tail
6th		0x33	
7th		0xC3	
8th		0x3C	

Note.
*1. The Response code with communication packet format (see Communication Packet Structure Section for details)

4.2.4　touch_response (0x72/ 0x73/ 0x77/ 0x78/ 0x79)

seq	Cmd-code / Par-data	Descriptions
1	--	Use set_sys_config to config the functions

Touch Release Coordinate Response code (0x72):

Seq.	Content	Byte in Hex	Descriptions
1st	Header	0xAA	Communication packet header
2nd	Command	0x72	Touched release Coordinate
3rd	X coordinate	Xh	Coordinate in 16bit binary value
4th		Xl	X = horizontal coordinate
5th	Y coordinate	Yh	Y = vertical coordinate
6th		Yl	
7th	Tail	0xCC	Communication packet tail
8th		0x33	
9th		0xC3	
10th		0x3C	

Note.
*1. The Response code with communication packet format (see Communication Packet Structure Section for details)

Touch Down Coordinate Response code (0x73):

Seq.	Content	Byte in Hex	Descriptions
1st	Header	0xAA	Communication packet header
2nd	Command	0x73	Touched down Coordinate
3rd	X coordinate	Xh	Coordinate in 16bit binary value
4th		Xl	X = horizontal coordinate
5th	Y coordinate	Yh	Y = vertical coordinate
6th		Yl	
7th	Tail	0xCC	Communication packet tail
8th		0x33	
9th		0xC3	
10th		0x3C	

Note.
*1. The Response code with communication packet format (see Communication Packet Structure Section for details)

Touch Key ID Response code (0x78):

Seq.	Content	Byte in Hex	Descriptions
1st	Header	0xAA	Communication packet header
2nd	Command	0x78	Touched release Key_ID defined by TOPWAY TML Graphic Editor will be response to host
3rd	Page_ID	Page_IDh	Page_ID = the touch key in page(16bit binary value)
4th		Page_IDl	
5th	Y coordinate	Key_ID	Key_ID (8bit binary value)
6th	Tail	0xCC	Communication packet tail
7th		0x33	
8th		0xC3	
9th		0x3C	

Note.
*1. The Response code with communication packet format (see Communication Packet Structure Section for details)

Touch Key ID Response code (0x79):

Seq.	Content	Byte in Hex	Descriptions
1st	Header	0xAA	Communication packet header
2nd	Command	0x79	Touched down Key_ID defined by TOPWAY TML Graphic Editor will be response to host
3rd	Page_ID	Page_IDh	Page_ID = the touch key in page(16bit binary value)
4th		Page_IDl	
5th	Y coordinate	Key_ID	Key_ID (8bit binary value)
6th	Tail	0xCC	Communication packet tail
7th		0x33	
8th		0xC3	
9th		0x3C	

Note.
*1. The Response code with communication packet format (see Communication Packet Structure Section for details)

Touch Key VP_ADD+VP_Value Response code (0x77):

Seq.	Content	Byte in Hex	Descriptions
1st	Header	0xAA	Communication packet header
2nd	Command	0x77	Touch Key VP_ADD+VP_Value Response code
3rd	VP_ADD	Addr3（MSB）	VP Address
4th		Addr2	0x080000 ~ 0x08FFFF:VP_N16 Address
5th		Addr1	0x020000 ~ 0x02FFFF:VP_N32 Address
6th		Addr0(LSB)	0x030000 ~ 0x03FFFF:VP_N64 Address
			0x000000 ~ 0x01FFFF:VP_STR Address
7th	Data	:	No.of byte
:		:	VP_N16: 2byte
:		:	VP_N32: 4byte
:		:	VP_N64: 8byte
:		:	VP_STR: string (with end mark ("\0'(0x00)))
:	Tail	0xCC	Communication packet tail
:		0x33	
:		0xC3	
:		0x3C	

Note.
*1. The Response code with communication packet format (see Communication Packet Structure Section for details)

4.2.5 set_sys_config (0xE0)

seq	Cmd-code / Par-data	Descriptions
1	0xE0	Baud Rate and system parameter configuration
2	0x55	
3	0xAA	
4	0x5A	
5	0xA5	
6	Baud_Set	Baudrate Set: 0x00 = 1200bps 0x01 = 2400bps 0x02 = 4800bps 0x03 = 9600bps 0x04 = 19200bps 0x05 = 38400bps 0x06 = 57600bps 0x07 = 115200bps
7	sys_par1	Bit7 = 0: Touch panel function disable Bit7 = 1: Touch panel functions enable (*3)(default) Bit[1..0]: Touch actions configuration (*2, *3)
8	0x00	Reserved

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)
*2. Touch panel configuration:

Sys_par1 Bit7	Sys_par1 Bit1	Sys_par1 Bit0	Response To host	Descriptions
0	0	0	Null	Not touch panel functions
1	0	1	Coordinates	Touch down Coordinate will be response to host
1	1	0	Coordinates	Touch release Coordinate will be response to host
1	1	1	Key ID	Touch Key_ID defined by TOPWAY TML Graphic Editor will be response to host

*3. see set_touch section for response code

4.2.6 sel_project (0xE1)

seq	Cmd-code / Par-data	Descriptions
1	0xE1	Select project folder
2	Prj_ID	0~9, project ID 0: System execute the default project "THMT" 1~9: System execute the project "THMT01"~"THMT09"

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

4.2.7 touch_calib (0xE4)

seq	Cmd-code / Par-data	Descriptions
1	0xE4	Touch panel calibration
2	0x55	
3	0xAA	
4	0x5A	
5	0xA5	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)
*2. Keep pressing the touch panel during power on, could also trigger the touch_calib function

4.2.8 screen_saver (0x5E)

seq	Cmd-code / Par-data	Descriptions
1	0x5E	Screen saver
2	Time1h	time out time in seconds, range: 0x0000 ~ 0xffff
3	Time1l	(0x0000: disable screen saver function) (*2)
4	PWM_LE	PWM_LE = 0 ~ 0x3F (default 0x19 in dim down), the backlight dimmed level in screen saving mode (*2) Screensavers brightness can not be greater than the backlight brightness.

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)
*2. default value defined by TML graphic editor configuration

4.2.9 backlight_ctrl (0x5F)

seq	Cmd-code / Par-data	Descriptions
1	0x5F	backlight brightness control
2	PWM_LE	PWM_LE=0x00 ~ 0x3F (*2)

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)
*2. default value defined by TML graphic editor configuration

4.2.10 buzzer_touch_sound (0x79)

seq	Cmd-code / Par-data	Descriptions
1	0x79	buzzer touch sound control
2	Time	Sounding time length (in 10ms), range 0x00~0x3F 0x00= disable (*2)

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)
*2. default value defined by TML graphic editor configuration

4.2.11 buzzer_ ctrl (0x7A)

seq	Cmd-code / Par-data	Descriptions
1	0x7A	Buzzer control
2	Loop count	Loop count, Range: 0x01 ~ 0xFF. 0xFF = buzzer infinite loop
3	T1	Buzzer play time 1 Range: 0x00 ~ 0xFF (0~25.5s)(unit 100ms)
4	T2	Buzzer play time 2 Range: 0x00 ~ 0xFF (0~25.5s)(unit 100ms)
5	Freq1	T1 time Buzzer frequency, Unit 100 Hz Ranges: 0x05 ~ 0x32 (500Hz ~ 5KHz) 0x00 = T1 time period buzzer turn off
6	Freq2	T2 time Buzzer frequency, Unit 100 Hz Ranges: 0x05 ~ 0x32 (500Hz ~ 5KHz) 0x00 = T1 time period buzzer turn off

Note:
    1. The buzzer sound time is (T1 + T2)*100ms

4.2.12 Flash_write (0x90)

seq	Cmd-code / Par-data	Descriptions
1	0x90	Write data to the flash at specified address
2	Address3(MSB)	the specified start address to write
3	Address2	Address range =0x00000 ~ 0x03FFFF
4	Address1	
5	Address0(LSB)	
6	Data_Lengthh	The no. of data byte to write.
7	Data_Lengthl	Length =0x0001 ~ 0x0400
8	Data	data to write.
:	:	
:	:	
:	:	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

4.2.13 Flash_read (0x91)

seq	Cmd-code / Par-data	Descriptions
1	0x91	Read data from the flash at specified address
2	Address3(MSB)	the specified start address to write
3	Address2	Address range =0x00000 ~ 0x03FFFF
4	Address1	
5	Address0(LSB)	
6	Data_Lengthh	The no. of data byte to read
7	Data_Lengthl	Length =0x0001 ~ 0x0400

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

Response code:

Seq.	Content	Byte in Hex	Descriptions
1st	Header	0xAA	Communication packet header
2nd	Command	0x91	Command executed
3rd	Data	data	Read back data
:		:	
:		:	
:	Tail	0xCC	Communication packet tail
:		0x33	
:		0xC3	
:		0x3C	

Note.
*1. The Response code with communication packet format (see Communication Packet Structure Section for details)

4.2.14 RTC_read (0x9B)

seq	Cmd-code / Par-data	Descriptions
1	0x9B	Read the current RTC value

Response code:

Seq.	Content	Byte in Hex	Descriptions
1st	Header	0xAA	Communication packet header
2nd	Command	0x9B	Command executed
3rd	Date	Year	Year: 00~99 (00=year 2000) (8bit binary value)
4th		Month	Month: 01~12 (8bit binary value)
5th		Day	Day: 01~31 (8bit binary value)
6th	Time	Hour	Hour 00~23 (24hr format)(8bit binary value)
7th		Minute	Minutes 00~59 (8bit binary value)
8th		Second	Second 00~59 (8bit binary value)
9th	Tail	0xCC	Communication packet tail
10th		0x33	
11th		0xC3	
12th		0x3C	

Note.
*1. The Response code with communication packet format (see Communication Packet Structure Section for details)

4.2.15 RTC_set (0x9C)

seq	Cmd-code / Par-data	Descriptions
1	0x9C	Set the RTC
2	Year	Year = 00~99(2000 ~ 2099)
3	Month	Month = 00~12
4	Date	Date = 00~31
5	Hour	Hour = 00~23
6	Minute	Minute = 00~59
7	Second	Second = 00~59

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

4.2.16 USR_bin_read (0x93)

seq	Cmd-code / Par-data	Descriptions
1	0x93	Read USR_bin data from the flash at specified address
2	Address3(MSB)	the specified start address to write
3	Address2	Address range = 0x00000 ~ 0x03FFFF
4	Address1	
5	Address0(LSB)	
6	Data_Lengthh	The no. of data byte to read
7	Data_Lengthl	Length = 0x0001 ~ 0x0400

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

Response code:

Seq.	Content	Byte in Hex	Descriptions
1st	Header	0xAA	Communication packet header
2nd	Command	0x93	Command executed
3rd	Data	data	Read back data
:		:	
:		:	
:	Tail	0xCC	Communication packet tail
:		0x33	
:		0xC3	
:		0x3C	

Note.
*1. The Response code with communication packet format (see Communication Packet Structure Section for details)

4.2.17 U_drv_format (0xE2)

seq	Cmd-code / Par-data	Descriptions
1	0xE2	Format the USB drive.
2	0x55	All the files (include the security lock file) will be erased.
3	0xAA	
4	0x5A	
5	0xA5	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

4.2.18 U_drv_unlock (0xE3)

seq	Cmd-code / Par-data	Descriptions
1	0xE3	Unlock the USB drive of file read/write with pre-stored password.
2	PW	PW: password in ASCII
:	:	Length = 127max.
:	:	
:	'\0'	'\0'(0x00): string end mark

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

4.3 Display Control Function Commands Details

4.3.1 disp_page (0x70)

seq	Cmd-code / Par-data	Descriptions
1	0x70	Display a pre-stored TML file(page)
2	Page_IDh	Page_ID = 0~999
3	Page_IDl	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

4.3.2 set_element_fg (0x7E)

Seq	Cmd-code / Par-data	Descriptions
1	0x7E	Set foreground colors of the STR, N16, N32 or N64
2	Element	0x00 = STR; 0x01 = N16, N32, N64
3	Page_IDh	Page_ID = 0~999
4	Page_IDl	
5	Element_ID	VP_STR = 0~127; N16, N32, N64 = 0~119
6	0x00	Reserve
7	FGh	Foreground color(0~0xffff)
8	FGl	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

4.3.3 set_element_bg (0x7F)

Seq	Cmd-code / Par-data	Descriptions
1	0x7F	Set background color of the STR, N16, N32 or N64
2	Element	0x00 = STR; 0x01 = N16, N32, N64
3	Page_IDh	Page_ID = 0~999
4	Page_IDl	
5	Element_ID	VP_STR = 0~127, N16, N32, N64 = 0~119
6	Mode	0x00: non transparent; 0x01 : transparent
7	BGh	Background color(0 ~ 0xffff)
8	BGl	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

4.3.4 set_codepage (0xE7)

Seq	Cmd-code / Par-data	Descriptions
1	0xE7	Sets country character set and code-page character set
2	Country	1 ~ 11, country character set
3	Codepage	1 ~ 22, code-page character set

Note.
*1. Country and CodePage table

Country Code	Descriptions	Code Page	Descriptions
1	USA	1	437 (OEM – United States)
2	France	2	737 (OEM – Greek 437G)
3	Germany	3	852 (OEM – Latin II)
4	United Kingdom	4	860 (OEM – Portuguese)
5	Demark I	5	863 (OEM – Canadian French)
6	Demark II	6	865 (OEM – Nordic)
7	Sweden	7	866 (OEM – Russian)
8	Italy	8	874 (ANSI/OEM – Thai)
9	Spain	9	932 (ANSI/OEM – Japanese Shift-JIS)
10	Japan	10	1250 (ANSI - Central Europe)
11	Norway	11	1251 (ANSI – Cyrillic)
--	--	12	1252 (ANSI – Latin I)
--	--	13	1253 (ANSI – Greek)
--	--	14	1254 (ANSI – Turkish)
--	--	15	1255 (ANSI – Hebrew)
--	--	16	1256 (ANSI – Arabic)
--	--	17	1257 (ANSI – Baltic)
--	--	18	1258 (ANSI – Viet Nam)
--	--	19	GB2312
--	--	20	GBK
--	--	21	EUC_KR
--	--	22	Big5

4.3.5   suspend_vp_refresh (0xE8)

Seq	Cmd-code / Par-data	Descriptions
1	0xE8	Set the screen to pause the refresh and deactivate the touchkey or release the pause to refresh and enable the touchkey
2	55	
3	AA	
4	5A	
5	A5	
6	Mode	0x00: release the pause to refresh and enable the touchkey 0x01: pause the refresh and deactivate the touchkey

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

4.4 VP Function Commands Details

4.4.1   Successive_write (0x82)

Seq	Cmd-code / Par-data	Descriptions
1	0x82	Write successive value to VP_N16, VP_N32, VP_N64
2	Addr3(MSB)	VP_N16 Address = 0x080000 ~ 0x08FFFF (should be aligned every 2 byte)
3	Addr2	VP_N32 Address = 0x020000 ~ 0x02FFFF (should be aligned every 4 byte)
4	Addr1	
5	Addr0(LSB)	VP_N64 Address = 0x030000 ~ 0x03FFFF (should be aligned every 8 byte)
6	Length	The number of data to write (Length = 1~255)
7	Data 1(MSB)	the value to write
8	Data 2	No. of byte of Data:
9	Data 3	VP_N16 = Length *2,
⋮ ⋮	⋮ Data n(LSB)	VP_N32 = Length *4, VP_N64 = Length *8,

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

4.4.2   Successive_read (0x83)

Seq	Cmd-code / Par-data	Descriptions
1	0x83	Read successive value to VP_N16, VP_N32, VP_N64
2	Addr3(MSB)	VP_N16 Address = 0x080000 ~ 0x08FFFF (should be aligned every 2 byte)
3	Addr2	VP_N32 Address = 0x020000 ~ 0x02FFFF (should be aligned every 4 byte)
4	Addr1	
5	Addr0(LSB)	VP_N64 Address = 0x030000 ~ 0x03FFFF (should be aligned every 8 byte)
6	Length	The number of data to write (Length = 1 ~ 255)

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

Response code:

Seq.	Content	Byte in Hex	Descriptions
1st	Header	0xAA	Communication packet header
2nd	Command	0x83	Command executed
3rd	VP_ADD	Addr3(MSB）	VP Address
4th		Addr2	0x080000 ~ 0x08FFFF:VP_N16 Address
5th		Addr1	0x020000 ~ 0x02FFFF:VP_N32 Address
6th		Addr0(LSB)	0x030000 ~ 0x03FFFF:VP_N64 Address
7rd	Length	NO.	No. of data
8rd	Data	Data n(MSB)	No. of byte of Data:
⋮		⋮	VP_N16 = Length *2,
⋮		⋮	VP_N32 = Length *4,
(n-1)th		Data1	VP_N64 = Length *8,
nth		Data0(LSB)	
(n+1)th	Tail	0xCC	Communication packet tail
(n+2)th		0x33	
(n+3)th		0xC3	
(n+4)th		0x3C	

Note.
*1. The Response code with communication packet format (see Communication Packet Structure Section for details)

4.4.3 BP1_write (0x4B)

Seq	Cmd-code / Par-data	Descriptions
1	0x4B	Write raw bit-map data to the VP_BP1
2	Addr3(MSB)	VP_BP1 Address = 0x040000 ~ 0x05FFFF
3	Addr2	
4	Addr1	
5	Addr0(LSB)	
6	Length3(MSB)	the number of data
7	Length2	Length = 1 ~ 98304
8	Length1	
9	Length0(LSB)	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)
*2. After the above command issued, it follow with the raw data byte with out communication packet structure.
*3. over all command flow

HOST	Flow	module
BP1_write Command (in communication packet structure)	→	Instruct to wait for data….
Raw 1bpp image data (without communication packet structure)	→	Store the data into VP_BP1
	←	Response code ":>" in ASCII (without communication packet structure)

4.4.4 BP1_write_compress (0x4C)

Seq	Cmd-code / Par-data	Descriptions
1	0x4C	Write compressed bit-map data to the VP_BP1
2	Addr3(MSB)	VP_BP1 Address = 0x040000 ~ 0x05FFFF
3	Addr2	
4	Addr1	
5	Addr0(LSB)	
6	Length3(MSB)	the number of data
7	Length2	Length = 1 ~ 98304
8	Length1	
9	Length0(LSB)	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)
*2. After the above command issued, it follow with the compressed data byte with out communication packet structure.
*3. over all command flow

HOST	Flow	module
BP1_write Command (in communication packet structure)	→	Instruct to wait for data….
compressed 1bpp image data (without communication packet structure)	→	Store the data into VP_BP1
	←	Response code ":>" in ASCII (without communication packet structure)

4.4.5 G16_write (0x4D)

Seq	Cmd-code / Par-data	Descriptions
1	0x4D	Write graph values to the VP_G16 array
2	Addr1_H	VP_G16 Address = 0x060000 ~ 0x07FFFF
3	Addr1l	
4	Addr2h	
5	Addr2l	
6	Sizeh	Array-size = 1 ~ 1024
7	Sizel	(*2, *3)
8	Data(MSB)	16 bit data array
9	Data(LSB)	(no. of byte = 2x array-size)
10	Data(MSB)	
11	Data(LSB)	
⋮	⋮	
⋮	⋮	
⋮	⋮	
⋮	⋮	
⋮	⋮	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)
*2. Array-size = no. of 16bit values
*3. Array-size suggest to be same at the size value defined in TML editor

4.4.6 G16_write_rotate (0x4E)

Seq	Cmd-code / Par-data	Descriptions
1	0x4E	Write graph values to the last position of VP_G16 array with rotation effect
2	Addr1_H	VP_G16 Address = 0x060000 ~ 0x07FFFF
3	Addr1_L	
4	Addr2_H	
5	Addr2_L	
6	Size_H	Array-size to be rotate = 1 ~ 65535
7	Size_L	(*2. *3)
8	Data(MSB)	16 bit data value to be add to the end-of-array
9	Data(LSB)	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)
*2. Array-size = no. of 16bit values
*3. Array-size suggest to be same at the value defined in TML editor

4.4.7 System Register Write (0x3B)

seq	Cmd-code / Par-data	Descriptions
1	0x3B	System Register Write Command
2	Addr3(MSB)	Timer_Ctrl0 Address = 0xFFFF00
3	Addr2	
4	Addr1	Timer_Ctrl7 Address = 0xFFFF07
5	Addr0(LSB)	
6	Data	the value to write

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

URL: www.topwaydisplay.com
www.topwaysz.com
Document Name:SMART LCD Command v5.04 Manual Rev0.4.doc
Page: 15 of 19

4.4.8 System Register Read (0x3C)

seq	Cmd-code / Par-data	Descriptions
1	0x3C	System Register Read Command
2	Addr3(MSB)	Address = 0xFFFF00
3	Addr2	:
4	Addr1	Address = 0xFFFFFF
5	Addr0(LSB)	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

Response code:

Seq.	Content	Byte in Hex	Descriptions
1st	Header	0xAA	Communication packet header
2nd	Command	0x3C	Command executed
3rd		Addr3(MSB)	Address = 0xFFFF00
4th	Address	Addr2	:
5th		Addr1	Address = 0xFFFFFF
6th		Addr0(LSB)	
7th	Data	Data(1Byte)	the value of the register
8th		0xCC	
9th	Tail	0x33	Communication packet tail
10th		0xC3	
11th		0x3C	

Note.
*1. The Response code with communication packet format (see Communication Packet Structure Section for details)
*2. When Timer reach the 0x00000000 or 0x7FFFFFFF, a notification will be provided a 0x77 response code with the corresponding Timer Address and Value.(See touch_response(0x77)for details)

4.4.9 STR_write (0x42)

Seq	Cmd-code / Par-data	Descriptions
1	0x42	Write string to VP_STR
2	Addr3(MSB)	the VP_STR Address = 0x00000 ~ 0x01FFFF
3	Addr2	(each VP_STR = 128 bytes)
4	Addr1	(address value must be divisible by 128)
5	Addr0(LSB)	
6	data	String to write
:	:	Total no. of byte in string ≤128
:	:	
:	'\0'	'\0'(0x00): string end mark

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

4.4.10 STR_read (0x43)

Seq	Cmd-code / Par-data	Descriptions
1	0x43	Read string from VP_STR
2	Addr3(MSB)	the VP_STR Address = 0x00000 ~ 0x01FFFF
3	Addr2	(each VP_STR = 128 bytes)
4	Addr1	(address value must be divisible by 128)
5	Addr0(LSB)	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

Response code:

Seq.	Content	Byte in Hex	Descriptions
1st	Header	0xAA	Communication packet header
2nd	Command	0x43	Command executed
3rd	String data	data	String code
:		:	
:		:	
:	\0	0x00	"\0'(0x00): string end mark
:	Tail	0xCC	Communication packet tail
:		0x33	
:		0xC3	
:		0x3C	

Note.
*1. The Response code with communication packet format (see Communication Packet Structure Section for details)

URL: www.topwaydisplay.com
www.topwaysz.com
Document Name:SMART LCD Command v5.04 Manual Rev0.4.doc
Page: 16 of 19

4.4.11 STR_fill (0x46)

Seq	Cmd-code / Par-data	Descriptions
1	0x46	Write string to VP_STR
2	Addr3(MSB)	he VP_STR Address = 0x00000 ~ 0x01FFFF
3	Addr2	(each VP_STR = 128 bytes)
4	Addr1	(address value must be divisible by 128)
5	Addr0(LSB)	
6	Lengthh	the number of VP_STR (including the start address) to be filled
7	Lengthl	Length = 1 ~ 1024
8	data	String to write
:	:	Total no. of byte in string ≤128
:	:	
:	'\0'	'\0'(0x00): string end mark

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

4.4.12 N16_write (0x3D)

Seq	Cmd-code / Par-data	Descriptions
1	0x3D	Write 16bit number to VP_N16
2	Addr3(MSB)	VP_N16 Address = 0x080000 ~ 0x08FFFF
3	Addr2	(each VP_N16 = 2 byte)
4	Addr1	(address value must be divisible by 2)
5	Addr0(LSB)	
6	High Byte	The 16 bit value to write
7	Low Byte	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

4.4.13 N16_read (0x3E)

Seq	Cmd-code / Par-data	Descriptions
1	0x3E	Read 16bit number from VP_N16
2	Addr3(MSB)	VP_N16 Address = 0x080000 ~ 0x08FFFF
3	Addr2	(each VP_N16 = 2 byte)
4	Addr1	(address value must be divisible by 2)
5	Addr0(LSB)	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details

Response code:

Seq.	Content	Byte in Hex	Descriptions
1st	Header	0xAA	Communication packet header
2nd	Command	0x3E	Command executed
3rd	N16 value	Data1(MSB)	16 bit value
4th		Data0(LSB)	
5th	Tail	0xCC	Communication packet tail
6th		0x33	
7th		0xC3	
8th		0x3C	

Note.
*1. The Response code with communication packet format (see Communication Packet Structure Section for details)

4.4.14 N16_fill (0x3F)

Seq	Cmd-code / Par-data	Descriptions
1	0x3F	Fill 16bit number to the VP_N16
2	Addr3(MSB)	VP_N16 Address = 0x080000 ~ 0x08FFFF
3	Addr2	(each VP_N16 = 2 byte)
4	Addr1	(address value must be divisible by 2)
5	Addr0(LSB)	
6	Lengthh	the number of VP_N16 (including the start address) to be filled
7	Lengthl	Length = 1 ~ 32768
8	High Byte	the 16 bit value to fill
9	Low Byte	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

4.4.15 N32_write (0x44)

Seq	Cmd-code / Par-data	Descriptions
1	0x44	Write 32bit number to VP_N32
2	Addr3(MSB)	VP_N32 Address = 0x020000 ~ 0x02FFFF
3	Addr2	(each VP_N32 = 4 byte)
4	Addr1	(address value must be divisible by 4)
5	Addr0(LSB)	
6	Data3(MSB)	the 32 bit no. value write.
7	Data2	
8	Data1	
9	Data0(LSB)	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

4.4.16 N32_read (0x45)

Seq	Cmd-code / Par-data	Descriptions
1	0x45	Read 32bit number from VP_N32
2	Addr3(MSB)	VP_N32 Address = 0x020000 ~ 0x02FFFF
3	Addr2	(each VP_N32 = 4 byte)
4	Addr1	(address value must be divisible by 4)
5	Addr0(LSB)	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details

Response code:

Seq.	Content	Byte in Hex	Descriptions
1st	Header	0xAA	Communication packet header
2nd	Command	0x45	Command executed
3rd	N32 value	Data3(MSB)	32 bit value
4th		Data2	
5th		Data1	
6th		Data0(LSB)	
7th	Tail	0xCC	Communication packet tail
8th		0x33	
9th		0xC3	
10th		0x3C	

Note.
*1. The Response code with communication packet format (see Communication Packet Structure Section for details)

4.4.17 N32_fill (0x47)

Seq	Cmd-code / Par-data	Descriptions
1	0x47	Fill 32bit number to the VP_N32
2	Addr3(MSB)	VP_N32 Address = 0x020000 ~ 0x02FFFF
3	Addr2	(each VP_N32 = 4 byte)
4	Addr1	(address value must be divisible by 4)
5	Addr0(LSB)	
6	Lengthh	the number of VP_N32 (including the start address) to be filled
7	Lengthl	Length = 1 ~ 16384
8	Data3(MSB)	the 32 bit no. value to fill
9	Data2	
10	Data1	
11	Data0(LSB)	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

4.4.18 N64_write (0x48)

Seq	Cmd-code / Par-data	Descriptions
1	0x48	Write 64bit number to VP_N64
2	Addr3(MSB)	VP_N64 Address= 0x030000 ~ 0x03FFFF
3	Addr2	(each VP_N64 = 8 byte)
4	Addr1	(address value must be divisible by 8)
5	Addr0(LSB)	
6	Data7(MSB)	the 64bit no. value write.
7	Data6	
⋮	⋮	
12	Data1	
13	Data0(LSB)	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

4.4.19 N64_read (0x49)

Seq	Cmd-code / Par-data	Descriptions
1	0x49	Read 64bit number from VP_N64
2	Addr3(MSB)	VP_N64 Address= 0x030000 ~ 0x03FFFF
3	Addr2	(each VP_N64 = 8 byte)
4	Addr1	(address value must be divisible by 8)
5	Addr0(LSB)	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details

Response code:

Seq.	Content	Byte in Hex	Descriptions
1st	Header	0xAA	Communication packet header
2nd	Command	0x49	Command executed
3rd	N64 value	Data7(MSB)	64 bit value
4th		Data6	
⋮		⋮	
9th		Data1	
10th		Data0(LSB)	
11th	Tail	0xCC	Communication packet tail
12th		0x33	
13th		0xC3	
14th		0x3C	

Note.
*1. The Response code with communication packet format (see Communication Packet Structure Section for details)

4.4.20 N64_fill (0x4A)

Seq	Cmd-code / Par-data	Descriptions
1	0x4A	Fill 64bit number to the VP_N64
2	Addr3(MSB)	VP_N64 Address= 0x030000 ~ 0x03FFFF
3	Addr2	(each VP_N64 = 8 byte)
4	Addr1	(address value must be divisible by 8)
5	Addr0(LSB)	
6	Lengthh	the number of VP_N64 (including the start address) to be filled
7	Lengthl	Length = 1 ~ 8192
8	Data7(MSB)	the 64 bit no. value to fill
9	Data6	
⋮	⋮	
14	Data1	
15	Data0(LSB)	

Note.
*1. Command should be transferred in communication packet structure (see Communication Packet Structure Section for details)

K1 Terminal	
No	Pin Name
1	VSS
2	NC
3	RTX(BUSY)
4	TX
5	RX
6	VDD

200.0
(2-4.3)
(22.26)
(155.48(V.A.))
(22.96)
154.08(A.A.)
42.0
116.0
(6-20.4)
(4-4.3)
(16.98)
(17.68)
30.0
2.1(Silicon Ring)
(6.5MAX.)(*8)
(21.5)
5.7
2-62.5
113.6

800×480 Pixels

125.0
(87.32(V.A.))
85.92(A.A.)
1.86

56.0
119.0

5.7
188.6
Phoenix MC 1.5/6-ST-3.5-1840405
or equivalent
K1
Mini USB
(39.3)
(59.5)

6-(1.6x2.5)
P3.5x(6-1)=17.5

K1 Details
Scale=2/1

Note:
*1. LCD Display Type: TFT.Transmissive
*2. Pixel Arrangment: RGB-STRIPE
*3. Color Depth : 65k Colors
*4. Operating Voltage : 11.0~26.0V
*5. Backlight : White LED
*6. K1 User Interface : RS-232C
*7. Touch Panel Type : Resistive Touch Panel
*8. Operating Temperature : -20°C~70°C
*9. Storage Temperature : -30°C~80°C
*10. Applicable assemble panel thickness = 6.5MAX.

B		
A		
Rev	Note	Date

Dwg Title
HKT070DTA-1C Outline Dwg

Dwg No.
MK-005965-1-1

Date
2017-02-17

Scale 4/5	Tol. ±0.5	Unit mm	Paper Size A3	
Approved		Checked		Drawn HeHongLiang

TOPWAY