

SwellRight Ultra Packer

Swellable Packer System for Zonal Isolation

SwellRight Ultra packer offers a cost-effective solution for high pressure applications.

SwellRight Ultra packer provides the highest pressure rating on the swellable market. With 2000psi/ft, TAQA's 5ft high pressure packers can withstand pressures up to 10,000psi, enabling the customer to utilize smaller pup joints. TAQA's packers can effectively reduce the amount of rubber element required for high pressure applications, for use in horizontal and vertical wells.

Utilising TAQA's patented technology, the high pressure packers can be used in applications between 0°C and 150°C, and are available in both oil and water swell compounds.

SwellRight packers are shipped from TAQA's manufacturing plant to the well site or customer's warehouse where they are delivered in a 'ready-to-run' condition, keeping rig time costs minimal.

Features

- Patented back-up element design provides highest pressure rating on the market
- Anti-extrusion end-rings
- Available in oil or water swell elements

Benefits

- Ready-to-run reducing rig time
- Can be run in horizontal or vertical wells
- Can utilise shorter packer lengths to maintain high pressure

Technical Specifications

Base pipe Size	4.500	5.500	6.625	7.000
Rubber OD	5.625 - 5.750	8.000 - 8.250	8.000 - 8.250	8.500 - 8.750
Sealing ID Range	6.000 - 6.125	8.125 - 8.500	8.125 - 8.500	8.625 - 9.000





