

Selector	Example	Selects
<u>*</u>	\$("#*")	All elements
<u>#id</u>	\$("#lastname")	The element with id="lastname"
<u>.class</u>	\$(".intro")	All elements with class="intro"
<u>.class,.class</u>	\$(".intro,.demo")	All elements with the class "intro" or "demo"
<u>element</u>	\$("#p")	All <p> elements
<u>el1,el2,el3</u>	\$("#h1,div,p")	All <h1>, <div> and <p> elements
<u>:first</u>	\$("#p:first")	The first <p> element
<u>:last</u>	\$("#p:last")	The last <p> element
<u>:even</u>	\$("#tr:even")	All even <tr> elements
<u>:odd</u>	\$("#tr:odd")	All odd <tr> elements
<u>:first-child</u>	\$("#p:first-child")	All <p> elements that are the first child of their parent
<u>:first-of-type</u>	\$("#p:first-of-type")	All <p> elements that are the first <p> element of their parent
<u>:last-child</u>	\$("#p:last-child")	All <p> elements that are the last child of their parent
<u>:last-of-type</u>	\$("#p:last-of-type")	All <p> elements that are the last <p> element of their parent
<u>:nth-child(n)</u>	\$("#p:nth-child(2)")	All <p> elements that are the 2nd child of their parent
<u>:nth-last-child(n)</u>	\$("#p:nth-last-child(2)")	All <p> elements that are the 2nd child of their parent, counting from the last child
<u>:nth-of-type(n)</u>	\$("#p:nth-of-type(2)")	All <p> elements that are the 2nd <p> element of their parent
<u>:nth-last-of-type(n)</u>	\$("#p:nth-last-of-type(2)")	All <p> elements that are the 2nd <p> element of their parent, counting from the last child
<u>:only-child</u>	\$("#p:only-child")	All <p> elements that are the only child of their parent

<u>:only-of-type</u>	\$("#p:only-of-type")	All <p> elements that are the only child, of its type, of their parent
<u>parent > child</u>	\$("#div > p")	All <p> elements that are a direct child of a <div> element
<u>parent descendant</u>	\$("#div p")	All <p> elements that are descendants of a <div> element
<u>element + next</u>	\$("#div + p")	The <p> element that are next to each <div> elements
<u>element ~ siblings</u>	\$("#div ~ p")	All <p> elements that are siblings of a <div> element
<u>:eq(<i>index</i>)</u>	\$("#ul li:eq(3)")	The fourth element in a list (index starts at 0)
<u>:gt(<i>no</i>)</u>	\$("#ul li:gt(3)")	List elements with an index greater than 3
<u>:lt(<i>no</i>)</u>	\$("#ul li:lt(3)")	List elements with an index less than 3
<u>:not(<i>selector</i>)</u>	\$("#input:not(:empty)")	All input elements that are not empty
<u>:header</u>	\$("#:header")	All header elements <h1>, <h2> ...
<u>:animated</u>	\$("#:animated")	All animated elements
<u>:focus</u>	\$("#:focus")	The element that currently has focus
<u>:contains(<i>text</i>)</u>	\$("#:contains('Hello')")	All elements which contains the text "Hello"
<u>:has(<i>selector</i>)</u>	\$("#div:has(p)")	All <div> elements that have a <p> element
<u>:empty</u>	\$("#:empty")	All elements that are empty
<u>:parent</u>	\$("#:parent")	All elements that are a parent of another element
<u>:hidden</u>	\$("#p:hidden")	All hidden <p> elements
<u>:visible</u>	\$("#table:visible")	All visible tables
<u>:root</u>	\$("#:root")	The document's root element
<u>:lang(<i>language</i>)</u>	\$("#p:lang(de)")	All <p> elements with a lang attribute value starting with "de"

<u>[attribute]</u>	\$("#[href]")	All elements with a href attribute
<u>[attribute=value]</u>	\$("#[href='default.htm']")	All elements with a href attribute value equal to "default.htm"
<u>[attribute!=value]</u>	\$("#[href!='default.htm']")	All elements with a href attribute value not equal to "default.htm"
<u>[attribute\$=value]</u>	\$("#[href\$='.jpg']")	All elements with a href attribute value ending with ".jpg"
<u>[attribute =value]</u>	\$("#[title ='Tomorrow']")	All elements with a title attribute value equal to 'Tomorrow', or starting with 'Tomorrow' followed by a hyphen
<u>[attribute^=value]</u>	\$("#[title^='Tom']")	All elements with a title attribute value starting with "Tom"
<u>[attribute~=value]</u>	\$("#[title~='hello']")	All elements with a title attribute value containing the specific word "hello"
<u>[attribute*=value]</u>	\$("#[title*='hello']")	All elements with a title attribute value containing the word "hello"
<u>:input</u>	\$("#:input")	All input elements
<u>:text</u>	\$("#:text")	All input elements with type="text"
<u>:password</u>	\$("#:password")	All input elements with type="password"
<u>:radio</u>	\$("#:radio")	All input elements with type="radio"
<u>:checkbox</u>	\$("#:checkbox")	All input elements with type="checkbox"
<u>:submit</u>	\$("#:submit")	All input elements with type="submit"
<u>:reset</u>	\$("#:reset")	All input elements with type="reset"
<u>:button</u>	\$("#:button")	All input elements with type="button"
<u>:image</u>	\$("#:image")	All input elements with type="image"
<u>:file</u>	\$("#:file")	All input elements with type="file"
<u>:enabled</u>	\$("#:enabled")	All enabled input elements
<u>:disabled</u>	\$("#:disabled")	All disabled input elements
<u>:selected</u>	\$("#:selected")	All selected input elements
<u>:checked</u>	\$("#:checked")	All checked input elements