

# Artificial Neural Networks (ANNs)

## Introduction

**Sabah Sayed**

*Department of Computer Science*


*Faculty of Computers and Artificial Intelligence*

*Cairo University*

*Egypt*


# Why we need ANNs?

- There are some advanced operations (like face recognition, hand-writing recognition ... etc) that we can do using our brain, but we don't know how it is exactly/internally done.
- We used to successfully do these operations after sufficient amount of **training** and **practice**.
- Unfortunately, it is very hard to try writing such a program that can recognize faces or hand-written text.
- Here, the role of the ANNs comes, **It mimics the training activities that are internally done using the *Nerve System* inside the human brain!**
- Training occurs through learning from many **already-known past examples**.
- A well-trained ANN will be able to yield correct results for **new unknown problem instances**.



# Example: Hand-writing Recognition


- It is very hard to develop a program that tells what makes a 2





# The Brain

## The Brain as an Information Processing System

The human brain contains about **10 billion** nerve cells, or **neurons**. On average, each neuron is connected to other neurons through about **10 000** synapses.



# The Biological Neuron




- The brain is a collection of about 10 billion interconnected neurons. Each **neuron** is a cell that uses **biochemical reactions** to **receive**, **process** and **transmit** information.
- Each terminal button is connected to other neurons across a small gap called a **synapse**.





# ANNs

- ANNs incorporate the two fundamental components of biological neural networks:

1. Neurons (nodes)
2. Synapses (weights)





# Axon/Synapse vs. Weight







# Neuron vs. Node



# Structure of a node




Squashing/Activation function limits node output:



# A Neuron Model

- When a neuron receives *excitatory input* that is sufficiently large compared with its *inhibitory input*, it sends a spike of electrical activity down its axon.
- *Learning* occurs by changing the effectiveness of the synapses so that the influence of one neuron on another changes.




- We conduct these neural networks by first trying to deduce the essential features of neurons and their interconnections.
- We then typically program a computer to simulate these features.

# Definition of Neural Network

- A Neural Network is a **system** composed of **many simple processing elements operating in parallel** which can **acquire, store, and utilize** experiential knowledge.
- **Neural network:** *information processing paradigm inspired by biological nervous systems, such as our brain*
- Structure: large number of highly interconnected processing elements (*neurons*) working together
- Like people, they learn *from experience* (by example)

# The Key Elements of Neural Networks


- Neural computing requires a number of **neurons**, to be connected together into a **neural network**. Neurons are arranged in layers.





$$a = f(p_1w_1 + p_2w_2 + p_3w_3 + b) = f\left(\sum p_iw_i + b\right)$$

- Each **neuron** within the network is usually a **simple processing unit** which takes one or more inputs and produces an output.
- At each neuron, every input has an associated **weight** which modifies the strength of each input.
- The neuron simply adds together all the inputs and calculates an output to be passed on.


# ANN



# Diagram of a simple ANN




# Network Layers




- **Input Layer** - The activity of the input units represents the **raw information** that is fed into the network.
- **Hidden Layer** - The activity of each hidden unit is determined by:
  - The activities of the **input** units and
  - The **weights** on the connections between the input and the hidden units.
- **Output Layer** - The behavior of the output units depends on:
  - The activity of the **hidden** units and
  - The **weights** between the hidden and output units.




# Topologies of Neural Networks



*completely  
connected*



*feedforward  
(directed, a-cyclic)*



*recurrent  
(feedback connections)*

# History

- 1943: McCulloch–Pitts “neuron”
  - Started the field
- 1962: Rosenblatt’s perceptron
  - Learned its own weight values; convergence proof
- 1969: Minsky & Papert book on perceptrons
  - Proved limitations of single-layer perceptron networks
- 1982: Hopfield and convergence in symmetric networks
  - Introduced energy-function concept
- 1986: Backpropagation of errors
  - Method for training multilayer networks
- Present: Probabilistic interpretations, Bayesian and spiking networks

# Artificial Neural Networks vs. Computers

- Computers have to be explicitly programmed:
  - Analyze the problem to be solved.
  - Write the code in a programming language.
- Neural networks learn from examples:
  - No requirement of an explicit description of the problem.
  - No need for a programmer.
  - The neural network adapts itself during a *training period*, based on examples of similar problems even without a desired solution to each problem.
  - After sufficient training, the neural network is able to relate the problem data to the solutions, inputs to outputs, and it is then able to offer a viable solution to a brand new problem.
  - Able to generalize or to handle incomplete data.

# The ANN applications


- ***Classification, the aim is to predict the class of an input vector***
- ***Pattern matching, the aim is to produce a pattern best associated with a given input vector***
- ***Pattern completion, the aim is to complete the missing parts of a given input vector***
- ***Optimization, the aim is to find the optimal values of parameters in an optimization problem***
- ***Control, an appropriate action is suggested based on given an input vectors***
- ***Function approximation/times series modeling, the aim is to learn the functional relationships between input and desired output vectors;***
- ***Data mining, with the aim of discovering hidden patterns from data (knowledge discovery)***
- **Noise Reduction**

# Different types of Neural Networks

- **Feed-forward Neural Network: (FFNN)**

- It allows signals to travel **one way only**; from input to output.
- There is **no feedback** (loops) i.e. the output of any layer does not affect that same layer.
- It tends to be straight forward networks that associate inputs with outputs. They are extensively used in **pattern recognition**.
- This type of organization is also referred to as **bottom-up** or **top-down**.

- Single layer FFNN
- Multilayer FFNN




Single Layer FFNN

# Different types of Neural Networks

- **Feedback Neural Networks**

- Feedback networks can have signals traveling in both directions by introducing **loops** in the network.
- Feedback networks are **dynamic**; their 'state' is changing continuously until they reach an equilibrium point.
- They remain at the equilibrium point until the **input changes** and a new equilibrium needs to be found.
- Feedback architectures are also referred to as **interactive** or **recurrent**, although the latter term is often used to denote feedback connections in single-layer organizations.



# Feed-forward Neural Networks (FFNNs)

Information flow is **unidirectional**

Data is presented to *Input layer*


Passed on to *Hidden Layer*

Passed on to *Output layer*


Information is **distributed**

Information processing is **parallel**

Internal representation (interpretation) of data



# Feeding data through the Network



$$(1 \times 0.25) + (0.5 \times (-1.5)) = 0.25 + (-0.75) = -\mathbf{0.5}$$

Squashing:

$$\text{Sigmoid}(x) = \frac{1}{1 + e^{-x}} \qquad \frac{1}{1 + e^{0.5}} = 0.3775$$



# Phases and Data of an ANN

- Phases:
  - Learning (training)
    - Training can be done using **Back-propagation** technique (will be seen later).
    - Training is done using a big part of known historical (labeled) data.
      - The dataset contains both inputs and their corresponding output(s).
    - This phase is *time consuming*
  - Testing
    - Testing is done using the **Feed-forward** technique.
    - A small part of the historical data is used in this phase.
  - Execution
    - The **Feed-forward** technique is used.
    - New unlabeled data (inputs with unknown outputs) are fed to the NN.
- Labeled Data:
  - Data is usually given in one or more consistent dataset(s)
  - Data is divided into two parts:
    - One part for the **training/learning** phase
    - Another part for the **testing** phase

# Example: Pattern Recognition


- An important application of neural networks is pattern recognition. Pattern recognition can be implemented by using a feed-forward neural network that has been **trained** accordingly.
- During training, the network is trained to **associate outputs with input patterns**.
- When the network is used, it identifies the input pattern and tries to output the associated output pattern.
- The power of neural networks comes to life when a pattern that has no output associated with it, is given as an input.
- In this case, **the network gives the output that corresponds to a taught input pattern that is least different from the given pattern.**

# Pattern Recognition (cont.)




- Suppose a network is trained to recognize the patterns T and H.
- The associated patterns are all black and all white respectively as shown above.

# Pattern Recognition (cont.)




Since the input pattern looks more like a 'T', when the network classifies it, it sees the input closely resembling 'T' and outputs the pattern that represents a 'T'.

# Pattern Recognition (cont.)



The input pattern here closely resembles 'H' with a slight difference. The network in this case classifies it as an 'H' and outputs the pattern representing an 'H'.




# Pattern Recognition (cont.)



- Here the top row is 2 errors away from a 'T' and 3 errors away from an H. So the top output is a black.
- The middle row is 1 error away from both T and H, so the output is random.
- The bottom row is 1 error away from T and 2 away from H. Therefore the output is black.
- Since the input resembles a 'T' more than an 'H' the output of the network is in favor of a 'T'.

# Example

- ALVINN uses a learned ANN to steer an autonomous vehicle driving at normal speeds on public highways
  - Input to network: 30x32 grid of pixel intensities obtained from a forward-pointed camera mounted on the vehicle
  - Output: direction in which the vehicle is steered
  - Trained to mimic observed steering commands of a human driving the vehicle for approximately 5 minutes



# Issues to be discussed

- Initializing the weights.
- Use of a learning algorithm.
- Set of training examples.
- Encode the examples as inputs.
- Convert output into meaningful results.