Student Dashboard with Live Clock

Objective

Build a **Student Dashboard** application using Angular that demonstrates:

- @Input() (Parent → Child communication)
- @Output() (Child → Parent communication)
- Angular Lifecycle Hooks (ngOnInit, ngOnChanges, ngOnDestroy, ngAfterViewInit)
- Reusable Components
- ng-content

Requirements

1. App Component (Main Dashboard)

- Create an array of students:

```
students = [
  { id: 1, name: 'Sara', track: 'Frontend', grade: 85 },
  { id: 2, name: 'Ali', track: 'Backend', grade: 70 },
  { id: 3, name: 'Mona', track: 'UI/UX', grade: 90 }
];
```

- Display the students using a child component (StudentCardComponent)

---

2. Student Card Component (Reusable)

- Create a reusable component to display a single student

Requirements:

- Receive student data using @Input()
- Display:
  - Name
  - Track
  - Grade

Add buttons:

- **View Details** → sends selected student to parent

---

3. Component Communication

Child → Parent using @Output()

- Emit an event when:
    - View Details button is clicked (send student object)

Parent Responsibilities:

- Store and display the selected student

---

4. Student Details Component

- Create a component to display selected student details

Requirements:

- Receive student data using @Input()
- Display full student information
- Show only when a student is selected

---

5. Live Clock Component

Requirements:

- Create a component that displays the current time
- Update the time every second

Use Lifecycle Hooks:

- ngOnInit() → start the clock
- ngOnDestroy() → stop the interval
- ngAfterViewInit() → log when view is initialized
- ngOnChanges() → log when input changes (optional if you pass input)

Behavior:

- Add a navbar (student details - clock)

---

6. Reusable Wrapper Component (ng-content)

- Create a reusable component (e.g., CardWrapperComponent)
- Create a resuable Button

Requirements:

- Use <ng-content> to wrap dynamic content
- Style it as a reusable card layout

Example Usage:

```
<app-card-wrapper>
  <h3>Student Info</h3>
  <!-- dynamic content -->
</app-card-wrapper>
```