```cpp
#include<iostream>
using namespace std;

struct student
{
    int code;
    char name[80];
    float grade1;
    float grade2;
    int flag;
};
struct employee{
    int id;
     char name[80];
     float salary;
     int flag;
};
struct department
{
    int flag;
    union
    {
        student s;
        employee e;
    }person;
};
struct Node {
    department info;
    Node *next;
};

int main(){
    char c;
    int flag;
    Node *list, *temp;
    cout<<"if you want to enter data enter y: "<<endl;
    cin>>c;
    if(c!='y'){
        cout<<"thanks"<<endl;
        exit(0);
    }
    list = new Node;

        cout<<"0 - for student "<<endl;
        cout<<"1- for employee"<<endl;
        cout<<"Enter your choice: ";
```

```cpp
        cin>>flag;
        switch (flag){
         case 0:
              cout<<"please Enter student code: ";
              cin>>list->info.person.s.code;
              cout<<"please Enter student name: ";
              cin>>list->info.person.s.name;
              cout<<"please Enter student first grade: ";
              cin>>list->info.person.s.grade1;
              cout<<"please Enter student seconed grade: ";
              cin>>list->info.person.s.grade2;
               list->next = NULL;
              list->info.flag=0;
              break;
          case 1:
              cout<<"Enter employee id: ";
              cin>>list->info.person.e.id;
              cout<<"Enter employee name: ";
              cin>>list->info.person.e.name;
              cout<<"Enter employee salary: ";
              cin>>list->info.person.e.salary;
              list->next = NULL;
              list->info.flag=1;

              break;

                   default:
        cout << "Error Invalid!" << endl;
        break;
         }

        cout<<"if you want to enter data enter y: "<<endl;
        cin>>c;
        temp = list;

    while (c == 'y'){
       temp->next = new Node;
       temp = temp->next;
       cout<<"0 - for student "<<endl;
       cout<<"1- for employee"<<endl;
       cout<<"Enter your choice: ";
       cin>>flag;
       switch (flag)
       {
       case 0:
            cout<<"please Enter student code: ";
```

```cpp
                    cin>>temp->info.person.s.code;
                    cout<<"please Enter student name: ";
                    cin>>temp->info.person.s.name;
                    cout<<"please Enter student first grade: ";
                    cin>>temp->info.person.s.grade1;
                    cout<<"please Enter student seconed grade: ";
                    cin>>temp->info.person.s.grade2;
                temp->next = NULL;
                temp->info.flag = 0;
                break;
            case 1:
                    cout<<"Enter employee id: ";
                    cin>>temp->info.person.e.id;
                    cout<<"Enter employee name: ";
                    cin>>temp->info.person.e.name;
                    cout<<"Enter employee salary: ";
                    cin>>temp->info.person.e.salary;
                temp->next = NULL;
                temp->info.flag = 1;
                break;
            default:
                    cout << "Error Invalid!" << endl;
                    break;
            }
    cout << "If you want to Enter anothor info type y : ";
    cin >> c;
        }

        cout<<endl<<"Displaying department Record: "<<endl;
            temp = list;
        while(temp!=NULL)
        {
            switch(temp->info.flag)
            {
            case 0:
         cout<<"stutent record : "<<endl;
          cout<<"Code : "<<temp->info.person.s.code<<endl;
         cout<<"Name : "<<temp->info.person.s.name<<endl;
         cout<<"F grade : "<<temp->info.person.s.grade1<<endl;
         cout<<"S grade : "<<temp->info.person.s.grade2<<endl;
                    cout<<endl;
                        break;
            case 1:
                cout<<"employee record : "<<endl;
                 cout<<"id : "<<temp->info.person.e.id<<endl;
                 cout<<"Name : "<<temp->info.person.e.name<<endl;
```

```cpp
            cout<<"Salary : "<<temp->info.person.e.salary<<endl;
                        cout<<endl;
                        break;
            }
            temp = temp->next;
      }

      return 0;
}
```

------- OutPut-------