



TAHSEEEL MERCHANT API VERSION 1.0

1. CREATE ORDER:

API POST URL:

<https://lounge.tahseeel.com/api/?p=order>

Parameters:

Param	Details
uid *	UserID of Merchant. Will be supplied by Tahseeel.
pwd *	Password of Merchant. Will be supplied by Tahseeel.
secret *	Secret Key of Merchant. Will be supplied by Tahseeel.
order_no *	Order Number of your e-commerce portal.
order_amt *	Order Amount in KWD upto 3 decimals.
delivery_charges *	Delivery Charges. Amount in KWD upto 3 decimals.
total_items *	Integer Value of Total Number of items in cart.
cust_name *	Name of the Customer.
cust_email	Email ID of the customer. Email/Mobile, anyone is required.
phone_code	Country Code of Phone number. Supply this with Mobile Number.
cust_mobile	Mobile Number of the customer. Email/Mobile, anyone is required.
callback_url *	Callback URL to which Tahseeel should redirect after the payment.
knet_allowed *	KNET should be allowed for this payment? 0 for NO, 1 for YES.
cc_allowed *	CreditCard should be allowed for this payment? 0 for NO, 1 for YES.
remarks:	Any remarks you want to add to this particular payment.

* REQUIRED

Responses:

JSON Response	Details
<code>{"error":true,"msg":"Please select an appropriate API function name. Or contact administrator for latest API documentation."}</code>	ERROR. Specify p=order.
<code>{"error":true,"msg":"Please submit appropriate data."}</code>	ERROR. Specify POST data.
<code>{"error":true,"msg":"Please provide API's Username (uid) to access API."}</code>	ERROR. Specify uid param.
<code>{"error":true,"msg":"Please provide API's Password (pwd) to access API."}</code>	ERROR. Specify pwd param.
<code>{"error":true,"msg":"Please provide API's Secret Key (secret) to access API."}</code>	ERROR. Specify secret param.
<code>{"error":true,"msg":"API access is not allowed. Please contact the administrator."}</code>	ERROR. Contact admin. Your API is not enabled yet.
<code>{"error":true,"msg":"No such API credentials found."}</code>	ERROR. Please check with admin for API credentials.
<code>{"error":true,"msg":"Please provide 'order_no'."}</code>	ERROR. Specify order_no param
<code>{"error":true,"msg":"Please provide 'cust_name'."}</code>	ERROR. Specify cust_name param
<code>{"error":true,"msg":"Please provide 'order_amt'."}</code>	ERROR. Specify order_amt param
<code>{"error":true,"msg":"Please provide 'delivery_charges'."}</code>	ERROR. Specify delivery_charges param
<code>{"error":true,"msg":"Please provide 'total_items'."}</code>	ERROR. Specify total_items param
<code>{"error":true,"msg":"Please provide 'cust_email' or 'cust_mobile'."}</code>	ERROR. Specify cust_email/cust_mobile param
<code>{"error":true,"msg":"Please provide 'callback_url'."}</code>	ERROR. Specify callback_url param
<code>{"error":true,"msg":"Please provide 'knet_allowed'."}</code>	ERROR. Specify knet_allowed param
<code>{"error":true,"msg":"Please provide 'cc_allowed'."}</code>	ERROR. Specify cc_allowed param
<code>{"error":true,"msg":"Error: <DATABASE_ERROR>" }</code>	ERROR. Some database issue. Report to TAHSEEEL admin.
<code>{"error":false,"msg":"Order saved successfully.", "link":"<TAHSEEEL_ORDER_PAYMENT_LINK>"}</code>	SUCCESS. Redirect user to the LINK returned in this response.

API Example:

POST:

https://lounge.tahseeel.com/api/?p=order&uid=USERNAME&pwd=PASSWORD&secret=SECRETKEY&cust_name=John&cust_email=johndoe@gmail.com&order_amt=100&delivery_charges=10&order_no=abcd1234&total_items=3&callback_url=google.com&knet_allowed=1&cc_allowed=1

RESPONSE:

```
{ "error":false, "msg":"Order saved successfully.",  
  "link":"https://lounge.tahseeel.com/o/?id=11&hash=592081b9e1150" }
```

Redirect User to this URL and there he/she can make the payment. TAHSEEEL will redirect user to your site with all response parameters of payment, it FAILED or was SUCCESSFUL.

CALL BACK RESPONSE:

1. If User Cancels on this page, he/she will be redirected to:

<http://google.com?cancelled=1>

2. If User Goes for the payment, he/she will be redirected to:

http://google.com?cancelled=0&hash=cf5f5fdr4ht6&inv_id=12&tx_date=20%20JAN%202017%2012:17:59&tx_amt=110&Result=CAPTURED&PaymentID=2131231232131233&PostDate=2005&TranID=324234324&Auth=232&Ref=213123213&tx_id=223&tx_mode=KNET&tx_status=PAID

PARAM	DETAILS
cancelled	0 for user cancelled. 1 for proceed with payment.
hash	Unique hash id for the invoice.
inv_id	Invoice id for merchant and customer to be shown in the lounge.
tx_date	Transaction Date by the customer.
tx_amt	Transaction Amount.
tx_id	Transaction ID on TAHSEEEL server.
tx_mode	KNET or CC for CreditCard.
tx_status	PAID, FAILED, REDIRECTED, EXPIRED, UNPAID.
result	Result from KNET/CC transaction.
PaymentID	PaymentID from KNET/CC transaction.
PostDate	PostDate from KNET/CC transaction.
TranID	Transaction ID from KNET/CC transaction.
Auth	Auth Code from KNET/CC transaction.
Ref	RefNo from KNET/CC transaction.

2. GET ORDER INFO:

API POST URL:

https://lounge.tahseeel.com/api/?p=order_info

Parameters:

Param	Details
uid *	UserID of Merchant. Will be supplied by Tahseeel.
pwd *	Password of Merchant. Will be supplied by Tahseeel.
secret *	Secret Key of Merchant. Will be supplied by Tahseeel.
id *	inv_id received in above URL.
hash *	hash received in above URL.

* REQUIRED

Responses:

JSON Response	Details
{"error":true,"msg":"Please select an appropriate API function name. Or contact administrator for latest API documentation."}	ERROR. Specify p=order_info.
{"error":true,"msg":"Please submit appropriate data."}	ERROR. Specify POST data.
{"error":true,"msg":"Please provide API's Username (uid) to access API."}	ERROR. Specify uid param.
{"error":true,"msg":"Please provide API's Password (pwd) to access API."}	ERROR. Specify pwd param.
{"error":true,"msg":"Please provide API's Secret Key (secret) to access API."}	ERROR. Specify secret param.
{"error":true,"msg":"API access is not allowed. Please contact the administrator."}	ERROR. Contact admin. Your API is not enabled yet.
{"error":true,"msg":"No such API credentials found."}	ERROR. Please check with admin for API credentials.
{"error":true,"msg":"Please provide 'id'."}	ERROR. Specify id param
{"error":true,"msg":"Please provide 'hash'."}	ERROR. Specify hash param
For success see RESPONSE in axample below.	SUCCESS. See response in below example.

API Example:

POST:

http://lounge.tahseeel.com/api/?p=order_info&uid=USERNAME&pwd=PASSWORD&secret=SECRETKEY&id=11&hash=592081b9e1150

RESPONSE:

```
{
  "created_dt":"Sat, 20-May-2017 10:49:45", // When this order was created
  "order_no":"abcd1234", // What was the order number
  "inv_id":"11", // What was the invoice ID
  "hash":"592081b9e1150", // The invoice hash
  "cust_name":"John", // Customer Name
  "cust_email":"johndoe@gmail.com", // Customer Email
  "cust_mobile":"", // Customer Email
  "order_amt":"200.0000", // Order Amount
  "delivery_charges":"10.0000", // Delivery Charges
  "total_items":"3", // Total Items
  "remarks":"", // Remarks
  "callback_url":"google.com", // CALLBACK URL
  "invoice_type":"OrderAPI", // Invoice Type Static. OrderAPI
  "status":"Unpaid (1)", // Status and No.of views in brackets
  "TxInfo": // If TX is attempted, detailed info
  [
    "tx_id" => "12", // TAHSEEEL TX ID
    "amt" => "110.350", // Amount
    "type" => "KNET", // KNET or CC
    "PaymentID" => "212321312312", // PaymentID from KNET/CC
    "Result" => "CAPTURED", // CAPTURED or NOT CAPTURED from KNET/CC
    "PostDate" => "2005", // PostDate from KNET/CC
    "TranID" => "2333", // TranID from KNET/CC
    "Auth" => "4234", // Auth Code from KNET/CC
    "Ref" => "324244324", // Ref No from KNET/CC
    "TrackID" => "23324", // TrackID from KNET/CC
    "UDF1" => "", // UDF1 from KNET/CC
    "UDF2" => "", // UDF2 from KNET/CC
    "UDF3" => "", // UDF3 from KNET/CC
    "UDF4" => "", // UDF4 from KNET/CC
    "UDF5" => "", // UDF5 from KNET/CC
    "tx_status" => "SUCCESS", // Initiated, Redirected, Error, SUCCESS, FAILED
    "tx_dt" => " Sat, 20-May-2017 10:49:45", // Transaction Time
  ]
}
```