
# **PRODUCT DATA**

## **VALVES**

## **PVC-U SINGLE UNION CHECK VALVE**

### **NEW**





Code	Size DN	Dimensions (mm)						Nominal Pressure	Minimum Opening
		D	dO	d1	d2	Т	L	PN(kg/cm²)	Pressure PN(kg/cm²)
503010100301	15(20)	47.00	26.90	20.30	19.95	16.50	77.50	PN10	0.1 5-0.3
503010100302	20(25)	53.90	32.50	25.30	24.95	19.00	94.50	PN10	0.15-0.3
503010100303	25(32)	67.00	40.30	32.30	31.90	22.50	111.00	PN10	0.15-0.3
503010100304	32(40)	78.50	49.40	40.35	39.90	26.50	129.00	PN10	0.1 5-0.3
503010100305	40(50)	93.20	61.60	50.35	49.90	31.50	143.00	PN10	0.1 5-0.3
503010100306	50(63)	110.60	73.40	63.40	62.90	36.70	154.70	PN10	0.15-0.3
503010100307	65(75)	130.60	89.60	75.40	74.90	44.00	185.40	PN10	0.1 5-0.3
503010100308	80(90)	148.40	105.50	90.50	89.90	51.50	21 3.70	PN10	0.15-0.3
503010100309	100(110)	173.40	126.50	110.60	109.90	61.50	238.40	PN10	0.15-0.3

#### **Valve Description**

- 1. Material: PVC-U
- 2. Size: DN15-100
- 3. Standard: DIN
- 4. Connection: Socket
- 5. Color: Dark Gray

#### **Product Features**

- 1. Meet drinking water standards.
- 2. Solid inner ball, good water stop effect.
- 3. Parts can be replaced, simple and economical.
- 4. The material is nano-modified to improve the pressure resistance and impact resistance of the product.
- 5. Thickened valve body for high compression resistance.
- 6. Valve factory 100% pressure test.

01	raucet	1	FVC-U
02	Nut	1	PVC-U
03	Rubber Ring	1	EPDM
04	Located Ring	1	PVC-U
05	Ball	1	PVC-U
06	Body	1	PVC-U

