
PRODUCT DATA

VALVES

PVC-U THREADED TRUE UNION CHECK VALVE








Code	Size DN	Dimensions (mm)							Nominal Pressure	
		D	d0	d1	d2	Т	L	Tr	s	PN(kg/cm²)
503010100101	15(20)	51.50	27.40	20.95	18.63	17.00	95.80	1/2"	3.58	PN10
503010100102	20(25)	59.00	32.70	26.44	24.12	19.50	109.58	3/4"	3.58	PN10
503010100103	25(32)	70.00	41.30	33.25	30.29	23.00	123.10	1"	3.58	PN10
503010100104	32(40)	85.40	49.60	41.91	38.95	27.00	147.50	1-1/4"	3.58	PN10
503010100105	40(50)	98.90	60.20	47.80	44.85	32.00	159.50	1-1/2"	3.58	PN10
503010100106	50(63)	122.20	76.00	59.61	56.66	38.50	184.80	2"	3.58	PN10
503010100107	65(75)	158.60	89.60	75.18	74.23	44.50	233.50	2-1/2"	3.58	PN10
503010100108	80(90)	192.10	105.40	87.88	84.93	52.00	255.00	3"	3.58	PN10
503010100109	100(110)	223.60	128.40	113.03	110.07	62.00	297.50	4"	3.58	PN10

Code	Size DN	Dimensions (mm)							Nominal Pressure	
		D	d0	d1	d2	Т	L	Tr	s	PN(kg/cm²)
503010100201	1/2"	51.50	27.40	20.95	18.63	17.00	95.80	1/2"	3.58	PN10
503010100202	3/4"	59.00	32.70	26.44	24.12	19.50	109.58	3/4"	3.58	PN10
503010100203	1"	70.00	41.30	33.25	30.29	23.00	123.10	1"	3.58	PN10
503010100204	1-1/4"	85.40	49.60	41.91	38.95	27.00	147.50	1-1/4"	3.58	PN10
503010100205	1-1/2"	98.90	60.20	47.80	44.85	32.00	159.50	1-1/2"	3.58	PN10
503010100206	2"	122.20	76.00	59.61	56.66	38.50	184.80	2"	3.58	PN10
503010100207	2-1/2"	158.60	89.60	75.18	74.23	44.50	233.50	2-1/2"	3.58	PN10
503010100208	3"	192.10	105.40	87.88	84.93	52.00	255.00	3"	3.58	PN10
503010100209	4"	223.60	128.40	113.03	110.07	62.00	297.50	4"	3.58	PN10

N0.	Name	Quantity	Material		
01	Faucet	2	PVC-U		
02	Nut	2	PVC-U		
03	Body	1	PVC-U		
04	Washer	1	PVC-U		
05	Rubber ring	1	EPDM		
06	Location Ring	1	PVC-U		
07	Ball	1	PVC-U		
08	O-Ring	2	EPDM		





Valve Description

- 1. Material: PVC-U
- 2. Size: DN15-100 1/2" -4"
- 3. Standard: DIN, ASTM
- 4. Connection: Threaded
- 5. Color: Dark Gray

Product Features

- 1. Simple economy.
- 2. The material is nano-modified to improve the pressure resistance and impact resistance of the product.
- 3. Thickened valve body for high compression resistance.
- 4. Valve factory 100% pressure test.
- 5. The body and seal are specially treated for better performance actuator performs 500,000 opening and closing tests